

# E CONTRACTOR E CATALOG

MECHO

# EFHD.

ECHO has been a leading innovator and manufacturer of professional-grade outdoor power equipment in North America since 1972. ECHO equipment is a favorite choice of green space professionals including commercial and residential landscapers, parks and rec departments, golf courses, municipalities, tree care and arborists.

ECHO's line-up includes Grass Trimmers, Chain Saws, Blowers, Hedge Trimmers, Edgers and Brushcutters complemented by a complete offering of Accessories and Genuine Replacement Parts to keep your equipment functioning for years. Due to our commitment to quality, your ECHO equipment is durable and will last season after season. Our outstanding commercial warranty - 2 years for all models except chain saws and cut-off saws which are 1 year - backs up the confidence we have in every piece of equipment. Our consumer warranty is 5 years on all models.

Headquartered in the Chicago area, ECHO sells its products in North America. Most independent dealers have trained sales and service professionals ready to help you find the ECHO equipment that is right for you. From establishing technological advancements in premium tools for landscaping and arborist professionals, to expanding its capabilities to meet industrial and consumer demand, ECHO has a heritage rich in accomplishment. The company prides itself on setting the industry standard with its dedication to new technology and quality products.

### **USAGE ICONS**

Look for these icons throughout the catalog as a visual indication on the recommended use for individual models.

### **Trimmers**

**Blowers** 



Medium Trimming 



### Heavy Trimming

### Brushcutters









**Medium Blowing** 











Heavy Blowing

### **Hedge Trimmers**

Small Hedges

✓ Light Blowing





(((=+;[])

# CONTENTS

eries		. 4
		. 6
ters		10
		12
Vac		15
Chain Saws		16
dle Chain Saws		18
aw		21
uners <sup>®</sup>		22
		24
mmers		26
hment Series <sup>™</sup>		28
finer		
		32
less		34
rills		36
S		36
Augers		
tivator	241	133
ls		37
Dr™	N. N. N.	38
ricant		39
ies.		40
tions		54
A REAL PROPERTY OF A REAL PROPER		



# **ECHO X SERIES - BEST-IN-CLASS PRODUCTS**

# WHAT DOES THE ECHO X SERIES DESIGNATION MEAN?

The ECHO X Series represents our best-in-class products designed for the professional user. Professional users of outdoor power equipment know that when there's work to be done, the only way to get it done is by relying on the best equipment on the market. You depend upon performance and durability because your livelihood depends on productivity and efficiency. The X Series label identifies ECHO's most powerful, lightweight and most productive products.

Committed to providing pro users what they demand, the ECHO X Series is ever-expanding, with recent introductions bringing the line-up to 28 individual models. Each model has specific features designed to help green space professionals perform their jobs quickly and efficiently. Look for the ECHO X Series logo throughout the catalog to identify models in the series.

Quick and easy start-ups, durability, long run time - season after season - performance that allows you to get one job done and keep moving to the next. Superior work demands superior products which leads to customer satisfaction and repeat business. After all, if your equipment doesn't work, neither do you. You need dependability. And at the end of the day, because you relied on the best equipment in the market, we help make sure the work day ends on time. Dependability is what you get from any of the growing number of X Series models.

Since 1972, ECHO has been a leading innovator and manufacturer of professional-grade power equipment, priding ourselves on setting industry standards with an unwavering dedication to advanced technology and premium quality.





# LOOK FOR THE ECHO X SERIES LOGO

# LIGHTWEIGHT POWERFUL **GREATER PRODUCTIVITY**



# 



### Lightweight curved shaft.

- 21.2 cc 2-stroke engine
- i-30<sup>™</sup> starting system reduces starting effort by 30%
- Ergonomic adjustable handle for a • custom fit
- 2-line Rapid Loader® for easy line • changes
- 16 in. cutting swath

# GT-225SF 📢

Lightweight curved shaft with Speed-Feed<sup>®</sup> head.

- 21.2 cc 2-stroke engine
- i-30<sup>™</sup> starting system reduces starting effort by 30%
- Ergonomic adjustable handle for a custom fit
- Speed-Feed<sup>®</sup> 400 trimmer head • reloads in seconds without tools or disassembly
- 16 in. cutting swath



WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov



The average lawn contains over 7,000,000 individual grass plants.





# GT-225i 📢

### The easiest starting curved shaft trimmer available.

- 21.2 cc 2-stroke engine
- i-75<sup>™</sup> starting system reduces starting effort by 75%
- Ergonomic adjustable handle for a custom fit
- 2-line Rapid Loader® for easy line changes
- 16 in. cutting swath



### Lightweight 55 in. extended-length curved shaft trimmer.

- 21.2 cc 2-stroke engine
- i-30<sup>™</sup> starting system reduces starting effort by 30%
- Rubber over-molded throttle handle provides an ergonomic grip
- Speed-Feed<sup>®</sup> 400 trimmer head reloads in seconds without tools or disassembly
- 16 in. cutting swath

See page 54 for additional features and specifications.



### **CURVED SHAFT TRIMMERS**

# **PERFORMANCE!**

What more can be said about the world's finest professional-grade trimmers? ECHO's easy-to-use custom ergonomic controls, lightweight design, and powerful 2-stroke engines enhance productivity. Spend less time creating a lasting impression. Whether you need a lightweight curved shaft model for simple trimming around posts or fence lines or you require the long reach of a straight shaft model, all ECHO Trimmers are backed by a 2-year commercial and a 5-year consumer warranty.

# SRM-225 🕠

### Fuel efficient, entry-level, professionalgrade trimmer.

- 21.2 cc 2-stroke engine
- i-30<sup>™</sup> starting system reduces starting effort by 30%
- Ergonomic cushioned front and rear handles • for user comfort
- Speed-Feed<sup>®</sup> 400 trimmer head reloads in • seconds without tools or disassembly
- 17 in. cutting swath



### With a Speed-Feed® head and i-75<sup>™</sup> starting technology.

- 21.2 cc 2-stroke engine
- i-75<sup>™</sup> starting system reduces starting effort by 75%
- Ergonomic cushioned front and rear handles for user comfort
- Speed-Feed® 400 trimmer head reloads in • seconds without tools or disassembly
- 17 in. cutting swath



- 25.4 cc 2-stroke engine
- 1.35 hp for fast, efficient cutting
- Two-stage air filtration system dramatically • increases cleaning capability and allows for longer maintenance intervals
- Speed-Feed<sup>®</sup> 400 trimmer head reloads in • seconds without tools or disassembly
- 17 in. cutting swath

# SRM-230 🕥

### **Outstanding power, durability and** performance.

- 22.8 cc 2-stroke engine
- Ergonomic, cushioned front and rear handles • for operator comfort
- Commercial-grade air filtration for long • engine life
- Speed-Feed<sup>®</sup> 400 trimmer head reloads in • seconds without tools or disassembly
- 17 in. cutting swath

# SRM-266 🕠

### Powerful performance and superior design.

- 25.4 cc 2-stroke engine
- i-30<sup>™</sup> starting system for reduced effort starting
- 2-stage commercial-grade air filtration for long engine life
- Ergonomic cushioned front and rear handles for increased comfort
- 17 in. cutting swath





### **Class-leading power and performance.**

- 30.5 cc 2-stroke engine
- 1.8 hp for increased cutting ability
- Two-stage air filtration system dramatically increases cleaning capability and allows for longer maintenance intervals
- Speed-Feed<sup>®</sup> 450 trimmer head reloads • in seconds without tools or disassembly - accepts to up .130 in. line
- 20 in. cutting swath

Light Trimming 😱 Medium Trimming 📢 Heavy Trimming

8

echo-usa.com // 800.432.3246

See page 54 for additional features and specifications.



WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

echo-usa.com // 800.432.3246

### STRAIGHT SHAFT TRIMMERS



### Revolutionary combination of low weight, and high horsepower and high torque.

• 25.4 cc 2-stroke engine

3

- 2:1 gear reduction creates 28% more torque than SRM-2620
- Two-stage air filtration system dramatically increases cleaning capability and allows for longer maintenance intervals
- Speed-Feed<sup>®</sup> 400 trimmer head reloads in seconds without tools or disassembly
- 17 in. cutting swath



### Same class-leading power as SRM-3020 but with more cutting torque.

- 30.5 cc 2-stroke engine
- 2:1 gear reduction creates 28% more torgue than SRM-3020
- Two-stage air filtration system dramatically increases cleaning capability and allows for longer maintenance intervals
- Speed-Feed<sup>®</sup> 450 trimmer head reloads • in seconds without tools or disassembly - accepts to up .130 in. line
- 20 in. cutting swath



### 📢 Light Trimming 🚮 Medium Trimming 📢 Heavy Trimming

See page 54 for additional features and specifications.



9

# BABBER

Ethanol both absorbs water and dissolves materials. NID YOU Avoid engine trouble and always purchase gas with KNOW? zero ethanol or use Red Armor® Fuel.

# **POWER, COMFORT AND STABILITY**

ECHO's innovative line of professional-grade brushcutters can tackle all clearing applications including rough grass, thickets, shrubs and dense undergrowth.

# SRM-225U 💔

### Strong performance in a lightweight design.

- 21.2 cc 2-stroke engine •
- i-30<sup>™</sup> starting system reduces starting effort by 30%
- Offset U-handle with stop switch and . throttle lock out
- Speed-Feed<sup>®</sup> 400 trimmer head reloads in seconds without tools or disassembly
- Blade sold separately



### **Class-leading power and performance.**

- 30.5 cc 2-stroke engine •
- 1.8 hp for increased cutting ability
- Handle can fold parallel to unit for storage and transport
- Speed-Feed<sup>®</sup> 450 trimmer head reloads in seconds without tools or disassembly
- Blade sold separately



www.P65Warnings.ca.gov

BRUSHCUTTERS





### **Revolutionary combination of low** weight and high horsepower.

- 21.2 cc 2-stroke engine
- 1.35 hp for fast, efficient cutting
- Handle can fold parallel to unit for storage and transport
- Speed-Feed<sup>®</sup> 400 trimmer head reloads in seconds without tools or disassembly
- Blade sold separately



### **Blade-ready brushcutter** with maximum power.

- 30.5 cc 2-stroke engine
- Solid steel drive shaft for smooth acceleration and light weight
- Pleated paper air filter for use in harsh conditions
- Offset U-handle with stop switch and throttle lock-out

See page 55 for additional features and specifications.



# 

1-80101

DID YOU A mature tree, between 60-70 years old, has an average of 175,000 - 225,000 leaves.

# **POWERFUL, PRODUCTIVE AND QUIET.**

An ECHO Leaf Blower will make quick work of any yard clean-up. Our lineup includes both handheld and backpack configurations with many operator-friendly features, like comfortable handles with "cruise control", padded backrests and shoulder straps, Posi-Loc™ tubes for secure pipe connections, and ProFire® ignitions for quick and easy starts. Most backpack blowers are available in either tube-mounted or hip-mounted throttles. ECHO's blower performance specs now include "blowing force" measured in Newtons (N) (see page 56). A newton is a measure of force and represents a single number to gauge a blower's effectiveness. All ECHO Blowers are backed by a 2-year commercial and a 5-year consumer warranty.

# PB-2520 🕥

**Class-leading performance at an** incredible value.

- 25.4 cc 2-stroke engine
- Category leading blower performance ٠
- Double-grid intake design reduces clogging
- . Exclusive curved blower tube provides rotational control reducing fatigue



•

٠

•







12

### HANDHELD BLOWERS





ECHO reduced the effort required to keep the handheld blower from rotating in towards the operator (green section). The effect makes the blower easier to handle and reduces stress on the operator's arm. Rotational control tube available on the PB-2520.



### A step up in features with 64 dB(A) low-noise performance.

25.4 cc 2-stroke engine

Flared end pipe increases air speed

Rubber top handle grip improves comfort while parallel handles allow two-handed use for reduced fatigue and improved maneuverability



### ECHO's Best-in-Class handheld blower loaded with professional features!

- 25.4 cc 2-stroke engine
- Pleated paper main filter and foam prefilter for use in dusty conditions
- Second handle allows two-handed use for reduced fatigue and improved maneuverability



Heavy Blowing

See page 56 for additional features and specifications.

echo-usa.com // 800.432.3246



### **BACKPACK BLOWERS**



# PB-265LN 🐼

### Comfortable operation with 64 dB(A) low-noise performance.

- 25.4 cc 2-stroke engine
- Great performance from a lightweight backpack blower
- Low noise output for noise sensitive • environments
- i-30<sup>™</sup> starting system reduces starting • effort by 30%
- Hip mounted throttle with cruise control ٠



### Highest performance in its class.

- 58.2 cc 2-stroke engine
- Unique vented back pad for hot weather and padded backrest/shoulder pads
- Posi-loc<sup>™</sup> pipes provide secure • connection
- Available in hip (PB-580H shown) or tube (PB-580T) throttles
  - Posi-loc<sup>™</sup> pipes provide secure connection

•

Available in hip (PB-755SH) or tube ٠ (PB-755ST shown) throttles

Professional design built for durability

Pleated, automotive-style air filter for

Powerful performance coupled with ease of operation and maintenance.

63.3 cc 2-stroke engine

and ease of maintenance

superior filtration

PB-755S



# **BLOW IT! SHRED IT! BAG IT!**

ECHO's versatile Shred 'N' Vac® turns yard debris into garden mulch fast. With ECHO's professional-grade 2-stroke engine, you have the power to reduce a volume of debris by a ratio of up to 12 to 1. The large 2-bushel capacity bag minimizes emptying. The ES-250 quickly converts to blower or vacuum applications. ECHO Shred 'N' Vacs are backed by a 2-year commercial and a 5-year consumer warranty.



### The most powerful low-noise blower available.

- 63.3 cc 2-stroke engine •
- Professional features with padded • backrest & shoulder straps
- ٠ Low noise output for noise sensitive environments
- Posi-loc<sup>™</sup> pipes provide secure • connection
- Available in hip (PB-760LNH) or tube • (PB-760LNT shown) throttles





### A powerful combination of air speed and air volume.

- Unique vented back pad for hot weather and padded backrest/shoulder pads
- Posi-loc<sup>™</sup> pipes provide secure connection



### The industry's most powerful backpack blower!

- Industry-leading 44N blowing force
- Innovative, light weight carbon fiber • frame and fan case reduces fatigue
- Fan intake provides cooling air across the user's back
- Available in hip (PB-8010H shown) or tube (PB-8010T) throttles

See page 56 for additional features and specifications



- 79.9 cc 2-stroke engine



WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

Medium Blowing

ES-250 converted to

a blower

Medium Blowing



- •
- Available in hip (PB-770H shown) or tube (PB-770T) throttles

Heavy Blowing

14 

Light Blowing

9

echo-usa.com // 800.432.3246



WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov





### Ideal for residential lawn maintenance.

- 25.4 cc 2-stroke engine
- Three tools in one: easily converts from • blower to vacuum/shredder
- Shredding blade reduces leaf volume by up to a 12:1 ratio •
- Exclusive curved blower tube reduces user fatigue when used as a blower
- All conversion components included

### Heavy Blowing

See page 56 for additional features and specifications.





# ARBORIST

14:10 S-271T/CS-303T/CS-355T/CS-361P/CS-2511T

Planting trees or shrubs in key areas on your property can save 25% on energy bills. They DID YOU provide both shade and wind breaks. It can also KNOW? add 15% to resale values.



# **AN ARBORIST'S DREAM MACHINE!**

Whether you're climbing a tree or in a bucket, ECHO Top Handle Chain Saws provide long-lasting, trouble-free performance. Superior quality begins with a professional-grade, 2-stroke engine and an advanced ignition system that ensures fast starts either on the ground, or in a tree/bucket. All ECHO Chain Saws are backed by the best commercial warranty in the industry: 1-year.





ECHO's most powerful top-handle chain saw.

Ergonomic handle with adjustable palm rest

Automatic, clutch-driven oiler for reduced oil

Spring-assist starter for reduced pulling effort

35.8 cc 2-stroke engine





A powerful and compact saw for professionals who prefer a rear handle configuration.

- Automatic, adjustable clutch-driven oiler for reduced oil consumption

consumption

•

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov



- 35.8 cc 2-stroke engine
- Tool-less, easy access air filter

FOR USE BY TREE SERVICE PROFESSIONALS ONLY.

See page 57 for additional features and specifications.





# REAR HANDLE

MECHO

0

The tradition of good luck by knocking on wood DID YOU) dates back to pagan tribes who would thump trees to evoke the protective spirits within. KNOW?

PERFORMANCE COTTINUE SYSTEM



# **SERIOUS CHAIN SAWS FOR SERIOUS JOBS**

Whether you're pruning limbs, cutting firewood, or taking down a whole tree, ECHO Chain Saws provide long-lasting, trouble-free performance. Superior quality begins with a professional-grade, 2-stroke engine and an advanced ignition system that ensure fast starts and smooth operation. Along with exceptional quality, ECHO Chain Saws have professional features such as vibration reduction systems, easy-access air filters, automatic oilers, inertia chain brakes, and the G-Force Engine Air Pre-Cleaner™. All ECHO Chain Saws are backed by a 1-year commercial and a 5-year consumer warranty.



### Professional features and lightweight.

- 30.5 cc 2-stroke engine •
- i-30<sup>™</sup> starter for 30% reduction in starting effort
- Tool-less, easy-access air filter
- Side access chain tensioner for quick chain adjustments







# **REAR HANDLE CHAIN SAWS**



# CS-4510 (16" and 18" Bar Lengths

### Easy-to-use mid-range saw with spring-assist starter and vibration reduction.

• 45 cc 2-stroke engine

TIMBER

- Spring-assist starter for reduced pulling effort
- Tool-less, easy access air filter
- Automatic, adjustable clutch-driven oiler for reduced oil consumption

O

Heavy-duty, easy-access air filter

Decompression valve for easy starting

Automatic, adjustable clutch-driven

oiler for reduced oil consumption

The new standard for tough!

59.8 cc 2-stroke engine



### Lightest saw in its class.

- 50.2 cc 2-stroke engine
- Spring-assist starter for reduced pulling effort
- Tool-less, easy access air filter
- Magnesium crankcase-provides lightweight durability



## **Bar Lengths**

### Increased power for professionals.

- 59.8 cc 2-stroke engine
- Professional-grade magnesium • sprocket cover and crank case
- ٠ Heavy-duty aluminum handle with rubbér grip
- 16 in. bar available as an accessory only



### 20% more power than the CS-490 with more professional features.

- 50.2 cc 2-stroke engine •
- Increased power with professional • features
- Lightest saw in its class •
- 16 in. bar available as an accessory only



### 18", 20", 24" and 27" **CS-620PW Bar Lengths**

### Same as CS-620P with full wrap handle.

- 59.8 cc 2-stroke engine
- Professional-grade magnesium sprocket • cover and crank case
- Heavy-duty aluminum handle with rubber arip
- Performance cutting system •





### ECHO's most powerful chain saw.

- 80.7 cc 2-stroke engine •
- Professional-grade aluminum handle with rubber grip
- Automatic, adjustable oiler with manual override
- Performance Cutting System<sup>™</sup> upgraded bar and aggressive chain for improved cutting performance

See page 58 for additional features and specifications.



# **BUILD A DREAM HARDSCAPE!**

Powered by a 73.5 cc 2-stroke professional-grade engine, the CSG-7410 provides more cutting torgue at the wheel due to a 2.6:1 drive ratio. High torque translates into a greater ability to cut through masonry blocks or concrete without bogging down. The saw also has a reversible cutting arm with a standard position for normal cutting and a reversed (outside mount) position to cut close to buildings or ground obstacles.

The CSG-7410 is extremely easy to start due to the spring-assist starter, decompression valve, choke with automatic fast idle and purge bulb. The starter system is completely sealed. The patented 4-stage air cleaner system protects the engine for longer life. The CSG-7410 is packed with professional features and comes with a one year warranty, making it ideal for landscape/hardscape contractors.



### **SPECIFICATIONS**

Engine Disp.	Max. Engine Speed	Spindle Speed	Dry Weight	Wheel Diameter	Max. Cutting Depth	Arbor Size
73.5 cc	9,800 rpm	3,820 rpm	23.6 lbs.	14 in.	4.9 in.	20 & 25.4 mm



Air injection air cleaner uses centrifugal force to remove dust and debris from air





### **CS-680 Bar Lengths**

- Professional-grade aluminum handle with rubber grip
- Automatic, adjustable oiler with • manual override
- Performance Cutting System<sup>™</sup> upgraded bar and aggressive chain for improved cutting performance









18". 20" and 24'

**Bar Lengths** 

# 20", 24" and 27"



20



### Powerful engine and high torque provides exceptional cutting performance.

- 73.5 cc 2-stroke engine •
- Class leading high-torque drive system
- Patented 4-stage air cleaner provides the engine • with clean air for long life
- Easy starting system includes reduced effort starter and decompression valve
- Abrasive wheel included, diamond wheel sold separately

# **4-Stage Air Cleaner**

echo-usa.com // 800.432.3246



21

DID YOU

(NOW?

A single tree absorbs up to 48 pounds of carbon dioxide in a year and, over a 40 year lifespan, it will hold almost one ton.



# **REACH NEW PERFORMANCE HEIGHTS!**

ECHO Power Pruners<sup>®</sup> provide extra long reach for fast, easy, and safe tree pruning with a lightweight design and maximum operator comfort. All backed by a 2-year commercial, 5-year consumer and a lifetime flexible cable warranty.



# PPF-225 Bar Length

### Fixed shaft Power Pruner<sup>®</sup>.

- 21.2 cc 2-stroke engine
- i-30<sup>™</sup> starting system reduces starting effort by 30% •
- Front and rear handle rubber grips for operator comfort and vibration reduction
- Magnesium gear case with side access chain tensioner





### Telescoping pruner with great power and cutting performance.

- 25.4 cc 2-stroke engine
- 1.35 hp for fast, efficient cutting
- Ergonomic loop handle with rubber grip for comfort and vibration reduction
- Shaft telescopes to over 12 feet
- Two-stage air filtration system dramatically increases cleaning capability and allows for longer maintenance intervals



# **POWER PRUNERS**



### Fixed shaft pruner with increased power.

- 25.4 cc 2-stroke engine
- 1.35 hp for fast, efficient cutting
- Front and rear handle rubber grips for operator comfort and vibration reduction
- Two-stage air filtration system dramatically increases cleaning capability and allows for longer maintenance intervals
- Magnesium gear case with side access chain tensioner



## Telescoping pruner with great power and cutting performance with an in-line handle.

- 25.4 cc 2-stroke engine
- 1.35 hp for fast, efficient cutting
- In-line handle with rubber grip for comfort and vibration reduction
- Shaft telescopes to over 12 feet
- Two-stage air filtration system dramatically increases cleaning capability and allows for longer maintenance interval







# **PERFECT EDGE<sup>™</sup> FOR A PERFECT LOOK!**

ECHO Perfect Edge<sup>™</sup> Edgers give that straight manicured look to commercial properties and residential home sites. Nothing finishes a yard like a crisp edge between a sidewalk and the turf.

# **PE-225**

Great choice for residential and commercial properties.

- 21.2 cc 2-stroke engine
- i-30<sup>™</sup> starting system reduces starting ٠ effort by 30%
- Captive wheel mount hardware for easy wheel height adjustability •
- Durable, molded shield for reduced • material kickback



# PE-2620S

### **Revolutionary combination of low** weight and high horsepower.

- 25.4 cc 2-stroke engine
- 1.35 hp for fast, efficient edging
- Straight shaft for easier use on tighter • walkways or enclosed spaces
- Two-stage air filtration system dramatically increases cleaning capability and allows for longer maintenance intervals
- Contoured aluminum debris shield with open face for reduced clogging
- 2:1 gear reduction to power through tough overgrown grass





### **Revolutionary combination of low weight** and high horsepower.

- 25.4 cc 2-stroke engine
- 1.35 hp for fast, efficient edging
- Two-stage air filtration system dramatically increases cleaning capability and allows for longer maintenance intervals
- Contoured aluminum debris shield with open face for reduced clogging
- 2:1 gear reduction to power through • tough overgrown grass





See page 60 for additional features and specifications.

# H I H

DID YOU KNÓW?

Historical data indicates hedges and hedgerows have been used to delineate agricultural plots as long as 4000 years ago.

# **A CUT ABOVE THE REST!**

For professionals who demand performance, ECHO Hedge Trimmers deliver. They're tough, reliable, and loaded with features including ECHO-exclusive laser-cut and precision-ground RazorEdge<sup>™</sup> blades for more efficient cutting.



### Superior features at an incredible value.

- 21.2 cc 2-stroke engine
- Incredibly light 10.0 lbs dry weight for reduced fatigue .
- Professional-grade double-sided, double-reciprocating blades for a clean cut
- 20 in. blade length for easy maneuvering in tight spaces





•

•

٠

length.

•

### Lightweight 20 in. shaft.

effort starting

Single-sided performance with built-in debris sweeper.

- 21.2 cc 2-stroke engine
- Front-facing exhaust improves plant health
- Leaf collector provides a cleaner finish
- 30 in. (HCS-3020) or 40 in. (HCS-4020) blade lengths



**Revolutionary combination of low weight, high** horsepower and superior cutting performance.

- 25.4 cc 2-stroke engine
- 1.35 hp for fast, efficient cutting
- 21 in. double-sided, double-reciprocating RazorEdge blades for long-lasting sharpness
- Long 51 in. shaft with 7-degree angle for long reach and best visibility of hedges during cutting

Small Hedges Tall Hedges



WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov





### Improved features and 24 in. blade

- 21.2 cc 2-stroke engine i-30<sup>™</sup> starting system reduces starting effort by 30%
- 24 in. double-sided, double-reciprocating RazorEdge<sup>™</sup> blades are precision ground and laser cut for long-lasting sharpness



### Lightweight with a front-facing exhaust and 5-position rotating handle.

- 21.2 cc 2-stroke engine
- Front-facing exhaust improves plant
- 5-position rotating rear handle for a variety of cutting positions
- 24 in. (HC-2420) or 30 in. (HC-3020) blade length



- 21.2 cc 2-stroke engine
- 21 in. double-sided, doublereciprocating RazorEdge blades for
- long-lasting sharpness
- Short shaft length for maximum maneuverability
- i-30<sup>™</sup> starting system for reduced

# SHC-225 🔘

### Comfortable, easy-to-handle 33 in. shaft.

- 21.2 cc 2-stroke engine
- 21 in. double-sided, double-reciprocating RazorEdge blades for • long-lasting sharpness
- Medium-length shaft provides balance • of maneuverability and reach
- ٠ i-30<sup>™</sup> starting system for reduced effort starting



### Shafted hedge trimmer with 135° articulation and 10 operating positions.

- 25.4 cc 2-stroke engine ٠
- 1.35 hp for fast, efficient cutting
- 21 in. double-sided, double-reciprocating RazorEdge blades for long-lasting sharpness
- Offset articulating gear case for easy cutting of the tops • of hedges or other hard-to-reach areas

See page 61 for additional features and specifications.



# PRO ATTACHMENT

Over 250,000 pink flamingos are sold and used as DID YOU decoration in front yards every year. KNOW?

# **A TOOL FOR EVERY NEED!**

The Pro Attachment Series<sup>™</sup> (PAS) is the economical way to stock your trailer or tool shed. The versatility and flexibility of this expandable system is as limitless as your ever-changing job requirements. Two power sources work in conjunction with multiple commercial-grade attachments - ranging from trimmers, brushcutters and blowers to edgers, hedge trimmers, pruners and debris sweepers - for unbeatable usefulness and reliable performance. All ECHO PAS power sources and attachments are backed by a 2-year commercial and a 5-year consumer warranty.

# **PAS-225**

### Ideal for residential applications.

- 21.2 cc 2-stroke engine
- i-30<sup>™</sup> starting system reduces starting effort by 30%
- Tool-less coupler allows for fast easy changes on multiple attachments
- Accepts up to 12 PAS Attachments (see page 62)

# **PAS-225SB**

### Speed-Feed® trimmer attachment included.

- 21.2 cc 2-stroke engine
- Includes powerhead and trimmer attachment
- i-30<sup>™</sup> starting system reduces starting effort by 30%
- Tool-less coupler allows for fast easy changes on multiple attachments
- Speed-Feed<sup>®</sup> 400 trimmer head reloads in seconds without tools or disassembly

# **PAS-225VP**

### **Economical Trimmer and** Edger combo kit.

- 21.2 cc 2-stroke engine
  - Includes powerhead, trimmer and edger attachments
  - i-30<sup>™</sup> starting system reduces starting effort by 30%
    - multiple attachments
    - Edger attachment features clog-resistant, open-faced metal shield

/!\

Tool-less coupler allows for fast easy changes on





### The most powerful 25.4 cc engine in the industry.

- 25.4 cc 2-stroke engine
- 1.35 hp
- Commercial-grade, 2-stage air filtration • system
- Tool-less coupler allows for fast easy changes on multiple attachments
- Accepts all available attachments





# PAS-225VPB

### **Economical Trimmer and** Blower combo kit.

- 21.2 cc 2-stroke engine
- Includes powerhead, trimmer and blower attachments
- i-30<sup>™</sup> starting system reduces starting effort by
- Tool-less coupler allows for fast easy changes on multiple attachments
- Blower has an axial direct-drive for maximum performance



See page 62 for additional features and specifications.



### PAS ATTACHMENTS

### **Curved Shaft Trimmer** 99944200615

- Easy-loading Rapid Loader<sup>®</sup> head with patented line locking mechanism
- Curved shaft allows precise trimming in tight area
- Length: 33 in.
- Weight: 3.9 lbs.

### **Bed Redefiner** 99944200465

- Patented, replaceable six-finger steel claw
- Brazed, carbide tips
- Adjustable support wheel for that perfect edge depth
- Length: 34.8 in.
- Weight: 8.5 lbs

### **Tiller/Cultivator** 99944200513

- 6.5 in. tilling swath
- Heavy-duty gear box
- 42:1 gear reduction for high torque tilling action
- Length: 35 in.
- Weight: 4.6 lbs

### 3 ft. Extension 99944200536

- Tool-less coupler easily and guickly attaches between the PAS powerhead and attachment
- Compatible with Power Pruner<sup>®</sup> and all hedge trimmer attachments
- Length: 36 in.
- · Weight: 2.6 lbs

30

### **Blower** 99944200490

 Solid drive shaft with 4-bearing support for durability and smooth performance

Speed-Feed<sup>®</sup> Trimmer

1.62:1 gear ratio for

strong performance

· Easy-loading Speed-

Feed<sup>®</sup> 400 trimmer

99944200540

head

• Length: 34 in.

Weight: 3 lbs.

- Direct-drive fan for efficient power transfer
- Metal ring on the blower tip gives added protection for demanding use
- Length: 25 in.

# 99944200486

- 21 in. double-sided. double- reciprocating RazorEdge<sup>™</sup> blades
- Extra heavy-duty, commercial-grade magnesium gear case
- Tip guard and aluminum I support bar to protect the cutting surface
- Length: 50 in.

- Heavy-duty gear case and automatic oiler
- Over 8 ft. of total reach including power source
- Able to change to a 12 in. bar and chain for Power **Pruners**<sup>®</sup>
- Length: 57 in.
- Weight: 4.8 lbs.

### **Pro-Torque<sup>™</sup> Trimmer** 99944200545

- Proven ECHOmatic<sup>™</sup> trimmer head Pro-Torque<sup>™</sup> gear case increases cutting
- torque by 50% • Length: 34 in.

**Curved Shaft Edger** 

wear plate

99944200470

Weight: 3.2 lbs.

Open-face, cast-metal

debris flap and steel

case increases cutting

7.75 in. blade provides

depth and durability

for sidewalk and bed

shield with rubber

Pro-Torque<sup>™</sup> gear

torque by 50%

excellent cutting

edging

99944200640

· Length: 33 in.

• Weight: 5.6 lbs.

Mid-Reach Hedge Trimmer

21 in. double-sided.

double- reciprocating

• Shorter shaft length for

best maneuverability

cutting surface

Length: 37.9 in.

• Weight: 3.6 lbs

Pro Paddle<sup>™</sup>

99944200620

• Ten, 1.625 in.

surfaces

sand

durable rubber fins

Won't harm grass

Useful for rocks.

mulch, pine

needles, pine

• Length: 36.5 in.

• Weight: 11.2 lbs

cones, acorns, and

• Tip guard and aluminum

support bar to protect the

RazorEdge<sup>™</sup> blades

### **Brushcutter** 99944200601

- 1.62:1 gear ratio for strong performance
- Barrier bar (included with PAS attachment) or U-handle kit with harness (sold separately) required for use on PAS
- Includes 8 in. 80-tooth brush blade
- Length: 32.7 in.
- Weight: 2.62 lbs.

### **Straight Shaft Edger** 99944200475

- Straight shaft for use on tight walkways
- Open-face, cast-metal shield with rubber debris flap and steel wear plate
- Pro-Torque<sup>™</sup> gear case increases cutting torque by 50%
- 7.75 in. blade
- Length: 33 in. Weight: 5.6 lbs.

### 180° Articulating Hedge Trimmer 99944200596

- 135 degrees of articulation in 15 degree increments
- · Blade folds flush to shaft for storage
- 21 in. double-sided. double-reciprocating blades
- Length: 64.4 in. (extended) 43.3 in. (storage position)
- Weight: 5.6 lbs
- **Pro Sweep**<sup>\*</sup> 944200553 22.5 in. sweeping swath
- of surfaces including concrete, lawn and SOIL
- bristles work to clean debris out of cracks and crevices
- Length: 36 in.



# **KEEP FLOWER BED EDGES IN SHAPE!**

Flower and mulch bed edges erode over time and need to be redefined. The old way to redefine the edge was to use a shovel, which is tough, time-consuming work. With its powerful 25.4 cc engine, the BRD-2620 cuts a crisp, beveled groove along the turf edge up to 7 TIMES FASTER than a shovel, leaving a professional, manicured finish. ECHO's Bed Redefiner is backed by a 2-year commercial and a 5-year consumer warranty.



# BRD-2620

- 25.4 cc 2-stroke engine
- 1.35 hp for fast, efficient cutting
- ٠ performance
- longer maintenance intervals

### **SPECIFICATIONS**

Engine Disp. (cc) 25.4



- Weight: 11.2 lbs







- **Power Pruner®** 99944200532
- Weight: 4.1 lbs

// *| | | | |* 





Redefines bed edges up to 7x faster than a shovel

Replaceable, patented, six-finger steel claw with brazed carbide tips for durability and

Two-stage air filtration system dramatically increases cleaning capability and allows for

uel Cap. (fl. oz.)	Gear Ratio	Debris Shield	Dry Weight (lb.)
20.6	2:1	Die-Cast Metal/ Nylon	17.7



# SPRAHS



### One hour of weeding can burn up to 300 calories DID YOU and pushing a lawn mower for one hour can burn KNOW? up to 500 calories.



# **A COMPLETE LINE-UP FOR EVERY NEED!**

ECHO Sprayers are available in handheld and backpack styles. The entire product line features lightweight tanks with UV inhibitors and ergonomic pump handles. All ECHO Sprayers are backed by a 2-year commercial and 5-year consumer warranty except MS-1H with a 90 day consumer warranty.

# MS-1H

### Handheld sprayer includes brass and plastic nozzles.

- Viton® pump seal for maximum durability
- .375 gal. capacity
- 45 maximum psi

### MS-21H **Convenient, lightweight**

handheld sprayer. • Poly wand includes three nozzles

- Viton® pump seal for
- ۲
- 2 gal. capacity
- 45 maximum psi



# MS-41BPD

### **Backpack sprayer with** piston-style pump.

- Tank with UV inhibitors and wide 6 in. mouth
- Ergonomic, fold-away pump handle
- Stainless steel wand includes three nozzles
- 4 gal. capacity
- 90 maximum psi

### sprayer in the market today.

- Piston/Diaphragm style pump • 28 in. stainless steel wand with .
- brass nozzle ٠
- largest in the market 4 gal. capacity •
- 90 maximum psi •

- maximum durability
- Wand includes 3 nozzles

# The best performing backpack

- Large 6 in. ID cap opening -

# **MS-31H**

### Larger capacity, handheld sprayer.

- Poly wand includes three nozzles
- Viton® pump seal for • maximum durability
- 3 gal. capacity
- 45 maximum psi



# **MS-53BPE**

### Large-capacity sprayer with piston-style pump.

- All critical seals Viton<sup>™</sup> formulation for increased durability
- Fold-away pump handle with storage clip
- 28 in. wand trigger with three nozzles for application versatility
- 5 gal. capacity
- 90 maximum psi

See page 63 for additional features and specifications.



### **58V CORDLESS**



# 58V CORDLESS PRODUCTS

The ECHO 58V Cordless line-up features six different tools using a common battery platform to perform lawn maintenance tasks around the home, all without the hassle of gas. All six tools feature powerful, maintenance-free brushless motors and heavy-duty construction, all with an outstanding warranty. The perfect choice for noise-sensitive environments.

# **PRO ATTACHMENT SERIES™ TRIMMER**

Powerful attachment-capable trimmer with our easy-loading Speed-Feed® 400 trimmer head.

- Powerful brushless motor provides gas-like performance
- Accepts up to 7 ECHO PAS attachments for incredible versatility • (see page 62)
- Variable speed trigger with hi/lo speed switch for ultimate • power control
- CST-58V2AH Includes 2AH battery and charger
- CST-58VBT Bare tool (no battery or charger)

# STRING TRIMMER 🛐

### Lightweight dedicated trimmer with our Speed-Feed® 400 head.

- Powerful brushless motor provides gas-like performance
- Dedicated trimmer for light weight and easy maneuverability
- Variable speed trigger with hi/lo speed switch for ultimate • power control
- CDST-58V2AH Includes 2AH battery and charger ٠
- CDST-58VBT Bare tool (no battery or charger) •

# HEDGE TRIMMER 🥿

### Double-sided, double-reciprocating hedge trimmer with commercial-quality blades.

- Powerful brushless motor provides gas-like performance •
- Heavy-duty gear case with metal housing for years of ٠ dependable performance
- Double-sided, double-reciprocating blades for excellent cut quality
- CHT-58V2AH Includes battery and charger •
- CHT-58VBT - Bare tool (no battery or charger)

34

echo-usa.com // 800.432.3246

SPECIFICA	TIONS				
Model	Line (in.)	Cutting Head	Cutting Swath (in.)	Weight w/ Battery (lbs.)	Run Time*
CST-58V	.095 or .080	Speed-Feed® 400	14 - 16	13.3	45 min.
			*continuou	is use on low sp	eed setting



### **SPECIFICATIONS**

Model	Line (in.)	Cutting Head	Cutting Swath (in.)	Weight with Battery (lbs.)	Run Time*
CDST-58V	.095 or .080	Speed-Feed® 400	14 - 16	10.5	55 min.
			*continuo	us use on low sp	eed setting

### **SPECIFICATIONS**

Model	Blade Length (in.)	Weight with Battery (lbs.)	Run Time
CHT-58V	24	11.5	90 Minutes
		*continuous use on lo	w speed setting

### WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

HANDHELD BLOWER 🧔

### Lightweight and powerful handheld blower.

- Powerful brushless motor provides gas-like performance
- Variable speed trigger and cruise control for ultimate power & convenience
- Turbo mode button for dislodging tough debris
- CPLB-58V2AH Includes 2AH battery and charger
- CPLB-58VBT Bare tool (no battery or charger)



### Rear-handle chain saw with incredible cutting performance.

- Powerful brushless motor and 16 in. bar length provide gaslike performance
- Side-access chain tensioner with on-board scrench for easy ٠ chain adjustments
- CCS-58V4AH Includes 4AH battery and charger
- CCS-58VBT Bare tool (no battery or charger)

# I AWN MNWFR

### 21 in. rear-discharge mower with quiet brushless motor.

- Powerful brushless motor provides gas-like performance
- On-board dual 58V battery storage for extended working time
- Includes grass catch bag and mulch plug
- Replaceable 21 in. mower blade
- CLM-58V4AH Includes (1) 4AH battery and charger ٠
- CLM-58VBT Bare tool (no battery or charger)

### **Replacement Parts**

21 in. Mower Blade	Mower Bag
Part #: ALB-58V	Part #: 970687001

### **BATTERIES AND CHARGERS**

Featuring triple-protection electronics, these batteries are equipped to prevent overcharging, overheating and overloading to deliver performance and durability.



**2AH Lithium-Ion Battery** 

2.7 lbs.

Part #: CBP-58V2AH

30 minute recharge time



### **4AH Lithium-Ion Battery** 1 hour recharge time Charges up to 5x faster than competition Larger battery for longer run time

- - •
  - •
  - 4 lbs. •
  - Part #: CBP-58V4AH

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov



### **58V CORDLESS**



### **SPECIFICATIONS**

Model	Air Volume (CFM)	Maximum Air Speed (MPH)	Weight with Battery (lbs.)	Run Time*
CPLB-58V	550	145	8	1 hr.
		*contin	uous use on low	speed setting
SPECIFICATI	15in. M	TIECHO G		
Model	Barl	Length (in.)	Weight with	Run Time

Model	Bar Length (in.)	Weight with Battery (lbs.)	Run Time
CCS-58V	16	13.7	112 cuts (6 in. log)

\* Uses 16A4CD3756C bar and 90PX56CQ chain



### **SPECIFICATIONS**

Model	Deck Size	Height	Cutting	Weight with	Run
	(in.)	Adjustment	Range (in.)	Battery (lbs.)	Time
CLM-58V	21	7-position	3/4 - 4	57	40 min.



**Lithium-Ion Charger** Features innovative charging technology for battery protection and extended life

Part #: CBC-58VA

echo-usa.com // 800.432.3246



### **ENGINE DRILL**

### 25.4 cc high-power engine delivers outstanding performance.

1.35 hp

EDR-26(

- Heavy-duty gear reduction for maximum torque
- Convenient reverse function ۰
- All-position diaphragm carburetor, with purge pump, allows • operation at any angle

### SPECIFICATION

Model	Engine Disp. (cc)	Gear Reduction Ratio	RPM	Torque (ft. lb.)	Chuck Diam.	Fuel Cap. (fl. oz.)	Dry Weight (Ib.)
EDR-260	25.4	17.1:1	0-650 forward/ reverse	12	1/2 in. standard	19.6	11.4

### **SPREADERS**

- Metal auger
- Pro-style "T handle" places controls at fingertips
- Maintenance-free gear case
- Includes rain cover

### EARTH/ICE AUGER



Shown with available 36 in. long, 10 in. diameter auger

### Powerful 42.7 cc engine makes the earth/ice auger a must for any digging/drilling operation.

- Heavy-duty handle and frame allows for single or two-person operation
- Turns into a powerful ice auger for year-round use
- Available auger lengths: 34 in. (881 mm) or 36 in. (925 mm) •
- Ice augers are 40 in. (L); 8 in. and 10 in. diameters

Augers not included, see page 50

### **SPECIFICATION**

Model	Engine Disp. (cc)	Carburetor	Maximum Torque at Engine <b>‡</b>	Maximum Torque at Auger‡	Fuel Cap. (fl. oz.).	Auger RPM <b>‡</b>	Dry Weight* (Ib.)
EA-410	42.7	Diaphragm w/		48.97 ft/ lb (66.4 Nm)	33.8	348 21.6	
			#	at max. engine	e power	* wit	hout auger

# RB-100S

Metal auger

Model

TC-210

- Pro-style "T handle" places controls at fingertips
- Maintenance-free gear case
- Includes rain cover



Model	Hopper Capacity (lbs.)	Tires	Frame
RB-80	80	12 in. pneumatic	Powder-coated steel
RB-100S	100	14 in. pneumatic	Stainless steel

### **TILLER/CULTIVATOR**

# TC-210

**SPECIFICATION** 

### Tremendous performance from a compact package.

- Four 9 in. diameter, 10-tooth, reversible, hardened-steel tines
- 42:1 reduction worm gear-type ٠ transmission
- Waterproof stop switch and throttle control located at operators fingertips







Fuel Cap.

Carburetor

Diaphragm w/

Purge Pump



## **GEAR TECHNOLOG BYPASS PRUNE**

- Multiplies leverage 3X
- High carbon steel blade
- Low friction-coated blades
- Composite handles
- Rubber overmolded grip
- Max. cut capacity: 5/8 in.

### Part #: HP-43



- High carbon-content steel blades sharpened and precision-ground
- Low friction-coated blades provide smooth cuts
- Gear technology reduces cutting effort
- Heavy-duty aluminum alloy ٠ handles
- Weight: 2.8 lbs. ٠
- Length: 32.5 in.
- Max. cut capacity: 2.25 in ٠

Part #: HA-2710

•

BYPASS LOPPER

precision-ground

cutting effort

Weight: 2.6 lbs.

Length: 32.5 in.

Max. Cut Capacity: 2.25 in.

handles

Part #: HA-2720

provide smooth cuts

•

•

High carbon-content steel

Low friction-coated blades

Gear technology reduces

Heavy-duty aluminum alloy

blades, sharpened and

Part #: HP-44

- High carbon content steel • with hardened and tempered cutting edge
- Ergonomic fawn foot, low moisture hickory handle for maximum strength and durability
- Factory sharpened cutting edge
- Head weight: 2 lbs.
- Handle length: 14 in.

Part #: HA-1142

### Part #: HA-1282

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

# LIMBING AXE

- High carbon content steel with hardened and tempered
- cutting edge Ergonomic fawn foot, low moisture hickory handle for maximum strength and
  - durability Factory sharpened cutting
  - edge

### Head weight: 2.25 lbs. Handle length: 28 in.





Dry Weight'





AECHUT	
<b>GFD</b>	



Engine

Disp.

(cc)t

21.2









## AN IIISTARI F GRIF **BYPASS PRUNEF**

High carbon steel blade

- Low friction-coated blades
- Composite handles
- Rubber overmolded arip
- Max. cut capacity: 1/2 in. or 1 in.



**HAND TOOLS** 

# **BYPASS PRUNER**

- Aluminum die-cast handles
- High carbon steel blade
- Low friction-coated blades
- Max. cut capacity: 1 in.
- Replaceable blades (Part #: 91231)

Part #: HP-62

# HEDGE SHEAR

- High carbon-content steel • blades, sharpened and precision-ground
- Low friction-coated blades provide smooth cuts
- Gear technology reduces cutting efforts
- Heavy-duty aluminum alloy handles
- Weight: 2.3 lbs. ٠
- Overall Length: 26 in.
- Blade Length: 8 in.
- Max. cut capacity: .375 in.

Part #: HA-2910

# FELLING AXE

- High carbon content steel with hardened and tempered cutting edge
- Ergonomic fawn foot, low moisture hickory handle for maximum strength and durability
- Factory sharpened cutting edge
- Head weight: 3.5 lbs.
- Handle Length: 36 in.



- Head weight and width is ideally suited for splitting wood
- Low moisture hickory handle for maximum durability and strenath
- Head weight: 6 lbs.
- Handle Length: 36 in.

Part #: HA-1366





# SPLITTING V

- Sharpened and ready for use
- Tapered cutting edge for efficient splitting
- Striking face is intended for driving splitting wedge
- Forged head weight 5 lbs.

Part #: HA-1005



# **PERFORMANCE ABOVE ALL™**

Red Armor is first and foremost about the user. Users who buy ECHO need to be rewarded for what they need most: Performance. The Red Armor family is designed exclusively for ECHO to deliver the ultimate performance for your outdoor power equipment. These Best-in-Class solutions offer a wide array of outdoor applications and continues to expand.

# RED ARMOR<sup>™</sup> FUEL EGHO Exclusiv

Red Armor<sup>™</sup> Fuel is 50:1 93 octane, ethanol-free fuel with ECHO Red Armor Oil for 2-stroke engines. Designed to deliver the ultimate performance for your engine, Red Armor Fuel cleans existing deposits, protects against future carbon build-up and promotes longer engine life. Fuel stays fresh up to 2 years opened, 5 years unopened.



ECHO Red Armor Oil is a premium 2-stroke semi-synthetic engine oil formulated with powerful detergents and anti-oxidants to clean existing deposits, protect against future carbon build-up and promote longer engine life. With unique fuel stabilizers blended in, fuel stays fresh up to 2 years in a properly sealed container. JASO FD and ISO L-EGD rated. Red Armor cleans and protects to ensure optimum engine performance and prolonged engine life.

2.6 fl. oz. tray	2.6 fl. oz.	5.2 fl. oz.	6.4 fl. oz.	12.8 fl. oz.	16 fl. oz.	1 gallon	5 gallons	55 gallon drum
(48 loose)	(8) 6 pks.	(8) 6 pks.	(8) 6 pks.	12 per carton	12 per carton	4 per carton	250 gallon mix	2,750 gallon mix
1 gallon mix	1 gallon mix	2 gallon mix	2.5 gallon mix	5 gallon mix	6 gallon mix	50 gallon mix	Part #: 6550250	Part #: 6552750
Part #: 6550000	Part #: 6550001	Part #: 6550002	Part #: 6550025	Part #: 6550005	Part #: 6550006	Part #: 6550050		

# RED ARMOR<sup>®</sup> FUEL TREATMENT

Red Armor Fuel Treatment keeps fuel fresh for up to 2 years with our unique blend of antioxidants, detergents and alcohol free based formula. The corrosion inhibitors protect against corrosion of the fuel system, while nitrogen-based detergents help to keep it clean. Ideal for both 2-stroke and 4-stroke engines for day to day use or extended storage.

- Anti-oxidant fuel stabilizers keep fuel stable up to 2 years
- Contains NO alcohol
- Detergents keep fuel system and engine clean
- Add to fresh fuel for ultimate protection and extended fuel life

# RED ARMOR<sup>™</sup> LUBRICANT

Red Armor Lubricant sets a new standard in lithium-based grease. Special adhesives and tackifiers eliminate sling-off and are impervious to water. With its enhanced protection power, capability to resist shock loads, ability to seal out moisture and contamination from critical components and corrosion resistance, Red Armor Lubricant is a high-performing, dependable grease to keep parts moving and lubricated for long lasting protection.



- Gear cases
- Spindles
- Cables
- Ball bearings

0.8 oz. tube Part #: 94001



**RED ARMOR® HAND SCRUB** 

Red Armor Hand Scrub is dirt-powered and water-activated to deliver a clean you've never experienced before. The dirt powered formula helps to absorb grease and toxins, while the all natural ingredients including olive oil, coconut oil, and lime oil scrub away dirt, grease and grime leaving your hands feeling smooth and hydrated; never dry or cracked. Free of harsh chemicals such as mineral oils, ammonia, sulfates, parabens or phthalates.

Tough on: Grease, Gas, and Sap Also removes: Tar, Grass Stains, Odors and More



# **RED ARMOR<sup>®</sup> BLADE CLEANER AND LUBRICA**

Red Armor Blade Cleaner and Lubricant is a bio-based universal solution for professional users. The tacky lubricant dissolves resins and sap that accumulate along the blade that hinder cutting performance. The exclusive formula helps reduce blade drag and inhibits corrosion while promoting plant health after trimming. Ideal hand tool uses include: pruners, shears, loppers, and axes. Suited for powertools including hedge trimmer blades, brushcutter blades, circular saw blades and more!



38





4.75 gallons

Part #: 7450005

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov



### **RED ARMOR™**





Part #: 7550012



1 fl. oz. sample pack Part #: 7550000

14 oz. cartridge Part #: 94014



Grease gun (for 8 oz. tube) Part #: 94016







64 oz. Part #: 35500064



Sample Pack Part #: 3550000



Part #: 4550012



# **POWERBLEND® GOLD OIL**

ECHO PowerBlend Gold 2-stroke engine oil includes detergents and a fuel stabilizer to maintain fuel's quality and optimize engine performance. Both additives help maintain a cleaner engine that helps minimize exhaust-port blockages while protecting other vital engine components from wear and corrosion. A low smoke emissions formula offers improved environmental impacts on the user and surrounding environment. Product meeting JASO M345 standards, FD rated, and meets ISO L-EGD.



OIL

2.6 fl. oz. tray (48 loose) 1 gallon mix Part #: 6450000G



2.6 fl. oz. (8) 6 pks. 1 gallon mix Part #: 6450001G



5.2 fl. oz. (8) 6 pks. 2 gallon mix Part #: 6450002G



(8) 6 pks. 2.5 gallon mix Part #: 6450025G



2,750 gallon mix Part #: 6452750G



5 gallon mix

Part #: 6450005G

in a properly sealed container.

12 pks.

16 fl. oz. 12 per carton

Environmentally safe and designed to biodegrade over time. Formulated with a vegetable base, anti-wear additives, and tackifiers for lubrication. Meets OECD 301 specifications. 2 year shelf life

6 gallon mix

**BIODEGRADABLE BAR AND CHAIN OIL** 

Part #: 6450006G

1 gallon 6 per carton 50 gallon mix

Part #: 6450050G



5 gallons 250 gallon mix Part #: 6450250G



1 gallon Part #: 6458006

**BAR AND CHAIN OIL** 

A special blend of lubricants and detergents that maximizes lubricity, reduces heat caused from bar and chain friction, minimizes resin build-up, and facilitates chip and dust removal.

# **OIL MEASURING CUP**



40

4 fl. oz. capacity Part #: 6450009







# **OIL PAIL DISPENSING PUMP**

For 5 gal. pail Part #: 99909-0010



1 gallon Part #: 6459007







# **BARS AND CHAINS**

ECHO Bars and Chains are specifically matched to get the most out of every saw. The chart is sorted by model number and includes the appropriate length bar and chain along with the link count, gauge, pitch, and file size.



		BAR		Drive Link			HAIN		
Chain Saw Models	Length in. (cm)	Sprocket Nose	Bar Part #	Count	Gauge (in.)	Pitch (in.)	Chain Part #	File Size	3-pack Cl
	12 (30)	Non-Replaceable	12A0CD3745C	45	.050	3/8 lp	91PXL45CQ	5/32 in.	-
CS-2511T	12 (30)	Non-Replaceable	12A4CD3745C	45	.043	3/8 lp	90PX45CQ	4.5 mm	-
	14 (35)	Non-Replaceable	14A0CD3752C	52	.050	3/8 lp	91PXL52CQ	5/32 in.	-
	14 (35)	Non-Replaceable	14A4CD3752C	52	.043	3/8 lp	90PX52CQ	4.5 mm	-
CS-271T	12 (30)	Non-Replaceable	12A4CD3745C	45	.043	3/8 lp	90PX45CQ	4.5 mm	-
	12 (30)	Non-Replaceable	12A0CD3745C	45	.050	3/8 lp	91PX45CQ	5/32 in.	-
	12 (30)	Non-Replaceable	12A0CD3745C	45	.050	3/8 lp	91PX45CQ	5/32 in.	-
CS-303T/310/352	14 (35)	Non-Replaceable	14A0CD3752C	52	.050	3/8 lp	91PX52CQ	5/32 in.	91PX52C
	16 (40)	Non-Replaceable	16A0CD3757C	57	.050	3/8 lp	91PX57CQ	5/32 in.	91PX57C
CS-355T	12 (30)	Non-Replaceable	12A0ED3745C	45	.050	3/8 lp	91PX45CQ	5/32 in.	-
	14 (35)	Non-Replaceable	14A0ES3752C	52	.050	3/8 lp	91PXL52CQ	5/32 in.	-
CS-355T/361P	16 (40)	Non-Replaceable	16A0ES3757C	57	.050	3/8 lp	91PXL57CQ	5/32 in.	-
	14 (35)	Non-Replaceable	14A0CD3752C	52	.050	3/8 lp	91PX52CQ	5/32 in.	91PX52C0
	14 (35)	Non-Replaceable	14A0ZD3752C	52	.050	3/8 lp	91PX52CQ	5/32 in.	91PX52C
CS-370/F	16 (40)	Non-Replaceable	16A0CD3757C	57	.050	3/8 lp	91PX57CQ	5/32 in.	91PX57C
	16 (40)	Non-Replaceable	16A0ZD3757C	57	.050	3/8 lp	91PX57CQ	5/32 in.	91PX57C
	18 (45)	Non-Replaceable	18A0CD3762C	62	.050	3/8 lp	91PX62CQ	5/32 in.	91PX62C
	16 (40)	Non-Replaceable	16A0CD3757C	57	.050	3/8 lp	91PX57CQ	5/32 in.	91PX57C
CS-400	18 (45)	Non-Replaceable	18A0CD3762C	62	.050	3/8 lp	91PX62CQ	5/32 in.	91PX62C
	16 (40)	Non-Replaceable	16B0AD3366C	66	.050	.325	20BPX66CQ	3/16 in.	511 X020
CS-4510	. ,		18B0AD3372C	72	.050	.325	20BPX00CQ 20BPX72CQ	3/16 in.	-
5-4010	18 (45)	Non-Replaceable							-
	20 (50)	Non-Replaceable	20B0AD3378C	78	.050	.325	20BPX78CQ	3/16 in.	-
0.400	16 (40)	Non-Replaceable	16F0AD3366C	66	.050	.325	20BPX66CQ	3/16 in.	-
CS-490	18 (45)	Non-Replaceable	18F0AD3372C	72	.050	.325	20BPX72CQ	3/16 in.	-
	20 (50)	Non-Replaceable	20F0AD3378C	78	.050	.325	20BPX78CQ	3/16 in.	-
	16 (40)	Non-Replaceable	16F0LD3366C	66	.050	.325	20LPX66CQ	3/16 in.	-
CS-501P	18 (45)	Non-Replaceable	18F0LD3372C	72	.050	.325	20LPX72CQ	3/16 in.	-
	20 (50)	Non-Replaceable	20F0LD3378C	78	.050	.325	20LPX78CQ	3/16 in.	-
	18 (45)	Non-Replaceable	18D0AS3864C	64	.050	3/8	72LPX64CQ	7/3 in.	-
CS-590	20 (50)	Non-Replaceable	20D0AS3870C	70	.050	3/8	72LPX70CQ	7/32 in.	72LPX700
	24 (60)	Non-Replaceable	24D0AS3884C	84	.050	3/8	72LPX84CQ	7/32 in.	-
	24 (60)	Replaceable	24D0PS3881C*	81	.050	3/8	72LPX81CQ	7/32 in.	-
	16 (40)	Replaceable	16D0PS3860C*	60	.050	3/8	72LPX60CQ	7/32 in.	-
	18 (45)	Replaceable	18D0PS3866C*	66	.050	3/8	72LPX66CQ	7/32 in.	-
CS-620P/620PW/680	20 (50)	Replaceable	20D0PS3870C*	70	.050	3/8	72LPX70CQ	7/32 in.	72LPX700
	24 (60)	Replaceable	24D0PS3881C*	81	.050	3/8	72LPX81CQ	7/32 in.	-
	27 (68)	Replaceable	27D0PS3893C*	93	.050	3/8	72LPX93CQ	7/32 in.	-
	20 (50)	Replaceable	20D0PS3870C*	70	.050	3/8	72LPX70CQ	7/32 in.	72LPX700
	24 (60)	Replaceable	24D0PS3881C*	81	.050	3/8	72LPX81CQ	7/32 in.	-
CS-800P	27 (68)	Replaceable	27D0PS3893C*	93	.050	3/8	72LPX93CQ	7/32 in.	-
	32 (80)	Replaceable	32D0PS3805C*	105	.050	3/8	72LPX105CQ	7/32 in.	-
	36 (90)	Replaceable	36D0PS3816C*	116	.050	3/8	72LPX116CQ	7/32 in.	-
CCS-58V4	16 (40)	Non-Replaceable	16A4CD3756C	56	.043	3/8 lp	90PX56CQ	4.5 mm	-
		BAR	<b>D - F</b>		Link Onumb	0	CHAIN	Obalia Daub #	E:1. 0
Power Pruner® Models PPF-225, 99944200532	Length in. (cn 10 (25)	n) Nose Non-Replace	Bar F able 10A0CI		Link Count	Gauge (in.) .050	<b>Pitch (in.)</b> 3/8 lp	Chain Part # 91VXL39CQ	File Siz
PF-225, 99944200532 PF-2620, PPT-2620/H	10 (25) 12 (30)	Non-Replace			39 44	.050	3/8 lp 3/8 lp	91VXL39CQ 91VXL44CQ	5/32
PF-225, PPF-2620,	12 (30)	Non-Replace		037440 037390	39	.043	3/8 lp	90PX39CQ	4.5 mm
	10(20)	non nopiaco	10/1401		50	.010	or or ip	00170000	1.0 1111

The part numbers listed above	e (e.a	91PXL52C0)	include a	two-or the
nio pur inumboro notou ubov	0 (0.g	. OI <u>I AL</u> OLOQ)	inoiuuo u	two or un

### Chain Type: LOW-KICK BACK CHAIN

- **PX** Low-vibration chisel cutters with ramped depth gauges, bumper drive links and standard sequence.
- BPX Low-vibration chisel cutters with bumper drive links and standard sequence.
- PXL Low-vibration semi-chisel cutter with ramped depth gauges, bumper drive links and longer top plate.



**CHAIN SAW ACCESSORIES** 



Blued cutters provide superior corrosion resistance and longer life.

Ip=Low Profile \* solid bars, all other bars are laminated

nree-letter code that references the chain type. See detailed descriptions below.

### Chain Type: PROFESSIONAL CHAIN

LPX Round-ground chisel cutters with bumper drive links and standard sequence. VXL Low-vibration semi-chisel cutter with ramped depth gauges and longer top plate.



### **CHAIN SHARPENING FILES**

A sharp chain makes all the difference in cutting speed, productivity, comfort, and safety. A wellsharpened chain reduces chain saw servicing costs, makes your work easier and prevents accidents. Check the chart on page 41 to find the appropriate file size for your model.



File Part #		Des	cription			
99988801700	5/32 in.	4.0 mm	File, 2-Pack			
99988801720	5/32 in.	4.0 mm	File, (5 ct.) Box of 12			
99988801701	11/64 in.	4.5 mm	File, 2-Pack			
99988801721	11/64 in.	4.5 mm	File, (5 ct.) Box of 12			
99988801702	3/16 in.	4.8 mm	File, 2-Pack			
99988801722	3/16 in.	4.8 mm	File, (5 ct.) Box of 12			
99988801703	13/64 in.	5.2 mm	File, 2-Pack			
99988801723	13/64 in.	5.2 mm	File, (5 ct.) Box of 12			
99988801704	7/32 in.	5.5 mm	File, 2-Pack			
99988801724	7/32 in.	5.5 mm	File, (5 ct.) Box of 12			
99988800730	6 in.	152 mm	Flat File, Box of 12			
99988801761			File Handle, , Pkg of 1			
99988801762	Plastic File Handle, Orange, Retail Pkg of 1					
99988801763			File Handle, splay Box of 20			

### CHAIN SHARPENING KITS

Each kit contains all the tools you will need to sharpen your chain and service the guide bar, including (2) round files, (1) flat file, file guide, depth gauge, and plastic handle presented in a rugged, practical carrying pouch.

Kit Part #	Description
99988800720	5/32 in. Chain Sharpening Kit
99988800721	11/64 in. Chain Sharpening Kit
99988800722	3/16 in. Chain Sharpening Kit
99988800723	13/64 in. Chain Sharpening Kit
99988800724	7/32 in. Chain Sharpening Kit

### **BAR AND CHAIN COMBOS**

### VALUE + CONVENIENCE = ONE GREAT COMBINATION

Keep maintenance easy with bars and chains in one package.

12 in. For CS-271T/303T/310/352: Part # 12A0CD91PX 14 in. For CS-303T/310/352/370/370F: Part # 14A0CD91PX 16 in. For CS-303T/310/352/370/370F/400/400F: Part # 16A0CD91PX 18 in. For CS-370/370F/400/400F: Part # 18A0CD91PX 20 in. For CS-590: Part # 20D0AST2LPX



### CHAIN SAW TIP GUARD

Protect against kick-back by preventing saw's tip from making contact with logs & branches.

CS-271T through CS-400: Part # 2894902 CS-450 through CS-800P: Part # 2893202

### **FASTENSION**<sup>™</sup>

Allows for guick and easy chain adjustment without tools.

For CS-370 and CS-400 only. Part # 99988802200

### **PLASTIC SCABBARD**

Marked in 2 in. increments to be cut anywhere between 12 in. and 20 in. in length.

Retail Pkg of 1: Part # 99988801595 Display Box of 12: Part # 89850308034



### FELLING WEDGES

Designed to prevent chain saw pinching while cutting. Made of durable plastics to withstand extreme conditions and temperatures.





### **BUMPER SPIKE**

Designed to provide more leverage while making a cut.

For CS-590: Part # 99988802100\* \*optional for right side mount For CS-271T: Part # C304000070 For CS-2511T: Part # C304000000\* \*optional for left side mount

Keeps engine clear of palm debris.



CS-361P: Part # 91208 (add-on) CS-355T: Part # 91209 (optional) CS-2511T: Part # A127000480 (optional)

### **STUMP VISE**

For easy in-woods chain sharpening.

Part # 99988801808

Part #	Length (in.)	Description	Qty.
99988801802	5.5	Smooth Wedge	24
99988801803	5.5	Spiked Wedge	24
99988801806	5.5	Smooth Wedge	1
99988891807	5.5	Spiked Wedge	1
99988801800	8	Smooth Wedge	12
99988801801	8	Spiked Wedge	12
99988801804	8	Smooth Wedge	1
99988801805	8	Spiked Wedge	1

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

### **CHAIN SAW CASES**

Protect your chain saw - it's worth protecting. Chain saws take a beating in the field; give them a break and protect them in between use with one of ECHO's high-quality durable storage cases. ECHO chain saw cases are built from the highest quality components and protect your saw from the elements.

### ToughChest<sup>™</sup> Chain Saw Cases

Solid, high-quality carrying case for your chain saw featuring interior slots for files, chain, glasses, oil and more. A multi-function case to protect your investment and offer longevity and durability. Does not fit CS-620P/PW.

Dimensions: 20 in. (L) x 12 in. (W) x 12.5 in. (H)

ToughChest - 20 Chain Saw Case ECHO saws with up to 20 in. bar Part #: 99988801210



ToughChest - 24 Chain Saw Case ECHO saws with up to 24 in. bar Does not fit CS-590 with 24 in. DOAS bar

Part #: 99988801211 32 in. Scabbard only for ToughChest - 20 & 24 ECHO saws with up to 32 in. bar

### **CHAIN SAW PERSONAL PROTECTION**

Safety should always be a priority when working with power tools. This should begin by using correct working methods, while also using high-quality equipment and the appropriate protective safety clothing. At ECHO, we take safety very seriously and offer a wide range of protective clothing to meet this need, from full chain saw protection clothing to helmets and gloves.

### Chain Saw Chaps

Part # 99988801212

Features six layers of protective material for superior protection and durability. An expandable 30 in. - 42 in. waist accommodates a variety of body types. Meets OSHA standards for leg protection. UL classified in accordance with ASTM F1897-2014.

### Not for use with cordless chain saws.

36 in. Long, Apron Design Part #: 99988801300 40 in. Long, Apron Design Part #: 99988801301 36 in. Long, Full Wrap Design Part #: 99988801302 40 in, Long, Full Wrap Design Part #: 99988801303

### **Arborist Pants**

Designed with eight layers of protective material in stretch nylon for comfort and flexibility. Features five pockets, trouser hooks and articulated knees to prevent pulling at waist. Length: 32 in.

### Meets OSHA standards for leg protection.

Not for use with cordless chain saws.

32 in 34 in. Waist Part #: 99988801304
36 in 38 in. Waist Part #: 99988801305
40 in 42 in. Waist Part #: 99988801306

## 44 in. - 46 in. Waist Part #: 99988801307



M Part #: 99988801600 L Part #: 99988801601 XL Part #: 99988801602 XXL Part #: 99988801603







42









### **CHAIN SAW ACCESSORIES**

### 20 in. Chain Saw Carry Bag

Constructed with heavy-duty Cordura® material and reinforced bottom and side panels to support the weight of the saw. Weather resistant with interior pockets for accessories and strap to secure saw.

Dimensions: 18.5 in. (W) x 12 in. (W) x 11.5 in. (H)

Part #: 103942147

### **Small Chain Saw Case**

Fits most small to medium sized saws and ECHO saws up to the CS-501 with an 18 in. bar. Light and portable to take on the go or for easy storage.

Does not fit CS-4510 or cordless chain saw CCS-58V4AH

Dimensions: 17.5 in. (L) x 12 in. (W) x 11.5 in. (H)

Length with scabbard: 33 in.

Part #: 99988801213

### **Chain Saw Safety Kit**

Includes helmet, earmuff (NRR 22 dB(A)) & visor screen system, safety glasses, work gloves (size L), and professional apron-style leg chaps.

Length: 36 in.

Expandable waist: 30 in. - 42 in. Part #: 99988801527

### **Chain Saw Safety Helmet System**

Includes helmet, mesh face visor, and ear protection.

Hearing: NRR 22 dB(A) rated

Part #: 99988801500

### **Replacement Parts:**

Harness Part #: 99988801501 Screen Part #: 99988801502 Visor Frame Part #: 99988801503 Ear Muffs Part #: 99988801504





43







### **TRIMMER & BRUSHCUTTER ACCESSORIES**



Our patented, revolutionary Speed-Feed® trimmer heads take the hassle out of refilling your trimmer head and are the easiest loading tap-to-advance heads available.

- No disassembly required; easy to load
- Reload trimmer line in 30 seconds or less
- Rugged head for medium/heavy-duty applications •
- Advance line by tapping the bottom of the head on the around
- Smooth bottom enables the head to glide along the ground for an even cut

### EASY AS



### 2. FEED LINE LINE UP ARROWS

### **3.** TWIST TOP DISC TO WIND

### SPEED-FEED® 400

- Accepts 20 ft. of .095 in. line
- Maximum line diameter: .105 in.
- Comes pre-loaded with .095 in. Cross-Fire<sup>®</sup> line
- Universal head also fits other competitor trimmer models

SRM Models Part #: 99944200907\* \*Universal fit model

GT Models Part #: 99944200908

Bulk Pkg of 24 Part #: 99944200907B

### SPEED-FEED<sup>®</sup> 450

44

- Accepts 25 ft. of .095 in. line
- High Capacity maximum line diameter: .130 in.
- Comes pre-loaded with .095 in. Cross-Fire<sup>®</sup> line

**Speed-Feed® 450 Part #:** 99944200903

// *| | | | |* 

### ECHOmatic<sup>®</sup> & ECHOmatic<sup>®</sup> Pro<sup>™</sup>

The industry's standard for commercial landscapers with easy bumpto-advance operation and simple, durable construction.

- Designed to fit ECHO SRM models only
- Comes pre-loaded with 20 ft. of .095 in. Cross-Fire<sup>™</sup> line
- Manual load design

### ECHOmatic<sup>®</sup> Pro<sup>™</sup>

- Designed for more demanding tasks
- 2-piece construction with partitioned spool reduces line tangles
- Accepts 20 ft. of .095 in. line
- Maximum line diameter: .130 in.

Single Pkg Part #: 21560031 Bulk Pkg of 8 Part #: 21560031B

### **ECHOmatic**<sup>®</sup>

- Accepts 20 ft. of .095 in. line
- Maximum line diameter: .105 in.

Single Pkg Part #: 21560070 Bulk Pkg (8) Part #: 21560070B

# RAPID-L 💽 ADER"

Loading line has never been guicker or easier. Simply insert the 8 in. pre-cut lengths into the eyelets and start trimming.

- No winding line, no disassembly needed
- Comes with .095 in. pre-cut Cross-Fire<sup>®</sup> line

### 2-Line Rapid Loader<sup>®</sup> Head

- Perfect for smaller jobs or open areas without obstacles.
- Accepts 8 in. strips of .095 in. and .105 in. Cross-Fire<sup>®</sup> line

### For most ECHO trimmers\*

Single Pkg Part #: 21560056

Bulk Pkg of 24 Part #: 21560056B \*see chart for details

### For non-ECHO units\*:

Accepts 8 in. strips of .080 in.-.130 in. pre-cut Cross-Fire<sup>®</sup> line

Single Pkg Part #: 21560062 \*includes universal mounting hardware

### 3-Line Rapid Loader<sup>®</sup> Head

50% more cutting ability for more demanding jobs.

Fits certain SRM models\*

Single Pkg Part #: 99944200221

\*see chart for details



WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

### **ADDITIONAL TRIMMER HEADS**



### **High-Capacity Manual Head**

- Traditional design for rugged use
- Accepts 40 ft. of .095 in. line
- Maximum line diameter: .130 in.
- For most ECHO SRM models Single Pkg Part #: 21560065

Bulk Pkg of 8 Part #: 21560065B

### conditions Maximum line diameter: .130 in. Round

٠

### Fixed Line Head Part #: 999442002

High Torgue Part#: 99944200225

### **TRIMMER HEAD FIT CHART**

Model	SRM ECHOmatic®	SRM ECHOmatic <sup>®</sup> Pro™	SRM Heavy-Duty Fixed	SRM Heavy- Duty Fixed (High Torque)	Speed-Feed® 400	Speed-Feed® 450	High-Capacity Manual	2-Line Rapid- Loader™	3-Line Rapid- Loader™	Maxi-Cut <sup>™</sup>	Pro Maxi-Cut
Part #	21560070	21560031	99944200220	99944200225	SRM: 99944200907 GT: 99944200908	99944200903	21560065	21560056	99944200221	215311	215511
For Trimmers											
GT-225											
GT-225i											
GT-225SF											
GT-225L											
SRM-225											
SRM-225i											
SRM-230											
SRM-266											
SRM-2620											
SRM-2620T											
SRM-3020						•					
SRM-3020T											
For Brushcutters	5										
SRM-225U											
SRM-2620U											
SRM-3020U											
Stand. Line Dia. / Max Dia.	.095 in./.105 in.	.095 in./.130 in.	.130 in./.155 in.	.130 in.	.095 in./.105 in.	.095 in./.130 in.	.095 in./.130 in.	.095 in./.130 in.	.095 in./.155 in.	NA	NA
										Standar	rd 🔳 Optional

Model	SRM ECHOmatic®	SRM ECHOmatic® Pro™	SRM Heavy-Duty Fixed	SRM Heavy- Duty Fixed (High Torque)	Speed-Feed <sup>®</sup> 400	Speed-Feed® 450	High-Capacity Manual	2-Line Rapid- Loader™	3-Line Rapid- Loader™	Maxi-Cut <sup>™</sup>	Pro Maxi-Cut™
Part #	21560070	21560031	99944200220	99944200225	SRM: 99944200907 GT: 99944200908	99944200903	21560065	21560056	99944200221	215311	215511
For Trimmers											
GT-225											
GT-225i											
GT-225SF											
GT-225L											
SRM-225											
SRM-225i											
SRM-230											
SRM-266											
SRM-2620											
SRM-2620T											
SRM-3020											
SRM-3020T											
For Brushcutters											
SRM-225U											
SRM-2620U											
SRM-3020U											
Stand. Line Dia. / Max Dia.	.095 in./.105 in.	.095 in./.130 in.	.130 in./.155 in.	.130 in.	.095 in./.105 in.	.095 in./.130 in.	.095 in./.130 in.	.095 in./.130 in.	.095 in./.155 in.	NA	NA
										Standar	d 🔳 Optional 📕





















See page 46 for Rapid Loader® pre-cut line.



**Heavy-Duty Fixed Line Head** Aluminum body for the most demanding

Can be loaded in 2 or 4-line configurations

• Comes with (2) 16 strips of Round line



### Maxi-Cut<sup>™</sup> and Pro Maxi-Cut<sup>™</sup>

- 3 serrated-edge polymer blades for heavy grasses and weeds
- Use when traditional trimmer line is not durable enough for dense cutting

For ECHO GT Model Part #: 215311 - Maxi-Cut For ECHO SRM Models\* Part #: 215511 - Pro Maxi-Cut Replacement Blades (12 pk) Part #: 215712



### NYLON TRIMMER LINE

### **BLACK DIAMOND<sup>™</sup>**

twisted, square edges



### **CROSS-FIRE®**

### multi-sided edges



### ROUND



### **SILENTWIST**<sup>™</sup>



DIACK DIAMONU				
	.095 in.	ft.	.105 in.	ft.
Lg. Clam	330095071	253	330105071	217
Med. Spool	330095073	885	330105073	708
Lg. Spool	330095075	1,394	330105075	1,132
<ul> <li>Ideal for all resident</li> </ul>	ial and commercial job	s; • Twisted	design reduces noise	levels and trimmer

• Twisted design reduces noise levels and trimmer vibrations, while its square edges deliver optimum cutting performance

• Resistant to welding and high temperatures

01033-1116												
	.065 in.	ft.	.080 in.	ft.	.095 in.	ft.	.105 in.	ft.	.130 in.	ft.	.155 in.	ft.
Mini Clam	102152652	40	102152802	40	102152953	40						
Small Clam	306065051	305	306080052	201	306095053	141	306105055	117				
Lg. Clam			311080062	402	311095063	282	311105065	234	311130064	150	311155066	126
Med. Spool			314080052	1,206	314095053	846	314105055	702	314130054	450	314155056	378
Lg. Spool			316080052	2,1010	316095053	1,410	316105055	1,170	316130054	750	316155056	630
Rapid Loader® P	re-cut											
	.080 in.		.095 in		.105 in	I.	.130 in		.155 in.			
10 count, 8 in. L	102202953		102202952		1022021	05	1022021	30	102202155			
20 count, 8 in. L	102212131		102212952		1022121	05	1022121	30	102212155			
50 count, 8 in. L	102222156		1022229	52	1022221	05	102222130		10222215	55		

 Ideal for medium duty jobs, larger lawns and heavier
 Delivers better efficiency in cutting time weeds

medium to heavy rugged weeds

heads

round

• Razor sharp edge for fast, clean cutting

· Works on most brands of gas-powered trimmer

- 8 cutting edges offer a more even, cleaner cut over
- Resistant to welding and high temperatures Works on most brands of gas-powered trimmers

Round								
	.080 in.	ft.	.095 in.	ft.	.105 in.	ft.	.130 in.	ft.
Mini Clam	102142802	40	102142952	40				
Sm. Clam	305080052	210	305095053	141	305105055	117		
Lg. Clam	310080062	402	310095063	282	310105065	234	310130064	150
Med. Spool	313080052	1,206	313095053	846	313105055	702	313130054	450
Lg. Spool	315080052	2,010	315095053	1,410	315105055	1,170	315130054	750

 Ideal for home or commercial multipurpose use • Long lasting and durable against hard surfaces

### · Easy to replace in trimmer head · Works on most brands of gas-powered trimmer

heads

Silentwist™						
	.080 in.	ft.	.095 in.	ft.	.105 in.	ft.
Mini Clam	320080060	40	320095060	40	320105060	40
Sm. Clam	321080060	160	321095060	115	321105060	90
Lg. Clam	322080060	320	322095060	230	322105060	185
Med. Spool	323080060	960	323095060	685	323105060	550
Lg. Spool	324080060	1,600	324095060	1,140	324105060	920

cut

- Ideal for cordless trimmers or small to light residential areas
- Decreases vibration for reduced noise levels

### WHAT LINE DIAMETER DO YOU NEED?

LIGHT WEEDS: small residential areas: - .065 in.-.080 in

46

MEDIUM WEEDS: larger residential areas or light commercial areas: - .085 in.-.105 in.

HEAVY WEEDS: industrial landscaping, commercial landscaping, large estates and residential areas: - .110 in. +

Improves fuel and battery consumption

Increases cutting time efficiency with a clean, even



WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

10 in. dia. 20 mm Arbor

dense weeds.

10 in. dia. 25 mm Arbor



Model

Part #

For Trimm

SRM-225/i

SRM-230

SRM-266

SRM-2620/T\*

SRM-3020/T

For Brushcu

SRM-225U

SRM-2620U\*

SRM-3020U

SRM-410U

Small Weeds

Large Weeds

### 8-Tooth Grass and Weed Blade

The 8-tooth blade is useful for thick grasses and dense weeds.

**BLADES AND CONVERSION KITS** 

etc. when installing optional blades or accessories.

**SEE BLADE FIT CHART** FOR PART NUMBER

3-Tooth Grass and Weed Blade

All blades require conversion kits, see chart below.

The 3-cutter blade is great for thick grasses and

8 in. dia. 20 mm Arbor

8 in. dia. 25 mm Arbor



### **80-Tooth Brush Blade**

The 80-tooth blade is perfect for reeds, heavy grass, and small bushes or saplings.

8 in. dia. 20 mm Arbor up to 2.5 in. cutting diameter



8 in. dia. 25 mm Arbor -Up to 2.5 in. cutting diameter

10 in. dia, 25 mm up to 3.5 in. cutting diameter

### 22-Tooth Saw Blade

The 22-tooth blade is best suited for saplings and other brush up to 2-1/4 in. diameter.

8 in. dia. 20 mm Arbor

8 in. dia. 25 mm Arbor

### **Blade Protectors**

Protect your brushcutter blade from storage wear and tear.

10 in. dia Part #: P021007470

### 8 in. dia Part #: P021016360



Reeds, Bushes, Heavy Grass

Bushes, Small Trees **Edger Attachment** 

Turn your straight shaft trimmer, brushcutter, or bed redefiner into a lawn edger.

### Part #: 99944230001

Fits SRM-230, SRM-266, SRM-2620T and BRD-2620

These kits are useful for converting the standard handles of an SRM trimmer to the bicycle of "U"handle of an SRM-brushcutter.

### See chart for Part #

Model	Offset U-Handle Kit	Blade Conversion	Kit (20 mm Arbor)	Tiller /Cultivator				
		No Blade	W/8 In 80 Tooth Blade					
SRM- 230 (SN: 05001001-07999999)	35130454230	99944200418	99944200422	SRAC-200				
SRM-225/i	99944200435	99944200418	99944200422	SRAC-200				
SRM-266	99944200675	99944200418	99944200422	SRAC-200				
SRM-2620/T*		99944200418	99944200422	SRAC-200				
SRM-3020/T**		99944200418						
SRM-225U/280U/2620U)				SRAC-200				
* 2620 series requires an 8 in. 20 mm blade when using 99944200418 ** 3020 series requires a 10 in. 20 mm blade when using 99944200418								



WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

**Offset U-handle Kits** 

A variety of brush and dense grass blades are available for all ECHO straight shaft (SRM Series) trimmers and brushcutters. A blade conversion kit is required if not supplied with your original trimmer. Refer to your operator's manual for the appropriate safety harnesses, handles, shields,

### **BLADE FIT CHART**

Arbor Size	10 in. 3-Tooth Grass and Weed Blade	8 in. 8-Tooth Grass and Weed Blade	8 in. 80-Tooth Brush Blade	10 in. 80-Tooth Brush Blade	8 in. 22-Tooth Saw Blade
(20mm) (25mm)	99944200047 99944200048	69600120331 69600121431	69500120331 69500121432	69500121431	99944200131 99944200141
landle kit or b	arrier bar is required	l for all metal blades)			
(20 mm)					
(20 mm)			•		•
(20 mm)					
(20 mm)	-				•
(20 mm)					
(20 mm)					
(25 mm)					
(25 mm)	-			-	
(25 mm)					

\*Please note if using a blade conversion kit, you MUST use a 20 mm blade. All blade conversion kits have 20 mm arbors. Standard ■ Optional ■ Blade conversion kit is required for metal blades and tri-cut blade.

### **APPLICATION GUIDE**

~	V			
<b>v</b>	<b>v</b>	<ul> <li>✓</li> </ul>	<b>v</b>	V
✓	✓	<ul> <li>✓</li> </ul>	✓	<b>v</b>
		~	v	<b>v</b>





### **Tiller/Cultivator Attachment**

Turn your trimmer or brushcutter into a ground tiller

Part #: SRAC-200 See chart below for trimmer compatibility.



### **Blade Conversion Kit**

These kits are required for converting the standard string trimming head of an SRM trimmer to a brush or grass and weed blade



### See chart for Part #





### **BLOWER AND SHRED 'N' VAC**

### **Rain Gutter Kits**

Make year-round gutter cleaning easier.

- Designed for use on single story • homes
- Removes leaves and debris from • autters
- Provides up to 15 ft. of reach with 7 ft. of extension tubes

Fits PB-255LN, PB-265LN, PB-755S, PB-2520, PB-2620, and ES-250

### Posi-loc<sup>™</sup> Part #: 99944100026

### Bent Tube

Angled design allows increased control when directing air flow.

Fits PB-760LN and PB-770

Standard Part #: E165000730

### **HEDGE TRIMMER ACCESSORIES**

### Blade Protectors

These guards protect the blades from contact with buildings, fences, or the ground. The guard does not interfere with blade performance.

HC-152, HC-155 and all SHC models Part #: 99988802000

HCA-266/HCA-2620 Part #: 99988802010 For all Single-Sided models Part #: 99988802020 HC-165/HC-2020 Part #: 99988802030



### **POWER PRUNER®ACCESSORIES**

Power Pruner extensions feature a heavy-duty, multi-layer cable that delivers durability and extended life while providing extra temporary reach when you need it.

### Lines Canad

3-ft. Extension for Fixed Pruner Fits all PPF Models: Part # 99946400011

- Extended reach up to 10 ft. 9 in.
- Average reach height\* 165 in. -181 in.

### 4-ft. Extension for Telescoping Pruner

- Fits all PPT Models: Part # 99946400023
- Extended reach up to 16 ft. 2 in.
- Average reach height\* 230 in.

48

\*Avg. reach height = length of unit + height of average individual



echo-usa.com // 800.432.3246

### **TILLER/CULTIVATOR ACCESSORY**

### **Replacement Kickstand for TC-210**

Part #: 99988800900



### **BED REDEFINER ACCESSORIES**

### **Replacement Claw**

6-finger replacement claw that features brazed carbide tips for extended performance and durability designed exclusively for use with the BRD-2620 and PAS Bed Redefiner Attachment.

Part #: 99944208000



### **EDGER ACCESSORIES**

### **Edger Blades**

For edging driveways, sidewalks, flower beds, and other borders

- •
- Length: 7.75 in.



Package of 2 Part #: 69601552632 Bulk Package of 50 Part #: 99944201000

### **Premium Edger Blades**

Twice as thick (.181in.) as the standard blade, premium edger blades are great for edging driveways, sidewalks, flower beds, and other borders.

- Length: 7.75 in.
- Fits on all ECHO edgers



Package of 2 Part #: 69601553630 Bulk Package of 25 Part #: 99944205000

### **Crack Chaser Wire Wheel**

Clears debris from driveways, cracks, sidewalks or payed brick walkways for a clean, well-manicured outdoor space.

www.P65Warnings.ca.gov

- Diameter: 6.875 in. •
- 25 mm arbor •
- Fits on all ECHO edgers •

### Part #: 99944206000



WARNING: Cancer and Reproductive Harm

### SPRAYER ACCESSORIES

A wide variety of accessories are available, from wands to nozzles, to increase the convenience of your manually-operated ECHO sprayer. Each accessory below works with every current ECHO manual sprayer except the MS-1H.

### **MANUALLY-OPERATED SPRAYER ACCESSORIES**

Adding CF valves to your wand or boom can help in conserving chemical mixtures while reducing waste and time by delivering a consistent flow control, independent of input pressure.





**Fan Spray Nozzle** Part #: 99944100350

CF Valve - 15 PSI Part #: 99944100508 CF Valve - 21 PSI Part #: 99944100509

### **WANDS**

ECHO wands are ideal for concentrated spraying application of pesticides, fertilizer, herbicides or watering smaller areas.

40 in. Stainless Steel Wand Part #: 99944100507

40 in. Polypropylene Wand Part #: 99944100506

### BOOMS

•

All ECHO booms are lightweight, flexible and corrosion resistant.





### 2-Nozzle Polypropylene Boom

- Length: 18 in.
- Sprays approx. 48 in. swath •
- Part #: 99944100500

## Part #: 99944100501

Length: 34 in.

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov



Standard .090 in. thickness





Fits on all ECHO edgers

SPRAYER ACCESSORIES



CF Valve - 29 PSI Part #: 99944100510



Spot Spraying Shield with Nozzle

For use with all ECHO wands

• 80% angle for full coverage spraying

Part #: 99944100503



### EARTH/ICE AUGER ACCESSORIES

### **EARTH AUGERS**

All ECHO augers have a 7/8 in. diameter shaft opening. The 6 in., 8 in. and 10 in. diameter augers feature a flex coil design to absorb ground shock better over other augers while slowing impact between blade and rock or other debris for better handling and operation.



**DUAL-BLADE ICE AUGERS** 





**REPLACEMENT BLADES AND POINTS** 



Weight: 15 lbs.

Part #: 99944900190



Part #: 99944900200

H. M.

10 in. Earth

Auger Blade

0-

Ice Auger Point

Part #: 99944900275

**Pro II Glasses** frame.



### **Tiger Glasses**

Curved, suspended, gray-tint lens, cushioned flexible temple pieces with five-position ratcheting angle adjustment, nose piece with three-position width adjustment.

Part #: 102922455



Multi-color tinted lens with grav Part #: 102922452

SAFETY GLASSES

**Tech Glasses** 

lens and frame.

Part #: 102922451

Integrated nose piece, non-slip

rubber template tips, gray tinted

**Traveler Glasses** Seamless curved lens for increased side protection, nose buds, length-adjustable temple pieces.

Part #: 102922453

### **SAFETY GLOVES**

### Sport/Landscape Gloves Flexible nylon with form-fitting fingers

and Velcro®-type wrist band for tight fit. M Part #: 103942194 L Part #: 103942196

Vibration-reducing Sport/

XL Part #: 103942197

Landscape Gloves



Short Sleeve - M Part #: 99988801809 Short Sleeve - L Part #: 99988801810 Short Sleeve - XL Part #: 99988801811 Short Sleeve - XXL Part #: 99988801812 Long Sleeve - M Part #: 99988801813 Long Sleeve - L Part #: 99988801814 Long Sleeve - XL Part #: 99988801815 Long Sleeve - XXL Part #: 99988801816

### Safety Vests

Highly visible vest features 5-point tear-away panels for safety. L Part #: 99988801400 XL Part #: 99988801401 XXL Part #: 99988801402

### Hearing Protection Helps reduce potentially harmful noise

emissions from damaging hearing. NRR 29 dB(A) rating. Meets ANSI 3.19 standards

Part #: 99988801520

### Premium Brushcutter Harness

Featuring 4 point suspension system enabling easier handling and reduces weight-bearing. Padded shoulder straps for comfort with quick-release pin for safety. Max waist size: 40 in.

Part #: 99944200202



### **EXTENSION SHAFTS**

ECHO extension shafts are compatible with 3 in.-10 in. earth augers. Not for use with 12 in. or longer earth augers



50

18 in. Extension (7/8 in. dia.) Part #: 99944900210

### **ENGINE DRILL ACCESSORIES**

///=H;//









3 in. dia. Heavy-duty

Auger (18 in. L)

Part #: 99944900061

7 in. dia. Gallon Pot

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

Earth Auger Adapter with Spring

Converts 7/8 in. to 1 in. dia.

Part #: 99944900335

**Keyless Chuck** 

**Keved Chuck** 

Part #: 99944900320

Part #: 99944900321

Premium, padded leather palm to reduce vibration, form-fitting fingers, and Velcro®-type wrist band for tight fit.

M Part #: 103942195 L Part #: 103942198 XL Part #: 103942199

**Heavy-duty Work Gloves** Features leather palms and fingers to offer durability and protection against most elements and sharp objects. Part #: 103942074

**Earplugs with Case** 

ANSI and OSHA approved. Carrying case keeps earplugs clean and ready to go. NRR 23 dB(A). Part #: 103942210

### **Brushcutter System**

Includes steel mesh face visor and ear muffs offering excellent face and ear protection while trimming or clearing brush. NRR 24 dB(A) rating. Part #: 99988801510



WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov











ECHO Safety Glasses are lightweight and impact resistant. Hard-coated, optical-grade, abrasion-resistant, polycarbonate lenses offer 99.9% protection from the most intense UV rays. All models meet ANSI Z87.1-2003 performance criteria.



### Jet Glasses

- Matte black plastic frame with rubber nose piece, removable foam pad around the lens, removable elastic head bank, mirrored tinted lenses with anti-fog coating.

Part #: 102922457



### **Aviator Goggles**

Removable full-wrap foam pad around lens, foam nose piece, mirrored gold-tint anti-glare lens with anti-fog coating, four-position ratcheting angle adjustment, full wrap-around adjustable elastic headband, lengthadjustable temple pieces.

Part #: 102922458

### SAFETY GEAR











### Shin Guards

Lightweight with padded shins and Velcro® straps for easy on/off access. Water resistant, won't absorb extra moisture in tall grass to weight user down.

- Fits up to 23 in. calf circumference
- Dimensions: 18 in. H x 9 in. W

Part #: 103942180

### Equipment Bag

Carryall solution for work gear and/or extra accessories to keep everything in one place.



Part #: 103942145

### Shoulder Straps

A shoulder strap is helpful for supporting the weight of a trimmer or brushcutter. Fits up to 46 in. waist. Cross-body fit: 52 in.

SRM Models Part #: 99944200200 \*Use SRM strap for GT-225L GT Models Part #: 99944200201



echo-usa.com // 800.432.3246



### Tech Glasses

Matte black plastic frame with gray tint lens, non-slip rubber pads on temple tips, gray tint side lenses.

Part #: 102922456



Clear Glasses

Economical, clear glasses, same as those included with ECHO units. Fit over most prescription glasses.

Part #: 102922051







# YOU GAN DO IT! IT'S EASY

BE PROACTIVE. By staying on top of recommended maintenance schedules, you not only prolong the life of your ECHO equipment, but also save time and money by reducing large scale repairs often incurred by not properly maintaining equipment.

OU CAN

- **EXTEND THE LIFE** of your equipment.
- REDUCE COSTLY REPAIRS and downtime with routine maintenance.
- **SAVE MONEY** doing installation yourself. You can do it! It's easy!
- **SAVE TIME** with everything you need in one convenient package.
- GENUINE ECHO REPLACEMENT PARTS

deliver high-performance results.



**TUNE-UP KIT** 



### **AIR FILTER KIT FUEL SYSTEM KIT**

- Air Filter • Lid Cleaner
- Lid Fastener
- Grommet Gasket
- Purge Bulb

Fuel Filter

• Fuel Lines

# **REPAIR CAN BE COSTLY... MAINTENANCE SAVES YOU TIME & MONEY**

Air Filter

• Fuel Filter

Spark Plug

A COMPLETE OFFERING OF MAINTENANCE KITS • TUNE-UP KITS • FUEL SYSTEM KITS • COMMON WEAR ITEMS

echo-usa.com/you-can



52

echo-usa.com // 800.432.3246



### MAINTENANCE KIT DIRECTORY

Model	Tune-Up Kit	Fuel System Kit	Gas Cap	Spark Plug	Purge Bulb	Air Filter Kit	Guide Bar Nu
Bed Redefiner							
BRD-2620	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
Chain Saw							
CS-2511T	90196Y	NA	NA	90186Y	90249Y	NA	NA
CS-271T	90178Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-303T	90149Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-310	90121Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-352	90175Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-355T	90144Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-370/F, CS-400	90155Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-4510	90197Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-490, CS-501P	90174Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-590, CS-620P/PW	90167Y	NA	NA	90114Y	90249Y	NA	90250Y
ledge Trimmer							
IC-155	90152Y	90188Y	90247Y	90114Y	90249Y	NA	NA
IC-2020	90152Y	90191Y	90247Y	90114Y	90249Y	NA	NA
IC-2420, HC-3020, HCS-3020, HCS-4020	90152Y	NA	NA	90114Y	90249Y	NA	NA
ICA-2620	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
HC-225/S	90152Y	90139Y	90247Y	90114Y	90249Y	90116Y	NA
HC-2620	90181Y	90182Y	90247Y	90186Y	90185	NA	NA
ro Attachment Series™							
AS-225/SB	90152Y	90127Y	90247Y	90114Y	90249Y	90116Y	NA
AS-2620	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
Blower							
B-2520	90183Y	90184Y	90247Y	90114Y	90249Y	NA	NA
B-255LN	90154Y	90130Y	90247Y	90114Y	90249Y	NA	NA
B-2620	90192Y	90193Y	90247Y	90114Y	90185Y	NA	NA
B-265LN	90154Y	NA	90247Y	90114Y	90249Y	NA	NA
B-580H/T	90156Y	90158Y	90247Y	90114Y	90249Y	NA	NA
B-755SH/ST	90156Y	90133Y	90247Y	90114Y	90249Y	NA	NA
В-770Н/Т	90122Y	NA	90247Y	90114Y	90249Y	NA	NA
B-8010H/T	90194Y	90195Y	90247Y	90186Y	90249Y	NA	NA
dger							
E-225	90152Y	90127Y	90247	90114Y	90249Y	90116Y	NA
E-2620/S	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
ower Pruner®90182Y							
PF-225	90152Y	90139Y	90247Y	90114Y	90249Y	90116Y	NA
PF-2620	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
PT-2620/H	90181Y	90282Y	90247Y	90186Y	90185Y	NA	NA
Shred 'N' Vac®							
S-250	90152Y	90129Y	90247Y	90114Y	90249Y	90112Y	NA
ïller							
C-210	90152Y	90176Y	90247Y	90114Y	90249Y	90112Y	NA
rimmer/Brushcutter							
it-225/i/L/SF, SRM-225/i/U	90152Y	90127Y	90247Y	90114Y	90249Y	90116Y	NA
RM-230	90152Y	90142Y	90247Y	90114Y	90249Y	90112Y	NA
RM-2620T/U	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
RM-266	90125Y	90137Y	90247Y	90114Y	90249Y	NA	NA
RM-3020/T/U	901231 90181Y	901371 90190Y	90247 F	901141 90186Y	902491 90185Y	NA	NA
SRM-410U	NA	NA	90247Y	NA	901831 90249Y	NA	NA
rimmer Head Maintenance Kit	N/A	IVA	302471	N/A	302431	IVA	IVA
or ECHOmatic <sup>®</sup> Pro Trimmer Head				90113 - Trimmer Spoo			
			00170V Con and C	pring Kit / 90170YB Car			
or Speed-Feed <sup>®</sup> 400 Trimmer Head			501701 - Gap and S	pring fully solvorb Cal	and opining Kit (bulk)		

### **YOUCAN® MAINTENANCE KITS**

\* bold maintenance kits are new

### FEATURES, BENEFITS, AND SPECIFICATIONS

TRIMMERS	GT-225	GT-225i	GT-225SF	GT-225L	SRM-225	SRM-225i	SRM-230	SRM-266	SRM-2620	SRM-2620T	SRM-3020	SRM-3020T
Features and Benefits												
Tool-less air filter cover for easy access	•	•	•	•	•	•	•	•	•	•	•	•
Commercial-grade felt air filtration for long engine life	•	•	•	•	•	•	•					
2-stage commercial-grade air filtration for long engine life								•				
2-stage pleated air filtration for long engine life									•	•	•	•
i-30 <sup>™</sup> starting system for 30% starting effort reduction	•		٠	•	•			•				
i-75 <sup>™</sup> starting system for 75% starting effort reduction		٠				•						
Digital ignition system for easy starting	•	•	•	•	•	•	•	•	•	•	•	•
Purge bulb for easy starting	٠	٠	•	٠	٠	•	•	•	•	٠	•	•
Ergonomic throttle handle with rubber grip for comfort				•	•	•	•	•	•	•	•	•
Ergonomic, adjustable front handle for a custom fit	٠	٠	•	٠	٠	•	•	•	•	٠	•	•
Debris shield with integrated cut-off knife for optimal line length	•	•	•	•	•	•	•	•	•	•	•	•
Engine vibration-reduction system for operator comfort				•	٠	•						
Extra heavy-duty vibration-reduction system for operator comfort							٠	٠	•	•	•	•
Speed-Feed® 400 cutting head for easy reloading			٠	•	٠	•	•	•	•	٠		
High-capacity Speed-Feed® 450 cutting head for more line											•	•
Powerhead components made from magnesium									•	•	•	•
Dual piston ring design for long engine life									•	•	•	•
2:1 Pro Torque <sup>™</sup> gear case ratio for superior power/cutting										•		•

### **SPECIFICATIONS**

Model	Engine Disp. (cc)	Carburetor (w/Purge Pump)	Fuel Capacity (fl. oz.)	Shaft Length (in)	Shaft Type	Starting System	Cutting Head	Shield and Cutting Swath (in.)	Drive Shaft	Gear Ratio	Nylon Line (in. dia)	Dry Weight (lb.)*	Dry Weight (lb.)**
GT-225	21.2	Rotary	14.2	48	Curved	i-30™	Rapid Loader®	GT with 16 in. Swath	4-Layer Cable	-	.080 Cross-Fire®	10.1	9.5
GT-225i	21.2	Rotary	14.2	48	Curved	i-75™	Rapid Loader®	GT with 16 in. Swath	4-Layer Cable	-	.080 Cross-Fire®	10.6	10.0
GT-225SF	21.2	Rotary	14.2	48	Curved	i-30™	Speed-Feed® 400	GT with 16 in. Swath	4-Layer Cable	-	.080 Cross-Fire®	10.8	9.5
GT-225L	21.2	Rotary	14.2	55	Curved	i-30™	Speed-Feed® 400	GT with 16 in. Swath	4-Layer Cable	-	.080 Cross-Fire®	11.2	10.2
SRM-225	21.2	Rotary	14.2	59	Straight	i-30™	Speed-Feed® 400	SRM with 17 in. Swath	4-Layer Cable	1.62:1	.095 Cross-Fire®	11.5	11.2
SRM-225i	21.2	Rotary	14.2	59	Straight	i-75™	Speed-Feed® 400	SRM with 17 in. Swath	4-Layer Cable	1.62:1	.095 Cross-Fire®	12	11.7
SRM-230	22.8	Rotary	19.1	59	Straight	Standard	Speed-Feed® 400	SRM with 17 in. Swath	4-Layer Cable	1.4:1	.095 Cross-Fire®	12.2	11.3
SRM-266	25.4	Rotary	16.9	59	Straight	i-30™	Speed-Feed® 400	SRM with 17 in. Swath	4-Layer Cable	1.4:1	.095 Black Diamond™	13.4	12.3
SRM-2620	25.4	Rotary	20.6	59	Straight	Standard	Speed-Feed® 400	SRM with 17 in. Swath	4-Layer Cable	1.62:1	.095 Black Diamond <sup>™</sup>	12.3	11.7
SRM-2620T	25.4	Rotary	20.6	59	Straight	Standard	Speed-Feed® 400	SRM with 17 in. Swath	4-Layer Cable	2:1	.095 Black Diamond™	12.5	11.9
SRM-3020	30.5	Rotary	24	59	Straight	Standard	Speed-Feed® 450	SRM with 20 in. Swath	4-Layer Cable	1.62:1	095 Black Diamond <sup>™</sup>	13.7	12.1
SRM-3020T	30.5	Rotary	24	59	Straight	Standard	Speed-Feed® 450	SRM with 20 in. Swath	4-Layer Cable	2:1	095 Black Diamond™	13.9	12.3
									with cutting he	ad and sl	hield **without cuttir	ng head c	or shield

### BRUSHCUTTERS

### Features and Benefits Tool-less air filter cover for easy access Commercial-grade felt air filtration for long engine life Pleated air filtration for long engine life 2-stage pleated air filtration for long engine life i-30<sup>™</sup> starting system for 30% starting effort reduction Digital ignition system for easy starting Purge bulb for easy starting Ergonomic U-handle with rubber grip for comfort and handling Debris shield with integrated cut-off knife for optimal line length Engine vibration-reduction system for operator comfort Extra heavy-duty vibration-reduction system for operator comfort Shoulder harness included for comfort and convenience Additional shield and hardware included for blade use Speed-Feed<sup>®</sup> 400 cutting head for easy reloading High-capacity Speed-Feed® 450 cutting head for more line and larger line Powerhead components made from high-grade magnesium for light weig Dual piston ring design for long engine life Tool-less U bar adjustment knob for ease of storage **SPECIFICATIONS**

Model	Engine Disp. (cc)	Carburetor (w/Purge Pump)	Fuel Capacity	Shaft Length (in)	Shaft Type	Starting System	Cutting Head	Shield and Cutting Swath (in.)	Drive Shaft	Arbor Size (mm)	Nylon Line (in. dia)	Dry Weight (lb.)*	Dry Weight (Ib.)**
SRM-225U	21.2	Rotary	14.2	59	Straight	i-30™	Speed-Feed® 400	SRM 17 in. Swath w/ Blade Shield	4-Layer Cable	25	.095 Cross-Fire®	13.6	12.7
SRM-2620U	25.4	Rotary	20.6	59	Straight	Standard	Speed-Feed® 400	SRM 17 in. Swath w/ Blade Shield	4-Layer Cable	25	.095 Black Diamond™	13.3	12.4
SRM-3020U	30.5	Rotary	24	59	Straight	Standard	Speed-Feed® 450	SRM 20 in. Swath w/ Blade Shield	4-Layer Cable	25	.095 Black Diamond <sup>™</sup>	14.8	13.2
SRM-410U	42.7	Rotary	33.8	60.2	Straight	Standard	10 in. Brush Blade	Metal Blade Shield	Steel	25	-	19.1	18.3



54



FEATURES, BENEFITS, AND SPECIFICATIONS												
	SRM-225U	SRM-2620U	SRM-3020U	SRM-410U								
	•	•	•									
	•											
				•								
		•	•									
	•	•	•	•								
	•	•	•	•								
	•	•	•	•								
	•	•	•									
	•											
		•	•	•								
	•	•	•	•								
	•	•	•	•								
			•									
le diameters	•	•										
ght and durability		•	•									
		•	•									
		•	•	•								

\*with cutting head and shield \*\*without cutting head or shield



BLOWERS AND SHRED 'N' VAC	PB-2520	PB-255LN	PB-2620	PB-265LN	PB-580H	PB-580T	PB-755SH	PB-755ST	PB-760LNH	PB-760LNT	PB-770H	PB-770T	PB-8010H	PB-8010T	ES-250
Features and Benefits															
Posi-loc <sup>™</sup> pipes for a secure connection	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
i-30 <sup>™</sup> starting system for 30% starting effort reduction				•											
Padded backrest and shoulder straps for comfort				•	•	•	•	•	•	•	•	•	•	•	
Low-noise, 65 dB(A) or less, output for noise-sensitive environments		•		•					•	•					
Pleated, automotive-style air filter for superior filtration			•		•	•	•	•	•	•	•	•	•	•	
Hip-mounted throttle with cruise control			•	•	•		•		•		•		•		
Tube-mounted throttle with cruise control						•		•		•		•		•	
"L"-style frame for impact damage resistance				•	•	•	•	•	•	•	•	•	•	•	
Leaf guard for keeping debris out of fan intake					•	•	•	•	•	•	•	•	•	•	
Extra-flexible tube for cold weather operation				•	•	•	•	•	•	•	•	•	•	•	
Wide-angle tube rotation for optimum mobility				•	•	•	•	•	•	•	•	•	•	•	
Rotational control for reduced operator fatigue	•														•
Rubber top handle grip for comfort and control		•	•												
Parallel handles for all-position operation		•	•												
Flared-end pipe for moving heavy or wet debris		•	•												
Throttle with cruise control for operator convenience	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Professional-grade felt air filtration for long engine life	•														•
35 in. long intake tube for easy reach															•
Patented, 4-blade shredding mechanism for optimum debris reduction															•
2-bushel collection bag with rear zipper for convenient emptying															•
Large professional-grade felt air filtration for long engine life	•	•		•											•

### SPECIFICATIONS

Model	Blower Type	Engine Disp. (cc)	Carb. (Purge Pump)	Starting System	Fuel Cap. (fl. oz.)	Air Volume* (CFM-pipe)	Maximum Air Speed* (MPH-pipe)	Newtons (N)	Noise Level dB(A)	Dry Weight** (lb)
PB-2520	Handheld	25.4	Yes	Standard	18.6	453	170	15.8	70	8.6
PB-255LN	Handheld	25.4	Yes	Standard	16.9	354	191	13	64	10.2
PB-2620	Handheld	25.4	Yes	Standard	20.3	456	172	15.8	70	9.8
PB-265LN	Backpack	25.4	Yes	i-30™	22.3	375	158	11	64	13.3
PB-580H/T	Backpack	58.2	Yes	Standard	62.0	510	215	22	70	22.9/22.6
PB-755SH/T	Backpack	63.3	Yes	Standard	67.6	651	233	28	74	24.7/24.7
PB-760LNH/T	Backpack	63.3	Yes	Standard	68.3	535	214	21	65	26.5/26.2
PB-770H/T	Backpack	63.3	Yes	Standard	68.3	756	234	33	74	24.5/24.3
PB-8010H/T	Backpack	79.9	Yes	Standard	83.8	1,071	211	44	79.3	24.8/24.5
ES-250	Shred 'N' Vac	25.4	Yes	Standard	16.9	391	165	13	70	12.6
1								*per ANSI B	\$175.2-2012 **	with blower pipe

### **ARBORIST CHAIN SAWS**

Features and Benefits
Dual-post chain brake for extra durability
Inertia-type chain brake for safety
Tool-less air filter cover for easy access
Tall profile bar with multi-rivet nose for longer life
Premium chain with extended-length cutters for greater life
Vibration-reduction system for operator comfort
i-30 $^{\scriptscriptstyle\rm TM}$ starting system for 30% starting effort reduction
Spring-assisted starting system for reduced effort starting
Digital ignition system for easy starting and smooth acceleration
Integrated choke and fast idle with trigger release for easy starting
G-Force Engine Air $\ensuremath{Pre-Cleaner}^{\ensuremath{\tiny M}}$ for cleaner air supply to engine
Automatic, adjustable oiler to match cutting conditions
Automatic, adjustable clutch-driven oiler for reduced oil consumption
Replaceable, metal bumper spike for improved control
Side access chain tensioner for quick chain adjustments
Metal lanyard ring for easy attaching and detaching to harness
Optional metal bumper spike for more control
Purge bulb for easy starting

### **SPECIFICATIONS**

Model	Engine Disp. (cc)	Engine Disp. (cu in)	Starting System	lgnition System	Purge Bulb	Oiling System	Vibration Reduction	Available Bar Length (in)	Fuel Cap. (fl. oz.)	Oil Cap. (fl. oz.)	Dry Weight* (lb)
CS-2511T	25.0	1.53	Spring-Assist	Digital	Yes	Auto/Adjustable	Yes	12, 14	6.4	4.7	5.2
CS-271T	26.9	1.64	i-30™	Digital	Yes	Auto/Adjustable**	Yes	12	8.1	5.4	6.6
CS-303T	30.1	1.84	Standard	CDI	Yes	Auto/Adjustable	Yes	12 (14 U.S. only)	8.5	5.1	7.7
CS-355T	35.8	2.19	Spring-Assist	Digital	Yes	Auto/Adjustable**	Yes	14, 16	11.2	8.2	7.7
CS-361P	35.8	2.19	Spring-Assist	Digital	Yes	Auto/Adjustable	Yes	14, 16	10.8	7.8	8.4
				(	+) Bar len	gths available as access	ories only *w	ithout bar and chain	**clutch-driver	***with	manual override

56

EEHD.





FEATURES, BENEFITS, A	ND	SPEC	CIFIC	CATI	ONS
	CS-2511T	CS-271T	CS-303T	CS-355T	CS-361P
	•			٠	
	•	•	•	٠	•
		•		•	•
	•			•	•
	•	•	•	•	•
		•			
	•			٠	•
	•	•		٠	•
	•	•		•	•
	•	•	•	•	•
	•	•		•	•
				٠	•
	•	•	•	٠	•
	•		•	•	
	•	•			
	•	•	•	•	•



### FEATURES, BENEFITS, AND SPECIFICATIONS

REAR HANDLE CHAIN SAWS	CS-310	CS-352	CS-370	CS-370F	CS-400	CS-4510	CS-490	CS-501P	CS-590	CS-620P	CS-620PW	CS-680	CS-800P
Features and Benefits													
Dual-post chain brake for extra durability	•	•	٠	•	•	•	•	•	•	٠	٠		
Inertia-type chain brake for safety	•	•	•	•	•	•	•	•	•	•	•	•	•
Tool-less air filter cover for easy access	•	•	٠	•	•	•	•	•	•	•	•	•	•
Automotive-style air filter for superior filtration			•	•	•							•	
Two-piece air filter for easy cleaning	•	•					•	•	•	•	•		
Round felt air filter						•							
Vibration-reduction system for operator comfort	•	•	•	•	•	•	•	•	•	•	•	•	•
i-30 <sup>™</sup> starting system for 30% starting effort reduction	•	•	•	•	•								
Spring-assisted starting system for reduced effort starting						•	•						
Digital ignition system for easy starting and smooth acceleration	•	•	•	•	•	•	•	•	•	•	•		
Integrated choke and fast idle with trigger release	•	•	•	•	•	•	•	•	•	•	•		
G-Force Engine Air Pre-Cleaner <sup>™</sup> for cleaner air supply	•	•	•	•	•		•	•	•	•	•		
Automatic clutch-driven oiler for reduced oil usage	•	•											
Automatic, adjustable oiler to match cutting conditions			•	•	•								
Automatic, adjustable clutch-driven oiler for reduced oil usage						•	•	•	•	•	•		
Automatic, adjustable oiler with manual override												•	•
Performance Cutting System <sup>™</sup> - upgraded bar and chain								•		•	•	•	•
Replaceable, metal bumper spike for improved control			•	•	•	•	•	•	•	•	•	•	•
Side access chain tensioner for quick chain adjustment	•	•	•		•	•	•	•	•	•	•	•	
Decompression valve for easy starting								•	•	•	•		
Aluminum handle with rubber grip for improved comfort								٠		٠	٠	•	•
Purge bulb for easy starting	•	•	•	٠	•	•							
Wrap handle for more gripping options											٠		
Translucent fuel tank for easy level checks						•		•	٠	٠	٠		
FasTension <sup>™</sup> tool-less chain tensioning system				•									

### **SPECIFICATIONS**

Model	Engine Disp. (cc)	Engine Disp. (cu in)	Starting System	lgnition System	Purge Bulb	Oiling System	Vibration Reduction	Available Bar Length (in)	Fuel Cap. (fl. oz.)	Oil Cap. (fl. oz.)	Dry Weight* (lb)
CS-310	30.5	1.86	i-30™	Digital	Yes	Automatic**	Yes	14, 16	8.5	8.8	8.8
CS-352	34.0	2.08	i-30™	Digital	Yes	Automatic**	Yes	14, 16	8.5	8.8	8.8
CS-370	36.3	2.22	i-30™	Digital	Yes	Auto/Adjustable	Yes	16, 18 (+)	13.9	9.5	10.1
CS-370F	36.3	2.22	i-30™	Digital	Yes	Auto/Adjustable	Yes	16, 18 (+)	13.9	9.5	10.4
CS-400	40.2	2.45	i-30™	Digital	Yes	Auto/Adjustable	Yes	16, 18	13.9	9.5	10.1
CS-4510	45.0	2.75	Spring-Assist	Digital	Yes	Auto/Adjustable**	Yes	16, 18	16.2	11.1	11.0
CS-490	50.2	3.06	Spring-Assist	Digital	No	Auto/Adjustable**	Yes	16, 18, 20	16.6	9.5	10.6
CS-501P	50.2	3.06	Standard	Digital	No	Auto/Adjustable**	Yes	16 (+), 18, 20	16.6	9.5	10.4
CS-590	59.8	3.64	Standard	Digital	No	Auto/Adjustable**	Yes	18, 20, 24	21.8	10.2	13.2
CS-620P/PW	59.8	3.64	Standard	Digital	No	Auto/Adjustable**	Yes	16 (+), 18 (+), 20, 24, 27	21.8	10.2	13.7/14.1
CS-680	66.8	4.07	Standard	SAIS	No	Auto/Adjustable***	Yes	20, 24, 27	21.6	12.5	14.6
CS-800P	80.7	4.92	Standard	SAIS	No	Auto/Adjustable***	Yes	24, 27, 32, 36	27.7	13.5	16.8
					(+) Bar lei	ngths available as acces	ssories only	*without bar and chain	**clutch-driv	en ***with	manual override

### **POWER PRUNERS®**

Features and Benefits	
Tool-less air filter cover for easy access	
2-stage air filter for improved filtration and long engine life	
i-30 <sup>™</sup> starting system for 30% starting effort reduction	
Digital ignition system for easy starting	
Purge bulb for easy starting	
Galvanized steel tube for rigidity and durability	
Aluminum inner drive shaft for torsion strength and light weight	
Ribbed fiberglass outer shaft for rigidity and control	
Ergonomic loop handle with rubber grip for comfort and handling	
In-line handle with rubber grip for comfort	
Shock-absorbing drive shaft prevents damage to shaft	
Automatic, adjustable oiler to match cutting conditions	
Side-access chain tensioner for quick chain adjustments	
Multi-layer flexible cable drive with lifetime warranty for buyer confidence	e
Rubberized front hand location for comfort and vibration reduction	
1.5:1 gear ratio provides torque needed to cut large branches	
Telescoping shaft for a variety of cutting heights	

### **SPECIFICATIONS**

Model	Engine Disp. (cc)	Starting System	Fuel Cap. (fl. oz.)	Oil Cap. (fl. oz.)	Length Collapsed (in)	Length Extended (in)	Optional Extension (ft)		Dry Weight* (lb)
PPF-225	21.2	i-30™	14.2	6.6	94	-	3	10	12.8
PPF-2620	25.4	Standard	20.6	6.6	96	-	3	12	13.2
PPT-2620	25.4	Standard	20.6	6.6	107	146	4	12	17.4
PPT-2620H	25.4	Standard	20.6	6.6	107	146	4	12	17.0

EEHD.



WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

FEATURES, BENEFITS, AND	SPE	CIFI	CATI	ONS
	PPF-225	PPF-2620	PPT-2620	PPT-2620H
	•	•	•	•
		•	•	•
	•			
	•	•	•	•
	•	•	•	•
			•	•
			•	•
			•	
	•	•		•
	•	•	•	•
	•	•	•	•
	•	•	•	•
e	•	•	•	•
	•	•	•	•
			•	•

\*without bar and chain



### FEATURES, BENEFITS, AND SPECIFICATIONS

EDGERS	PE-255	PE-2620	PE-2620S
Features and Benefits			
Tool-less air filter cover for easy access	•	•	•
Professional-grade felt air filtration for long engine life	•		
2-stage pleated air filtration for long engine life		•	•
i-30 <sup>™</sup> starting system for 30% starting effort reduction	•		
Digital ignition system for easy starting	•	•	•
Purge bulb for easy starting	•	•	•
Heavy-duty cylinder/piston plating for increased engine life		•	•
Ergonomic throttle handle with rubber grip for comfort		•	•
Ergonomic, adjustable front handle for a custom fit	•	•	•
Pro-Torque <sup>™</sup> gear case for long-lasting durability		•	•
Metal skid plate for reduced wear to debris shield	•		
Extra wide skid plate for added gear case protection		•	•
Durable, molded shield for reduced material kickback	•		
Clog-resistant, open-face metal shield for reduced clogging		•	•
Sight line on shield for straighter cuts	•	•	•
Heavy-duty adjustable guide wheel with solid rubber tread	•	•	•
Powerhead components made from high-grade magnesium for light weight and durability		•	•
Dual piston ring design for long engine life		•	•
Extra heavy-duty engine vibration reduction system		•	•

### **SPECIFICATIONS**

Model	Engine Disp. (cc)	Fuel Cap. (fl. oz.)	Starting System	Debris Shield	Blade Length (in)	Blade Thickness (in)	Dry Weight (lb)
PE-225	21.2	14.2	i-30™	High-Impact Nylon	7.75	0.090	13.1
PE-2620	25.4	20.6	Standard	Die-Cast Metal	7.75	0.090	14.1
PE-2620S	25.4	20.6	Standard	Die-Cast Metal	7.75	0.090	14.0

FEA	TUR	ES,	BEN	EFIT	S, A	ND S	SPEC	CIFIC	CATI	ONS
	HC-2020	HC-155	HC-2420	HC-3020	HCS-3020	HCS-4020	SHC-225	SHC-225S	SHC-2620	HCA-2620
HEDGE TRIMMERS	÷	ΗĊ	ΗĊ	Ϋ́Ε	HCS	HC	SHC	SHC	SHC	HC/
Features and Benefits										
Tool-less air filter cover for easy access	•	•	•	•	•	•	•	•	•	•
Commercial-grade felt air filter for improved filtration	•	•	•	•	•	•	•	•		
2-stage pleated air filter for improved filtration and long engine life									•	•
Purge bulb for easy starting	•	•	•	•	•	•	•	•	•	•
i-30 <sup>™</sup> starting system for 30% starting effort reduction	•	•	•	•	•	•	٠	٠		
RazorEdge <sup>™</sup> laser-cut, double-reciprocating blades for long-lasting sharpness	•	•	•	•	•	•	•	•	•	•
Blade design with 3 cutting edges for efficient clean cuts		•	•	•	•	•	•	•	•	•
Grease-able gear case for easy maintenance and longer life	•	•	•	•	•	•	•	•	•	•
Rigid support bars for straighter and more precise cuts	•	•	•	•	•	•	•	•	•	•
Tip guard prevents blade contact with buildings, fences, or the ground	•	•	•	•	•	•	•	•	•	•
5-position rotating handle for a variety of cutting positions			•	•						
Vibration-reduction system isolates front and rear handles from engine			•	•						
Rubber overmolded front handle for increased comfort			•	•	•	•	•	•		
Throttle handle with rubber grip for increased comfort							•	•	•	•
Cushioned front handle for increased comfort									•	•
Front facing exhaust helps eliminate bush browning			•	•	•	•				

### **SPECIFICATIONS**

Model	Engine Disp. (cc)	Carb. (w/Purge Pump)	Starting System	Fuel Cap. (fl. oz.)	Blade Length (in)	Shaft Length (in)	Double-Reciprocating Cutter Type	Dry Weight (Ib)
HC-2020	21.2	Rotary	i-30™	13.2	20	-	Double Sided	10.0
HC-155	21.2	Rotary	i-30™	16.9	24	-	Double Sided	11.5
HC-2420	21.2	Rotary	i-30™	12.5	24	-	Double Sided	11.5
HC-3020	21.2	Rotary	i-30™	12.5	30	-	Double Sided	11.9
HCS-3020	21.2	Rotary	i-30™	12.5	30	-	Single Sided	12.1
HCS-4020	21.2	Rotary	i-30™	12.5	40	-	Single Sided	13.1
SHC-225	21.2	Rotary	i-30™	14.2	21	33	Double Sided	12.1
SHC-225S	21.2	Rotary	i-30™	14.2	21	20	Double Sided	12.3
SHC-2620	25.4	Rotary	Standard	20.6	21	51	Double Sided	13
HCA-2620	25.4	Rotary	Standard	20.6	21	59	Double Sided	14.3







PRO ATTACHMENT SERIES <sup>™</sup>	PAS-225	PAS-225VP	PAS-225VPB	PAS-225SB	PAS-2620	CST-58V
Features and Benefits						
Tool-less air filter cover for easy access	•	•	•	•	•	-
Commercial-grade felt air filtration for long engine life	•	•	•	•		-
2-stage air filter for improved filtration and long engine life					•	-
i-30 <sup>™</sup> starting system for 30% starting effort reduction	•	•	•	•		-
Digital ignition system for easy starting	•	•	•	•	•	-
Purge bulb for easy starting	•	•	•	•	•	-
Heavy-duty cylinder/piston plating for increased engine life					•	-
Ergonomic throttle handle with rubber grip for comfort	•	•	•	•	•	-
Ergonomic, adjustable front handle for a custom fit	•	•	•	•	•	-
Engine vibration-reduction system for operator comfort	•	•	•	•	•	-
Attachment Capability						
Curved Shaft Trimmer	•	•	•	•	•	
Speed-Feed® Trimmer	•	•	•	•	•	•
Pro-Torque™ Trimmer	•	•	•	•	•	•
Brushcutter	•	•	•	•	•	•
Bed Redefiner					•	
Blower	•	•	•	•	•	
Curved Shaft Edger	•	•	•	•	•	
Straight Shaft Edger					•	•
Tiller/Cultivator	•	•	•	•	•	•
Hedge Trimmer	•	•	•	•	•	•
Mid-Reach Hedge Trimmer	•	•	•	•	•	•
180° Articulating Hedge Trimmer	•	•	•	•	•	•
3 ft. Extension	•	•	•	•	•	
Power Pruner®	•	•	•	•	•	
Pro Paddle™					•	
Pro Sweep™					•	

### SPECIFICATIONS

Model	Engine Disp. (cc)	Carb. (w/Purge Pump)	Fuel Capacity (fl. oz.)	Starting System	Length* (in.)	Dry Weight (lb)*
PAS-225	21.2	Rotary	14.2	i-30™	40.7	9.3
PAS-225VP	21.2	Rotary	14.2	i-30™	40.7	9.3
PAS-225VPB	21.2	Rotary	14.2	i-30™	40.7	9.3
PAS-225SB	21.2	Rotary	14.2	i-30™	40.7	9.3
PAS-2620	25.4	Rotary	20.6	Standard	40.7	9.9
						*Power Source on

	FEATURES, BENEFI	TS, /	AND	SPE	CIFI	CATI	ONS
SPRAYERS		MS-1H	MS-21H	MS-31H	MS-41BP	MS-41BPD	MS-53BPE
Features and Benefits							
Tank with UV inhibitors for long life		•	•	•	•	•	•
Tank marked in both gallons and liters for convenience			•	•	•	•	•
Ergonomic pump handle for comfortable operation		•	•	•	•	•	•
Fold-away handle with left or right hand operation					•	•	•
Piston-style pump for efficient operation		•	•	•	•		•
3-stage filtration for longer pump and wand life					•	•	
Viton <sup>™</sup> formulation seals for increased durability		•	•	•	•	•	•
Pressure-relief valve for convenient operation			•	•			
28 in. wand trigger with three nozzles for application versatility			•	•	•	•	•
Combo piston/diaphragm pump for higher pressure and extended lifespan						•	

### **SPECIFICATIONS**

Model	Туре	Capacity (gal)	Max. Pressure Rating (psi)	Weight (lb)
MS-1H	Handheld	0.375	45	0.9
MS-21H	Handheld	2	45	6.5
MS-31H	Handheld	3	45	7.6
MS-41BP	Backpack	4	90	9.9
MS-41BPD	Backpack	4	90	10.2
MS-53BPE	Backpack	5	90	12.4

### **CHEMICAL/SOLVENT CHART**

Chemical/Solvent	MS-1H	MS-21H	MS-31H	MS-41BP	MS-53BPE	Chemical/Solvent	MS-1H	MS-21H	MS-31H	MS-41BP	MS-41BPD	MS-53BPE
Acetone						Isopropyl Alcohol	•	•	•	•	•	•
Asphalt						Kerosene	•	•	•	•	•	•
Benzene	•	•	•	•	•	Lacquer Solvents						
Bleach Solutions*	•	•	•	•	•	Latex Paint						
Boric Acid	•	•	•	•	•	Methyl Ethyl						
Denatured	•	•	•	•	•	Naphtha	•	•	•	•	•	•
Diesel Fuel	•	•	•	•	•	Ridomill®	•	•	•	•	•	•
Diozone	•	•	•	•	•	Roundup®	•	•	•	•	•	•
Dow Chemical Path Finder	•	•	•	•	•	Sulfuric Acid	•	•	•	•	•	•
Enamel Paint						Toluene						
Ethyl Alcohol	•	•	•	•	•	Wettable Powders						
Hydrochloric Acid	•	•	•	•	•	Xylene	•	•	•	•	•	•



62



\*up to 5% concentration







f

O

You Tube www.instagram.com/ECHOUSA

www.youtube.com/ECHOUSA

ECHO Incorporated • 400 Oakwood Road, Lake Zurich, IL 60047-1564 • ECHO-USA.COM

For customer service or for your nearest ECHO dealer call toll free 1-800-432-3246. In Canada, call toll-free 1-800-700-1358.

Specifications, descriptions, and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without notice. Illustrations may include optional equipment and accessories and may not include all standard equipment.

> © 2019 ECHO Incorporated, a subsidiary of Yamabiko Corporation. All Rights Reserved. Printed in the U.S.A. #MKT1900001