



“

SNOWPLOWS & ACCESSORIES

MORE JOBS.
DONE FASTER.





“

RISE TO NEW CHALLENGES

**WHETHER OR NOT THEY HAPPEN DURING
REGULAR BUSINESS HOURS**

When plowing is your profession, it's up to you to keep the world moving through winter's worst. Less time worrying about your equipment means more time for clearing lots.

The ticking clock controls your paycheck. Minutes wasted are dollars lost. When your schedule is packed and your budget even tighter, the only thing worth your hard-earned money is *better results*.

That's why Western Products builds efficiency into every feature of our plows and spreaders. With more than 65 years of experience behind us, Western Products knows what it takes to conquer all the depths of winter.

Mother Nature may not offer guarantees—but we build a promise into every piece of equipment we make:


MORE JOBS. DONE FASTER.

UNIVERSAL FEATURES

WESTERN® snowplows are designed and manufactured with universal features that are engineered to maximize efficiency, performance and durability.

ULTRAMOUNT® 2 SNOWPLOW MOUNTING SYSTEM

The exclusive WESTERN UltraMount 2 system is designed for fast and easy installation and removal using a simple mechanical system. It features a robust one-piece design and is 100% compatible with UltraMount® system mounts and electrical platforms.



SIMPLE MECHANICAL SYSTEM

No hydraulic or electrical components to fail, and no tools required.

QUICK AND EASY ATTACHMENT

Drive into the extra-wide, flared receiver brackets. Pull the shoe handle up, pull the lock pin and rotate the handle up. Repeat on the other side and plug in the electrical connections.


DURABLE CONSTRUCTION

The entire UltraMount 2 attachment is built upon a robust A-frame/T-frame construction with three-inch square tubing for extra strength and durability.



EXCLUSIVE ROTATING PIVOT BAR

The patented PIVOT BAR keeps the attaching points level even when the blade is not, for accurate drive-in alignment. It also allows the blade to pivot while plowing on uneven terrain for a cleaner scrape and more even cutting edge wear.



REMOVABLE RECEIVER BRACKETS

Quickly maximize vehicle ground clearance in the off-season. No tools required.

UNIVERSAL FEATURES

CHAIN LIFT SYSTEM

The mechanical chain lift system offers a variety of performance and reliability advantages over a hydraulic system.



CLEAN SCRAPING PERFORMANCE

The chain lift system creates instantaneous “float” when lowering the blade, enabling it to freely follow the contours of the plowing surface for a cleaner scrape.

RELIABLE

With the simple mechanical chain lift design, there are fewer hydraulic and electrical components to worry about, so you can count on long life dependability.

HIGHER STACKING

With a chain lift you can stack snow higher because the plow's movement is not restricted by the length of the ram stroke like on cylinder lift systems.

UNIVERSAL FEATURES



FLEET FLEX ELECTRICAL SYSTEM

The FLEET FLEX electrical system provides true fleet interchangeability. The same CabCommand hand-held or joystick control can operate any UltraMount® and UltraMount® 2 mounted plow on any truck at any time.

Excludes DEFENDER™ plow and IMPACT™ UTV plows



SECURITY GUARD™ ANTI-THEFT SYSTEM

The exclusive WESTERN SECURITY GUARD snowplow anti-theft system is a safe and secure way to electronically lock your snowplow when it is detached from your truck. Unlike physical locks that can easily be cut or removed, the system provides a deterrent against theft by allowing you to electronically lock the snowplow's hydraulic functions, rendering your plow inoperable to unauthorized users.



ISOLATION MODULE

This advanced snowplow light and electrical system features improved electrical pins in the harness plugs for trouble-free connections. An under-hood module improves system life and complies with OEM requirements. No toggle switch is needed to change from vehicle to plow lights.



RELIABLE HYDRAULICS

We manufacture our own hydraulic components to ensure the highest standards of quality and reliability, so that you get a hydraulic system that's not only fast and responsive, but that's built to last season after season.



UNIVERSAL CONTROLS

Choose between a CabCommand hand-held control with push buttons or a joystick control, based on operator preference. For efficient, precise and intuitive blade control while plowing, both controls feature power "on" and "float" LED lights, backlighting for night operation and a plug-in connector for easy removal.



PRE-PUNCHED BLADES FOR ACCESSORIES

Plow blades are pre-punched for easy installation of accessories, providing a custom fit. The pre-punched holes also prevent damage to the powder coat that can sometimes occur when installing an accessory.

UNIVERSAL FEATURES



NIGHTHAWK™ DUAL-HALOGEN HEADLAMPS

NIGHTHAWK dual-halogen headlamps, standard on all new WESTERN® truck plows, feature separate cavities for the low-beam and high-beam lamps. With reflectors designed specifically for each mode, the low and high beams light up the road with brighter performance and greater reach than ever before.

STATE-OF-THE-ART REFLECTOR OPTICS

Provide a smooth, wide beam pattern with minimal glare.

ROBUST TWO-STUD MOUNTING

Keeps headlamps firmly in place, even under the harshest shock and vibration forces.

WATER INGRESSION/RELIABILITY

Ultra-reliable, dual-adhesive seal minimizes water ingress while the GORE-TEX® patch-protected vent allows humidity and condensation out without letting moisture in.

DUAL H9/H11 HALOGEN BULBS

Has an average life of 1,500 hours and is easy to replace through a simple three-screw bulb-access cover.



Excludes IMPACT™ UTV plows.



ULTRAFINISH™ BAKED-ON POWDER COAT

The ULTRAFINISH baked-on powder coat with epoxy primer is standard on all WESTERN plows, providing outstanding protection against wear and rust. Each WESTERN plow goes through an automated pretreatment process and multistage prewash to prepare the plow surface for optimum coating adhesion. Our durable epoxy primer improves corrosion resistance and enhances powder coat adhesion. Robotic guns ensure precise, consistent powder coat coverage. The final baking process seals the long-lasting, hard-as-nails WESTERN red coat. The result is a state-of-the-industry finish that will provide superior protection for your plow, season after season.



EFFICIENCY COMES FROM FLEXIBILITY.

Adapt to whatever the weather throws your way with the WESTERN® WIDE-OUT™* and WIDE-OUT™ XL adjustable wing snowplows. Offered in two blade sizes, the WIDE-OUT XL model extends from 8' 6" to 11' in straight blade mode, making it the widest WESTERN plow for truck applications. The plows are our tallest winged plows at 31", and feature independently controlled, flared wings that retract at the push of a button to maneuver in smaller and tighter areas.

HYDRAULIC WING EXTENSIONS

Independently position each wing to maximize blade width and move more snow. Wings slide laterally across a structurally reinforced slide box.

FLARED WINGS FOR EFFICIENCY

The WIDE-OUT plows feature flared wings as tall as 36" to maximize snowplowing efficiency and aggressively cast snow further while windrowing.

STRUCTURAL REINFORCEMENT

Six vertical ribs—eight on the XL model—a heavy-duty quadrant and a dual WESTERN POWER BAR provide exceptional torsional strength and rigidity across the entire back of the plow blade to eliminate blade twisting.

TRIP BLADE AND WING PROTECTION

Four heavy-duty coil springs protect your plow and truck by allowing the whole blade to trip when striking obstacles. The wings of the snowplow will trip in any position as well, including scoop.

THE WESTERN® WIDE-OUT™ AND WIDE-OUT™ XL ARE FOUR PLOWS IN ONE.



STANDARD CUTTING EDGES

The standard high-carbon steel cutting edge on the moldboard and wings ensures a clean scrape on every pass while reducing wear and extending the life of the blade.

HEAVY-DUTY SLIDE BOX

Structurally reinforced slide box is constructed with 3/16" heavy-grade steel.

HIGH-STRENGTH STEEL BASE CHANNEL

Provides extra support along the bottom of the plow blade.

ACCESSORIES

Back Drag Edge | Rubber Snow Deflector
Shoe Kit | Poly Moldboard Cutting Edge
Poly Wing Cutting Edge | 5/8" Steel Cutting Edge
Shock Absorber

*All product features and specifications listed in this brochure apply to WIDE-OUT snowplows with serial numbers beginning with 180210 and higher



“



MOLDBOARD AVAILABILITY

Powder Coated Steel:
8' model extends to 10' in straight and 8' 10" in scoop
8' 6" model extends to 11' in straight and 9' 10" in scoop
See pages 4-7 for all universal snowplow features.

HEAD OF ITS CLASS.

Get all of the benefits of a winged plow with the simple control of a straight blade with the WESTERN® PRODIGY™ multi-position wing snowplow. The wings automatically adjust to provide the most efficient plowing configuration for the job. This model adds versatility to your fleet without spending time training operators on how to use new equipment, keeping productivity and profitability high.

AUTOMATICALLY ADJUSTING WINGS

Wings automatically adjust into scoop or windrow when you change the plowing angle with the control.

STRUCTURAL REINFORCEMENT

Six vertical ribs and the exclusive WESTERN POWER BAR provide exceptional strength and rigidity across the entire back of the plow blade. Two additional ribs on each wing provide extra reinforcement.

STRAIGHT BLADE CONFIGURATION

When the job calls for a large straight blade, the wings can be pinned into a 9' 8" straight blade configuration.

TRIP BLADE AND WING PROTECTION

Four heavy-duty coil springs allow the whole blade to trip if an obstacle is struck. Wing protection is provided by heavy-duty coil springs and the cable assembly, which automatically return the wings to scoop position.

PRODIGY™

WESTERN® PRODIGY™ PLOWING CONFIGURATIONS.



Straight-ahead scoop mode Angled right for windrowing Angled left for windrowing

STANDARD CUTTING EDGE

A high-carbon steel cutting edge comes standard, reducing wear and extending the life of the blade.

ACCESSORIES

Back Drag Edge | Rubber Snow Deflector Shoe Kit | Shock Absorber

HIGH-STRENGTH STEEL BASE CHANNEL

Provides extra support along the bottom of the plow blade.

WESTERN

“



MOLDBOARD AVAILABILITY

Powder Coated Steel:
8' 7" in scoop mode and 7' 10" fully angled
See pages 4-7 for all universal snowplow features.



RAISE YOUR **GAME.**

Strength is about reliability—while still rising to new challenges. The WESTERN® MVP 3™ v-plow gives you all the power you need to plow through deep snow banks without skipping a beat. It's a plow that won't back down from a little overtime and takes care of business beyond nine to five. Be prepared for all the depths of winter with a WESTERN MVP 3 v-plow.

FLARED WINGS

Wings soar from a 31" center height up to 39" at the outer edge on 9' 6" models to plow through heavy snow or break through snowdrifts.

T-FRAME DESIGN

T-frame provides added strength and allows blade-pitch adjustment to reduce uneven cutting edge wear.

STRUCTURAL REINFORCEMENT

Six vertical ribs on the 7' 6" models and eight on the 8' 6" and 9' 6" models, combined with the exclusive WESTERN POWER BAR, provide exceptional torsional strength and rigidity to eliminate blade twisting.

MASSIVE CENTER PIN AND HINGE

A 1¼"-diameter, heat-treated, steel center pin resides within a three-connection-point hinge, keeping the wings tight for optimal performance.

ULTRALOCK DOUBLE-ACTING CYLINDERS

This standard feature locks the wings together to easily maneuver the plow as a straight blade. The double-acting cylinders also hold the wings firmly in place for clean back dragging.

STEEL CENTER-GAP COVER

For the cleanest pass in any position, the MVP 3™ v-plow has a snow-control deflector over the center hinge to help prevent snow from being lost over the top.

TRIP-EDGE PROTECTION

Each blade features independent trip-edge protection in all configurations, whether in V, scoop or straight, to keep snow in front of the blade.

STANDARD CUTTING EDGE

A high-carbon steel cutting edge comes standard, reducing wear and extending the life of the blade.

LIFT RAM

1¾"-diameter lift ram for more lifting power.

HIGH-STRENGTH STEEL BASE CHANNEL

Provides extra support along the bottom of the plow blade.

ACCESSORIES

Back Drag Edge* | Curb Guards
Plow Wings | Shoe Kit | ½" Steel Cutting Edge
Blade Stops | Rubber Snow Deflectors

*Not compatible with shoe kits on v-plows



“



MOLDBOARD AVAILABILITY

Powder Coated or Stainless Steel: 7' 6", 8' 6" and 9' 6" widths
High-Density Polyethylene: 8' 6" and 9' 6" widths
See pages 4-7 for all universal snowplow features.



Photo shown with optional accessories

TAKE ON MORE.

Like all WESTERN® products, the MVP PLUS™ v-plow is built for efficiency, durability and performance—but it also gives you the added level of productivity that only a v-plow can achieve, letting you cut through deep banks and clear more snow in fewer passes.



T-FRAME DESIGN

T-frame provides added strength and allows blade-pitch adjustment to reduce uneven cutting edge wear.

STRUCTURAL REINFORCEMENT

Six vertical ribs on the 7' 6" models and eight on the 8' 6" and 9' 6" models, combined with the exclusive WESTERN POWER BAR, provide exceptional torsional strength and rigidity to eliminate blade twisting.

CENTER PIN AND HINGE

A 1"-diameter steel center pin resides within a two-connection-point hinge, keeping the wings tight for optimal performance.

ULTRALOCK DOUBLE-ACTING CYLINDERS

This standard feature locks the wings together to easily maneuver the plow as a straight blade. The double-acting cylinders also hold the wings firmly in place for clean back dragging.

STEEL CENTER-GAP COVER

For the cleanest pass in any position, the MVP PLUS™ v-plow has a snow control deflector over the center hinge to help prevent snow from being lost over the top.

TRIP-EDGE PROTECTION

Each blade features independent trip-edge protection in all configurations, whether in V, scoop or straight, to keep snow in front of the blade.

STANDARD CUTTING EDGE

A high-carbon steel cutting edge comes standard, reducing wear and extending the life of the blade.

HIGH-STRENGTH STEEL BASE CHANNEL

Provides extra support along the bottom of the plow blade.

AVAILABLE IN POLY AND STEEL

Available in ¼" high-density polyethylene or 14-gauge powder coated steel. The durable poly blade provides a slick surface for enhanced snow-rolling action and a maintenance-free surface. The steel blade features our high-quality ULTRAFINISH™ powder coated surface.

ACCESSORIES

Back Drag Edge* | Curb Guards | Plow Wings Shoe Kit | ½" Steel Cutting Edge | Blade Stops Rubber Snow Deflector

*Not compatible with shoe kits on v-plows



“



MOLDBOARD AVAILABILITY

Powder Coated Steel: 7' 6", 8' 6" and 9' 6" widths
High-Density Polyethylene: 7' 6", 8' 6" and 9' 6" widths
See pages 4-7 for all universal snowplow features.



THERE'S NO JOB TOO BIG FOR A TRUE PRO.

Make the most of the Class 4 to 6 trucks in your fleet with a plow that stands up to the demands of heavy-duty commercial and light municipal snowplowing. The WESTERN® PRO PLUS® HD snowplow lets you make short work of large parking lots and local streets. Forget business cards—distinguish yourself with the clean pavement you leave behind when using our heaviest-duty plow.

REINFORCED FOR CLASS 6 POWER

Eight vertical ribs provide structural reinforcement, ensuring proper alignment and reducing stress on the overall plow assembly.

HEAVY-DUTY 10' STRAIGHT BLADE

The 34"-tall, 11-gauge, powder coated steel moldboard is 10' wide and designed to stand up to the extra demands of heavy-duty commercial and light municipal snowplowing.

STANDARD CUTTING EDGE

Equipped with a high-carbon steel cutting edge to reduce wear and extend the life of the blade, the PRO PLUS® HD snowplow ensures a clean scrape on every pass.

TRIP BLADE PROTECTION

Six heavy-duty coil springs protect your plow and truck by allowing the whole blade to trip when striking obstacles. Dual shock absorbers reduce jarring and soften the blade return when tripping occurs, to extend the life of your truck and plow.

ACCESSORIES

Shoe Kits—Standard wear and Extreme wear
Rubber Snow Deflectors | Blade Stops
Carbide Cutting Edge | 5/8" Steel Cutting Edge



“



MOLDBOARD AVAILABILITY

Powder Coated Steel: 10' width
See pages 4-7 for all universal snowplow features.



PRO PLUS® HD

MAKE YOUR **MARK.**

Give winter all you've got with the WESTERN® PRO PLUS® snowplow. Designed to fit a wide range of vehicles, this rugged straight blade is the ultimate tool for the toughest commercial operations.



STRUCTURAL REINFORCEMENT

Eight vertical ribs, a heavy-duty quadrant and the exclusive WESTERN POWER BAR provide exceptional torsional strength and rigidity, to eliminate blade twisting even under the most brutal conditions.

HIGH-STRENGTH STEEL BASE CHANNEL

Provides extra support along the bottom of the plow blade.

HIGH-STRENGTH RECTANGULAR TUBE QUADRANT

Built to withstand season after season of commercial use.

A-FRAME CONSTRUCTION

The 3" square tubing provides strength and durability.

PIVOT BOLT

The 1"-diameter pivot bolt secures the plow in place, ensuring proper alignment and reducing stress on the overall plow assembly.

TRIP BLADE PROTECTION

Four heavy-duty coil springs protect your plow and truck by allowing the whole blade to trip when striking obstacles. Dual shock absorbers reduce jarring and soften the blade return when tripping occurs, to extend the life of your truck and plow.

STANDARD CUTTING EDGE

A high-carbon steel cutting edge comes standard, reducing wear and extending the life of the blade.

ACCESSORIES

Curb Guards | Plow Wings
Rubber Snow Deflectors | Back Drag Edge
Poly Snow Deflector | Carbide Cutting Edge*
5/8" Steel Cutting Edge*

*Fits the 9' model only



“



MOLDBOARD AVAILABILITY

Powder Coated Steel: 8', 8' 6" and 9' widths
See pages 4-7 for all universal snowplow features.



TAKE “PROFESSIONAL” TO THE NEXT LEVEL.

With customers counting on you, it's time to invest in a plow you can trust. There's a good reason the WESTERN® PRO-PLOW® Series 2 snowplow remains one of the best-selling straight blades in the business.

AVAILABLE IN POLY AND STEEL

The 29"-tall moldboard comes in both high-density polyethylene and powder coated steel. The durable 7' 6" and 8' poly blades provide a slick surface for enhanced snow-rolling action and a maintenance-free surface. The 7' 6", 8' and 8' 6" steel blades feature our high-quality ULTRAFINISH™ powder coat surface.

STRUCTURAL REINFORCEMENT

Seven vertical ribs provide structural reinforcement for exceptional torsional strength and rigidity to eliminate blade twisting.

HIGH-STRENGTH STEEL BASE CHANNEL

Provides extra support along the bottom of the plow blade.

PIVOT BOLT

The 1"-diameter pivot bolt secures the plow in place, ensuring proper alignment and reducing stress on the overall plow assembly.

STANDARD BLADE SHOES

Blade shoes help to extend cutting edge and base angle life when plowing rough surfaces.

TRIP BLADE PROTECTION

Four heavy-duty coil springs protect your plow and truck by allowing the whole blade to trip when striking obstacles. Dual shock absorbers reduce jarring and soften the blade return when tripping occurs, to extend the life of your truck and plow.

STANDARD CUTTING EDGE

A high-carbon steel cutting edge comes standard, reducing wear and extending the life of the blade.

RUBBER SNOW DEFLECTOR

The rubber snow deflector comes standard on poly moldboard models to help keep snow off of your windshield while plowing. It is available as an accessory for the powder coated steel models.

ACCESSORIES

Back Drag Edge | Curb Guards
Poly Snow Deflector | Rubber Snow Deflector
½" Steel Cutting Edge | Rubber Cutting Edge



“



MOLDBOARD AVAILABILITY

Powder Coated Steel: 7' 6", 8' and 8' 6" widths
High-Density Polyethylene: 7' 6" and 8' widths
See pages 4-7 for all universal snowplow features.



STRIKE THE RIGHT BALANCE.

Get pro performance without an ounce of wasted weight. The WESTERN® MIDWEIGHT™ snowplow features professional grade reinforcement to push the boundaries of “light commercial work.”

AVAILABLE IN POLY AND STEEL

The 27"-tall moldboard comes in both high-density polyethylene and powder coated steel. The durable 7' 6" poly blade provides a slick surface for enhanced snow-rolling action and a maintenance-free surface, while the 7' 6" steel blade features our high-quality ULTRAFINISH™ powder coat surface.

STRUCTURAL REINFORCEMENT

Six vertical ribs and the exclusive WESTERN POWER BAR provide unmatched structural reinforcement, delivering exceptional torsional strength and rigidity to eliminate blade twisting.

HIGH-STRENGTH STEEL BASE CHANNEL

Provides extra support along the bottom of the plow blade.

PIVOT BOLT

The 1"-diameter pivot bolt secures the plow in place, ensuring proper alignment and reducing stress on the overall plow assembly.

TRIP BLADE PROTECTION

The two-spring trip blade protects your snowplow and truck when striking hidden obstacles. Elastomeric bumpers reduce jarring and soften the blade return when tripping occurs, to extend the life of your truck and plow.

STANDARD CUTTING EDGE

A high-carbon steel cutting edge comes standard, reducing wear and extending the life of the blade.

ACCESSORIES

Back Drag Edge | Curb Guards | Shoe Kit
Poly Snow Deflector | Rubber Snow Deflector



“



MOLDBOARD AVAILABILITY

Powder Coated Steel: 7' 6" width
High-Density Polyethylene: 7' 6" width
See pages 4-7 for all universal snowplow features.

Photo shown with optional accessory



PUT YOUR **HALF-TON TO WORK.**

Perfect for contractors and homeowners, the WESTERN® HTS™ snowplow is a full-size, full-featured plow designed for lighter half-ton, four-wheel-drive trucks. Engineered for strength and weight, this plow is ideal for personal and light commercial applications such as driveways, small commercial lots and parking spaces.



STRUCTURAL REINFORCEMENT

Six vertical ribs and the exclusive WESTERN POWER BAR provide unmatched structural reinforcement, delivering exceptional torsional strength and rigidity to eliminate blade twisting.

HIGH-STRENGTH STEEL BASE CHANNEL

Provides extra support along the bottom of the plow blade.

PIVOT BOLT

The 1"-diameter pivot bolt secures the plow in place, ensuring proper alignment and reducing stress on the overall plow assembly.

SCRAPE LOCK

Hydraulically holds the blade down for more efficient scraping and clean back dragging.

TRIP BLADE PROTECTION

The two-spring trip blade protects your snowplow and truck when striking hidden obstacles. Elastomeric bumpers reduce jarring and soften the blade return when tripping occurs, to extend the life of your truck and plow.

ULTRAMOUNT® SNOWPLOW MOUNTING SYSTEM

Designed for fast and easy installation and removal using a simple mechanical system. It features a robust one-piece design and is 100% compatible with UltraMount® 2 system mounts and electrical platforms.

STANDARD CUTTING EDGE

A high-carbon steel cutting edge comes standard, reducing wear and extending the life of the blade.

ACCESSORIES

Back Drag Edge | Curb Guards
Shoe Kit | Rubber Snow Deflector
3/8" Steel Cutting Edge



“



MOLDBOARD AVAILABILITY

Powder Coated Steel: 7' 6" width
See pages 4-7 for all universal snowplow features.



CLEAR YOUR PROPERTY LIKE A PRO.

Defend your driveway from the deepest drifts with the WESTERN® DEFENDER™ compact snowplow. Ideal for midsized pickups and SUVs, this plow knows a thing or two about how to get things done—and done right.

HIGH-STRENGTH CONSTRUCTION

Built with high-strength, low-alloy steel that is stronger and lighter than conventional steel. Protected by the long-lasting ULTRAFINISH™ baked-on powder coat.

STRUCTURAL REINFORCEMENT

Six vertical ribs deliver exceptional torsional strength to eliminate blade twisting.

TRIP BLADE PROTECTION

The two-spring trip blade protects your snowplow and truck when striking hidden obstacles. Elastomeric bumpers reduce jarring and soften the blade return when tripping occurs, to extend the life of your truck and plow.

HIGH-STRENGTH STEEL BASE CHANNEL

Provides extra support along the bottom of the plow blade.

SCRAPE LOCK

Hydraulically holds the blade down for more efficient scraping and clean back dragging.

EASY ON / EASY OFF

Simple mechanical attaching system makes attaching and detaching your plow quick and easy.

GROUND CLEARANCE

When the plow is not in use, quickly maximize vehicle ground clearance with the removable receiver brackets. No tools required.

PIVOT BOLT

The 1"-diameter pivot bolt secures the plow in place, ensuring proper alignment and reducing stress on the overall plow assembly.

STANDARD CUTTING EDGE

A high-carbon steel cutting edge comes standard, reducing wear and extending the life of the blade.

ACCESSORIES

3/8" Steel Cutting Edge | Poly Cutting Edge
Rubber Snow Deflector | Curb Guards
Shoe Kit



“



MOLDBOARD AVAILABILITY

Powder Coated Steel: 6' 8" and 7' 2" widths
See pages 4-7 for all universal snowplow features.





WESTERNIZE YOUR UTV.

Winter knows no limits—which means you shouldn't either. Built exclusively for utility vehicles, WESTERN® IMPACT™ UTV snowplows are professional-grade plows built to go anywhere that demands WESTERN-grade performance. Constructed from high-strength, low alloy steel, both models feature an easy-on/easy-off UTV mounting system and removable receiver brackets for exceptional ground clearance. IMPACT UTV plows feature Scrape Lock for clean scraping and back dragging.

STRAIGHT BLADE

- 6'-wide, 14-gauge powder coated steel moldboard
- Four vertical ribs for strength and durability
- 5", high-carbon steel cutting edge provides increased wear resistance and a clean scrape
- Trip blade protection protects your plow and UTV by allowing the whole blade to trip when encountering hidden obstacles



ACCESSORIES

Rubber Snow Deflectors | Poly Cutting Edges
Shoe Kits | Light Bar Kit | Curb Guards (straight blade only)
Plow Wings (v-plow only) | Blade Stop Kit (v-plow only)

MOLDBOARD AVAILABILITY

Powder Coated Steel: 6' widths — straight and v-plow

V-PLOW BLADE

- 6'-wide, flared v-plow easily adapts to handle 5' sidewalks and gates in angle, scoop or V position
- Six vertical ribs and our proven T-frame design provide added strength and reinforcement
- UltraLock double-acting cylinders lock the wings together to maneuver the plow as a straight blade and hold wings firmly in place for clean back dragging
- 5", high-carbon steel cutting edge provides increased wear resistance and a clean scrape
- Each blade features independent trip-edge protection in all configurations, whether in V, scoop or straight, to keep snow in front of the blade



SKID-STEER

WHEN ONLY A SKID-STEER WILL DO.

The WESTERN® skid-steer snowplow lineup makes busting out parking lots quicker and easier than ever before. Choose the easy-to-use and ultra-efficient PRODIGY™ snowplow or the heavy-duty and always reliable PRO PLUS® snowplows, so your crew can get the job done quicker and move on to the next lot faster.

PRODIGY SKID-STEER PLOW

The PRODIGY snowplow features patented wing technology that automatically adjusts to the most efficient plowing configuration for the job. The automatic movement of the wings is ideal for skid-steers because it provides wing-plow performance on a skid-steer platform with no additional wiring or controls.

PRO PLUS SKID-STEER PLOW

The impressive strength of the PRO PLUS snowplow makes it the straight blade of choice for punishing skid-steer applications. The PRO PLUS plow comes in a variety of blade widths so you can find the perfect plow for the job.

ONBOARD HYDRAULICS

Skid-steer plows are quick to install and easy to operate. Leverage the skid-steer's onboard hydraulic system for powerful, efficient operation. Relief valves help protect the operator and the equipment when encountering hidden obstacles.

ATTACHMENT

The universal skid-steer mount provides a number of application options. With 6 degrees of total side-to-side oscillation, the blade can easily follow the contours of the pavement for a cleaner scrape.



PILE DRIVER™

PUSH PRODUCTIVITY **TO THE LIMIT.**

There's no way around it: Big lots demand big equipment. Whether you're using a skid-steer, backhoe or wheel loader, the WESTERN® PILE DRIVER™ pusher plows attach quickly and easily to let you clean up the biggest jobs in minimal time.

STRUCTURAL-STEEL CHANNEL

A structural-steel channel across the entire blade is internally-lined with stiffener ribs for structural integrity and bucket-impact strength.

SIDE-SUPPORT POSTS

Side-support posts provide protection against bending from curbs or other accidental impact.

QUICK-CHANGE ATTACHMENT SYSTEM

Fully formed gussets support both the upper and lower posts, which connect directly with the internal stiffener rib, for strength and support.

STANDARD CUTTING EDGE AND SHOES

The premium rubber cutting edge is adjustable and reversible to maximize use. Abrasion-resistant, steel wear shoes on the sideplates enhance the life of the cutting edge.



PILE DRIVER FOR SKID-STEERS

Available in 8' and 10' widths, the PILE DRIVER pusher plow for skid-steers moves up to 7 and 9 cubic yards of snow.



PILE DRIVER FOR BACKHOES

Available in 10' and 12' widths, the PILE DRIVER pusher plow for backhoes moves up to 9 and 11 cubic yards of snow.



PILE DRIVER FOR WHEEL LOADERS

Available in 12', 14' and 16' widths, the PILE DRIVER pusher plow for wheel loaders moves up to 15, 18 and 21 cubic yards of snow.

RB-400 ROTARY BROOM

SWEEP IT **CLEAN.**

Wrap up detailing jobs in one clean sweep. The WESTERN® RB-400 walk-behind rotary broom is a combination sweeper/snowplow that sweeps and scrapes the sidewalk clean along buildings, curbs and edging.

ADJUSTABLE SPEED AND DOWN PRESSURE

Adjustable broom-rotation speed and down pressure allow you to adapt to any condition.

FLOATING, PIVOTING BROOM HEAD

Floating, pivoting broom head gives you five angle settings to adjust the trajectory of the snow.

PLOW BLADE

Quick-attach plow blade features wheels and floating design to move heavy or deep snow.

SEVEN-POSITION HEIGHT ADJUSTMENT

Seven-position handlebar height adjustment for operator comfort.

ACTIVE-ASSIST STEERING

Active-assist steering and freewheel design allow for 360-degree turning.

BRUSH-HEAD DESIGN

Unique brush-head design features angled outer bristles to clean up close to buildings, curbs and edging.

ACCESSORIES


Debris Catcher | Multi-Purpose Bristles



PROTECT YOUR INVESTMENT WITH WESTERN® PARTS & ACCESSORIES



Ensure your WESTERN snow removal equipment remains efficient and reliable season after season with Factory Original parts and accessories from your local WESTERN dealer. Using “will-fit” alternatives can alter your plow’s performance and may affect your product warranty. Stick with the WESTERN brand for the parts and accessories you need. It’s the smart choice for protecting your investment.



CUTTING EDGES

Keep your blade at the top of its game by installing a genuine WESTERN cutting edge. A cutting edge will increase wear resistance and restore your worn base angle to the proper geometry. Steel, rubber, poly and carbide options available depending on plow model.



RUBBER SNOW DEFLECTORS – 10" AND 18"

Made from 2-ply-heavy-duty rubber, these easy-to-install rubber deflector kits will provide improved visibility by deflecting snow forward instead of on your windshield.



POLY SNOW DEFLECTOR

This heavy-duty poly snow deflector is curved to improve snow containment and Roll-Action™ handling.



PLOW WINGS

Expand the carrying capacity of your MVP 3™, MVP PLUS™, PRO PLUS® and IMPACT™ UTV v-plow by adding a pair of genuine WESTERN plow wings.

MVP 3 plow wings shown



CURB GUARDS

Made of cast metal, curb guards protect the outer edge of your snowplow from wear when plowing along sidewalks and curbs. Curb guards vary by plow model.



SHOE KITS

Shoe kits help your plow glide over gravel and dirt at the correct height and extend cutting edge and base angle life when plowing on rocky or abrasive surfaces. Kits vary by plow model.



BACK DRAG EDGE

Angled to maximize back dragging, the WESTERN back drag edge is constructed of 1/4" abrasion-resistant steel. Easy to install, a back drag edge ensures a clean scrape every time.



BLADE STOPS

Protect your plow by ensuring heavy loads are distributed evenly. Made of reinforced, 3/16", high-strength steel tube, blade stops reduce stress and wear on heavy-duty plow blades.



LIGHT BAR KIT

The IMPACT™ UTV light bar accessory features twin LED headlamps to help keep you on the right path. Like IMPACT UTV snowplows, the light bar accessory is sturdy and engineered to stand up to the rigors of commercial plowing operations.



WESTERN® BLADE GUIDES WITH FLAGS

These attractive blade guides with replaceable flags help improve operator visibility and plow blade positioning.



COMMERCIAL BLADE GUIDES

Commercial blade guides are highly visible bright red, enhanced with reflective tape and available in 24" or 36" lengths.



SHOCK ABSORBER

Helps soften trip-blade return. Available for the PRODIGY™, WIDE-OUT™ and WIDE-OUT™ XL snowplows.



CONVERSION KIT

This easy-to-use UltraMount® to UniMount conversion kit enables you to attach a UniMount plow to a vehicle equipped with an UltraMount system vehicle mount. This kit is perfect if you have multiple snowplows.



FLEX ARM™ QUICK-RELEASE FLEXIBLE CONTROL MOUNT

Quick-release, flexible control mount adjusts into any position. Magnetic base for easy removal with no mounting holes in your dash.



PRO-GRIP MOUNT

Kit contains adhesive-backed locking strips to secure the WESTERN Solenoid Control and spreader controls to interior vehicle surfaces. Allows the control to be easily removed yet held firmly in place.



SNOWPLOW EMERGENCY PARTS KIT

Be prepared! Packed in an easy-to-store WESTERN Factory Original nylon duffel bag, these parts kits provide the high-volume, Factory Original parts needed for emergency snowplow repairs.



HIGH-PERFORMANCE HYDRAULIC FLUID

Available in quart and gallon containers, WESTERN high-performance hydraulic fluid is formulated to provide better viscosity in all temperatures. This means your plow will operate at the optimum level no matter what the weather conditions.



WESTERN FACTORY ORIGINAL PAINT

Time to touch up your WESTERN snowplow blade or black iron? Available in spray or quart cans, in red or black, topcoat or the primer-based undercoat, these Factory Original paints provide durable coverage and are formulated to match your original equipment.



MULTI-PURPOSE BRISTLES

The multi-purpose bristle kit replaces the snow brushes on the RB-400 rotary broom during the off-season. This allows you to use the machine for sweeping debris on a wide variety of surfaces and applications.



DEBRIS COLLECTOR

The debris collector gives you full use of your RB-400 rotary broom year round. It easily attaches to the front of the machine, so you can sweep up waste and debris quickly, keep it contained and dispose of it properly.

SPECIFICATIONS

WIDE-OUT™*

WIDE-OUT™ XL

PRODIGY™

PLOW TYPE	WINGED	WINGED	WINGED
MOLDBOARD OPTIONS	Steel	Steel	Steel
BLADE WIDTH	Retracted: 8' (2.44 m) Expanded: 10' (3.05 m) Scoop: 8' 10" (2.69 m)	Retracted: 8' 6" (2.59 m) Expanded: 11' (3.35 m) Scoop: 9' 10" (3.00 m)	Scoop: 8' 7" (2.62 m) Wings Pinned: 9' 8" (2.95 m)
BLADE HEIGHT	At Center: 31" (78.74 cm) On End: 35" (88.90 cm)	At Center: 31" (78.74 cm) On End: 36" (91.44 cm)	29 ½" (74.93 cm)
BLADE THICKNESS	14 ga (2.11 mm)	14 ga (2.11 mm)	12 ga (2.78 mm)
SHOCK ABSORBERS	Optional	Optional	Optional
TRIP SPRINGS	4	4	4
RIBS	6	8	8
LIFT CYLINDER	1 ¾" x 8" (4.45 cm x 20.32 cm)	1 ¾" x 8" (4.45 cm x 20.32 cm)	1 ½" x 8" (3.81 cm x 20.32 cm)
ANGLING RAMS	1 ½" x 10" (3.81 cm x 25.40 cm)	1 ½" x 10" (3.81 cm x 25.40 cm)	1 ½" x 10" (3.81 cm x 25.40 cm)
PLOWING WIDTH (FULL ANGLE)	Retracted: 7' 2" (2.18 m) Expanded: 9' (2.74 m) Scoop: 7' 11" (2.41 m)	Retracted: 7' 11" (2.41 m) Expanded: 10' 6" (3.20 m) Scoop: 9' 6" (2.90 m)	Full Angle: 7' 10" (2.39 m) Scoop: 8' 7" (2.61 m)
APPROX. WEIGHT* (LESS MOUNT)	1020 lb (462.66 kg)	1090 lb (494.42 kg)	880 lb (399 kg)
CUTTING EDGE	½" x 6" (1.27 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)
MOUNT TYPE	UltraMount® 2	UltraMount® 2	UltraMount® 2

*All product features and specifications listed in this brochure apply to WIDE-OUT snowplows with serial numbers beginning with 180210 and higher

MVP 3™

PLOW TYPE	V-PLOW	V-PLOW	V-PLOW
MOLDBOARD OPTIONS	Steel/Stainless	Steel/Stainless/Poly	Steel/Stainless/Poly
BLADE WIDTH	7' 6" (2.29 m)	8' 6" (2.59 m)	9' 6" (2.90 m)
BLADE HEIGHT	At Center: 31" (78.74 cm) On End: 37" (93.98 cm)	At Center: 31" (78.74 cm) On End: 38" (96.52 cm)	At Center: 31" (78.74 cm) On End: 39" (99.06 cm)
BLADE THICKNESS	14 ga (1.98 mm)	14 ga (1.98 mm) Poly: ¼" (6.40 mm)	14 ga (1.98 mm) Poly: ¼" (6.40 mm)
SHOCK ABSORBERS	—	—	—
TRIP SPRINGS	4	4	6
RIBS	6	8	8
LIFT CYLINDER	1 ¾" x 8" (4.45 cm x 20.32 cm)	1 ¾" x 8" (4.45 cm x 20.32 cm)	1 ¾" x 8" (4.45 cm x 20.32 cm)
ANGLING RAMS	1 ¾" x 11" (4.45 cm x 27.94 cm)	1 ¾" x 11" (4.45 cm x 27.94 cm)	1 ¾" x 11" (4.45 cm x 27.94 cm)
PLOWING WIDTH (FULL ANGLE)	Full Angle: 6' 7" (2.01 m) Scoop: 6' 4" (1.93 m) Full V: 6' 10" (2.08 m)	Full Angle: 7' 5" (2.26 m) Scoop: 7' 2" (2.18 m) Full V: 7' 8" (2.34 m)	Full Angle: 8' 6" (2.59 m) Scoop: 8' 2" (2.49 m) Full V: 8' 7" (2.62 m)
APPROX. WEIGHT* (LESS MOUNT)	885 lb (401 kg)	940 lb (426 kg) Poly: 890 lb (403 kg)	1022 lb (463 kg) Poly: 972 lb (440 kg)
CUTTING EDGE	⅜" x 6" (0.95 cm x 15.24 cm)	⅜" x 6" (0.95 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)
MOUNT TYPE	UltraMount® 2	UltraMount® 2	UltraMount® 2

MVP PLUS™

PLOW TYPE	V-PLOW	V-PLOW	V-PLOW
MOLDBOARD OPTIONS	Steel/Poly	Steel/Poly	Steel/Poly
BLADE WIDTH	7' 6" (2.29 m)	8' 6" (2.59 m)	9' 6" (2.90 m)
BLADE HEIGHT	29" (73.66 cm)	29" (73.66 cm)	31" (78.74 cm)
BLADE THICKNESS	Steel: 14 ga (1.98 mm) Poly: ¼" (6.40 mm)	Steel: 14 ga (1.98 mm) Poly: ¼" (6.40 mm)	Steel: 14 ga (1.98 mm) Poly: ¼" (6.40 mm)
SHOCK ABSORBERS	—	—	—
TRIP SPRINGS	4	4	6
RIBS	6	8	8
LIFT CYLINDER	1 ½" x 8" (3.81 cm x 20.32 cm)	1 ½" x 8" (3.81 cm x 20.32 cm)	1 ½" x 8" (3.81 cm x 20.32 cm)
ANGLING RAMS	1 ¾" x 11" (4.45 cm x 27.94 cm)	1 ¾" x 11" (4.45 cm x 27.94 cm)	1 ¾" x 11" (4.45 cm x 27.94 cm)
PLOWING WIDTH (FULL ANGLE)	Full Angle: 6' 6" (1.98 m) Scoop: 6' 3" (1.91 m) Full V: 6' 9" (2.06 m)	Full Angle: 7' 5" (2.26 m) Scoop: 7' 1" (2.16 m) Full V: 7' 7" (2.31 m)	Full Angle: 8' 3" (2.51 m) Scoop: 7' 11" (2.41 m) Full V: 8' 7" (2.62 m)
APPROX. WEIGHT* (LESS MOUNT)	Steel: 827 lb (375 kg) Poly: 799 lb (362 kg)	Steel: 880 lb (399 kg) Poly: 847 lb (384 kg)	Steel: 988 lb (448 kg) Poly: 964 lb (437kg)
CUTTING EDGE	⅜" x 6" (0.95 cm x 15.24 cm)	⅜" x 6" (0.95 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)
MOUNT TYPE	UltraMount® 2	UltraMount® 2	UltraMount® 2

PRO PLUS® HD PRO PLUS®

PLOW TYPE	STRAIGHT	STRAIGHT	STRAIGHT	STRAIGHT
MOLDBOARD OPTIONS	Steel	Steel	Steel	Steel
BLADE WIDTH	10' (3.05 m)	8' (2.44 m)	8' 6" (2.59 m)	9' (2.74 m)
BLADE HEIGHT	34" (86.36 cm)	31 ½" (80.01 cm)	31 ½" (80.01 cm)	31 ½" (80.01*cm)
BLADE THICKNESS	11 ga (3.05 mm)	12 ga (2.78 mm)	12 ga (2.78 mm)	12 ga (2.78 mm)
SHOCK ABSORBERS	2	2	2	2
TRIP SPRINGS	6	4	4	4
RIBS	8	8	8	8
LIFT CYLINDER	1 ¾" x 8" (4.45 cm x 20.32 cm)	1 ½" x 8" (3.81 cm x 20.32 cm)	1 ½" x 8" (3.81 cm x 20.32 cm)	1 ½" x 8" (3.81 cm x 20.32 cm)
ANGLING RAMS	2" x 12 ½" (5.08 cm x 31.75 cm)	1 ½" x 12" (3.81 cm x 30.48 cm)	1 ½" x 12" (3.81 cm x 30.48 cm)	1 ½" x 12" (3.81 cm x 30.48 cm)
PLOWING WIDTH (FULL ANGLE)	8' 9" (2.67 m)	6' 11" (2.11 m)	7' 4" (2.24 m)	7' 9" (2.36 m)
APPROX. WEIGHT* (LESS MOUNT)	1075 lb (487.61 kg)	805 lb (365 kg)	821 lb (372 kg)	837 lb (379 kg)
CUTTING EDGE	½" x 6" (1.27 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)
MOUNT TYPE	UltraMount® 2	UltraMount® 2	UltraMount® 2	UltraMount® 2

*UltraMount® 2 mount weight range: 28 to 145 lb.

SPECIFICATIONS CONT.

PRO-PLOW® SERIES 2

PLOW TYPE	STRAIGHT	STRAIGHT	STRAIGHT
MOLDBOARD OPTIONS	Steel/Poly	Steel/Poly	Steel
BLADE WIDTH	7' 6" (2.29 m)	8' (2.44 m)	8' 6" (2.59 m)
BLADE HEIGHT	29" (73.66 cm)	29" (73.66 cm)	29" (73.66 cm)
BLADE THICKNESS	Steel: 11 ga (3.18 mm) Poly: 3⁄8" (9.52 mm)	Steel: 11 ga (3.18 mm) Poly: 3⁄8" (9.52 mm)	11 ga (3.18 mm)
SHOCK ABSORBERS	1	1	1
TRIP SPRINGS	4	4	4
RIBS	7	7	7
LIFT CYLINDER	1 ½" x 8" (3.81 cm x 20.32 cm)	1 ½" x 8" (3.81 cm x 20.32 cm)	1 ½" x 8" (3.81 cm x 20.32 cm)
ANGLING RAMS	1 ½" x 10" (3.81 cm x 25.40 cm)	1 ½" x 10" (3.81 cm x 25.40 cm)	1 ½" x 10" (3.81 cm x 25.40 cm)
PLOWING WIDTH (FULL ANGLE)	6' 6" (1.98 m)	6' 11" (2.11 m)	7' 4" (2.24 m)
APPROX. WEIGHT* (LESS MOUNT)	Steel: 653 lb (296 kg) Poly: 677 lb (307 kg)	Steel: 668 lb (302 kg) Poly: 690 lb (312 kg)	686 lb (311 kg)
CUTTING EDGE	3⁄8" x 6" (0.95 cm x 15.24 cm)	3⁄8" x 6" (0.95 cm x 15.24 cm)	3⁄8" x 6" (0.95 cm x 15.24 cm)
MOUNT TYPE	UltraMount® 2	UltraMount® 2	UltraMount® 2



MIDWEIGHT™

HTS™

PLOW TYPE	STRAIGHT	STRAIGHT
MOLDBOARD OPTIONS	Steel/Poly	Steel
BLADE WIDTH	7' 6" (2.29 m)	7' 6" (2.29 m)
BLADE HEIGHT	27" (68.58 cm)	27" (68.58 cm)
BLADE THICKNESS	Steel: 14 ga (1.98 mm) Poly: ¼" (6.40 mm)	14 ga (1.98 mm)
TRIP SPRINGS	2	2
RIBS	6	6
LIFT CYLINDER	1 ½" x 8" (3.81 cm x 20.32 cm)	2" x 6 ¾" (5.08 cm x 17.15 cm)
ANGLING RAMS	1 ½" x 10" (3.81 cm x 25.40 cm)	1 ½" x 8" (3.81 cm x 20.32 cm)
PLOWING WIDTH (FULL ANGLE)	6' 6" (1.98 m)	6' 7" (2.01 m)
APPROX. WEIGHT* (LESS MOUNT)	Steel: 540 lb (244 kg) Poly: 532 lb (241 kg)	412 lb (186 kg)
CUTTING EDGE	3⁄8" x 6" (0.95 cm x 15.24 cm)	5⁄16" x 6" (0.80 cm x 15.24 cm)
MOUNT TYPE	UltraMount® 2	UltraMount®



*UltraMount® 2 mount weight range: 28 to 145 lb.

DEFENDER™

PLOW TYPE	STRAIGHT	STRAIGHT
MOLDBOARD OPTIONS	Steel	Steel
BLADE WIDTH	6' 8" (2.00 m)	7' 2" (2.10 m)
BLADE HEIGHT	23 ½" (59.70 cm)	23 ½" (59.70 cm)
BLADE THICKNESS	16 ga (1.50 mm)	16 ga (1.50 mm)
SHOCK ABSORBERS	—	—
TRIP SPRINGS	2	2
RIBS	6	6
PLOWING WIDTH (FULL ANGLE)	5' 11" (1.80 m)	6' 4½" (1.90 m)
APPROX. WEIGHT (LESS MOUNT)	290 lb (132 kg)	297 lb (135 kg)
CUTTING EDGE	¼" x 5" (0.60 cm x 12.70 cm)	¼" x 5" (0.60 cm x 12.70 cm)



IMPACT™

PLOW TYPE	UTV – V-PLOW	UTV – STRAIGHT
MOLDBOARD OPTIONS	Steel	Steel
BLADE WIDTH	6' (1.83 m)	6' (1.83 m)
BLADE HEIGHT	At Center: 25 ¾" (65.40 cm) On End: 29 ¼" (74.29 cm)	23 ½" (59.70 cm)
BLADE THICKNESS	14 ga (1.90 mm)	14 ga (1.90 mm)
SHOCK ABSORBERS	—	—
TRIP SPRINGS	2	2
RIBS	6	4
LIFT CYLINDER	1 ½" x 6" (3.81 cm x 15.24 cm)	1 ½" x 6" (3.81 cm x 15.24 cm)
ANGLING RAMS	1" x 8 ¾" (2.54 cm x 22.23 cm)	1" x 7" (2.5 cm x 18 cm)
PLOWING WIDTH*** (FULL ANGLE)	Full Angle: 5' (1.52 m) Scoop: 4' 7" (1.39 m) Full V: 5' (1.52 m)	5' 4" (1.60 m)
APPROX. WEIGHT	354 lb (160 kg)**	261 lb (119 kg)**
CUTTING EDGE	¼" x 5" (0.64 cm x 12.70 cm)	¼" x 5" (0.64 cm x 12.70 cm)
MOUNT TYPE	UTV Mounting System	UTV Mounting System



**Plus vehicle mount
*** IMPACT UTV V-Plow: For UTVs with a wider wheelbase, width can be adjusted to:
5' 6" (1.68 m) full angle, 5' 1" (1.55 m) scoop, 5' 6" (1.68 m) full V

SPECIFICATIONS CONT.



PRODIGY™		PRO PLUS®		
PLOW TYPE	SKID-STEER	SKID-STEER	SKID-STEER	SKID-STEER
MOLDBOARD OPTIONS	Steel	Steel	Steel	Steel
BLADE WIDTH	Scoop: 8' 7" (2.62 m) Wings Pinned: 9' 8" (2.95 m)	8' (2.44 m)	8' 6" (2.59 m)	9' (2.74 m)
BLADE HEIGHT	29 ½" (74.93 cm)	31 ½" (80.01 cm)	31 ½" (80.01 cm)	31 ½" (80.01 cm)
BLADE THICKNESS	12 ga (2.78 mm)	12 ga (2.78 mm)	12 ga (2.78 mm)	12 ga (2.78 mm)
SHOCK ABSORBERS	Optional	2	2	2
TRIP SPRINGS	4	4	4	4
RIBS	8	8	8	8
ANGLING RAMS	1 ½" x 10" (3.81 cm x 25.40 cm)	1 ½" x 12" (3.81 cm x 30.48 cm)	1 ½" x 12" (3.81 cm x 30.48 cm)	1 ½" x 12" (3.81 cm x 30.48 cm)
PLOWING WIDTH (FULL ANGLE)	7' 10" (2.39 m)	6' 11" (2.11 m)	7' 4" (2.24 m)	7' 9" (2.36 m)
CUTTING EDGE	½" x 6" (1.27 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)
MOUNT TYPE	Universal Skid-Steer Mount	Universal Skid-Steer Mount	Universal Skid-Steer Mount	Universal Skid-Steer Mount



PILE DRIVER™							
PLOW TYPE	SKID-STEER	SKID-STEER	BACKHOE	BACKHOE	WHEEL LOADER	WHEEL LOADER	WHEEL LOADER
MOLDBOARD OPTIONS	Steel	Steel	Steel	Steel	Steel	Steel	Steel
BLADE WIDTH	8' (2.44 m)	10' (3.05 m)	10' (3.05 m)	12' (3.66 m)	12' (3.66 m)	14' (4.27 m)	16' (4.88 m)
APPROX. WEIGHT	710 lb (322 kg)	790 lb (358 kg)	1030 lb (467 kg)	1150 lb (521 kg)	1680 lb (762 kg)	1815 lb (823 kg)	1950 lb (884 kg)
SIDEPLATE	36" x 36" (0.91 m x 0.91 m)	36" x 36" (0.91 m x 0.91 m)	36" x 36" (0.91 m x 0.91 m)	36" x 36" (0.91 m x 0.91 m)	48" x 48" (1.21 m x 1.21 m)	48" x 48" (1.21 m x 1.21 m)	48" x 48" (1.21 m x 1.21 m)
MACHINE APPLICATION	46-70 hp	70+ hp	2WD	4WD	1.5 yd (1.37 m)	2 yd (1.82 m)	3 yd (2.74 m)
SNOW CAPACITY	7 cu yd (6.40 cu m)	9 cu yd (8.23 cu m)	9 cu yd (8.23 cu m)	11 cu yd (10.06 cu m)	15 cu yd (13.72 cu m)	18 cu yd (16.46 cu m)	21 cu yd (19.20 cu m)
MOUNT TYPE	Quick Change Attachment System	Quick Change Attachment System	Quick Change Attachment System	Quick Change Attachment System	Quick Change Attachment System	Quick Change Attachment System	Quick Change Attachment System

Specifications subject to change without prior notice. Please visit westernplows.com for the most current specifications.

RB-400

PLOW TYPE	WALK-BEHIND ROTARY BROOM
EMPTY WEIGHT	238 lb (108 kg)
OVERALL DIMENSIONS (L x W x H)	Without Blade: 72" x 40" x 42 ½" (183.00 cm x 102.00 cm x 108.00 cm) With Blade: 80" x 40" x 42 ½" (203.00 cm x 102.00 cm x 108.00 cm)
SPEED	Up to 2.7 mph (4.40 km/h)
FORWARD GEARS	3
REVERSE GEARS	1
BRUSH PRESSURE ADJUSTMENT	Yes
ADJUSTABLE HANDLE HEIGHT	7 Position
ENGINE	Honda® GXV 160 OHV
TIRES	Polar Trec Snow Tires
SNOW BLADE WIDTH	Wide: 40" (102.00 cm) Angled: 37" (94.00 cm)
BRUSH DIAMETER	16" (40.60 cm)
BRUSH WIDTH	40" (102.00 cm)
FUEL CAPACITY	0.5 gal (1.9 L)



“

GIVE EVERY JOB THE FINISHING TOUCH

Ice? Sleet? Make sure you've got it all covered with WESTERN® ice control products, built to keep salt, sand and brine delivery consistent, efficient, and completely under your control.

To view our full-line of WESTERN spreaders, check out our 2018 Spreader Brochure or visit westernplows.com.





Western Products | P.O. Box 245038 | Milwaukee, WI 53224-9538

westernplows.com



Western Products reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Western Products or the vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle ratings with a snowplow. This product is manufactured under the following US patents: 6,145,222; 6,209,231; 6,408,549; 6,412,199; 6,526,677; 6,711,837; 6,928,757; 7,134,227; 7,400,058; 7,430,821; 7,737,576; CAN patents 2,354,257; 2,358,145; 2,358,354; 2,639,052; and other patents pending. Western Products offers a limited warranty for all snowplows and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: CONTRACTOR GRADE®, DEFENDER™, HTS™, IMPACT™, MIDWEIGHT™, MVP 3™, MVP PLUS™, NIGHTHAWK™, PILE DRIVER™, POLY PRO-PLOW® Series 2, PRO-FLO™ 900, PRO-PLOW® Series 2, PRO PLUS®, PRO PLUS® HD, PRODIGY™, Roll-Action™, SECURITY GUARD™, Striker™, Tornado™, Tornado™ UTV, ULTRAFINISH™, UltraMount®, UltraMount® 2, WESTERN®, WIDE-OUT™ and WIDE-OUT™ XL.

©2018 Douglas Dynamics, LLC
All rights reserved.

 A DIVISION OF DOUGLAS DYNAMICS, LLC

Printed in U.S.A.
Form No. 77011 – AU18