SUPER 104

104" WIDTH OF CUT MAKES BIG JOBS EASY



WIUE-AREA MOWER WITH Zero-Turn Maneuverab<u>ility</u>

Hustler's Super 104 can easily handle acres of work. Offering a 104" width of cut, zero-turn precision and up to an impressive 11 mph speed, this machine is in a class by itself. Its industrial-grade HyperDrive® Hydro System is engineered to handle thousands of hours of the toughest jobs out there. Transporting is easy as it folds into an 80" transport width. A Grammar suspension seat, welded steel deck and 12 gallon fuel capacity provide comfort, durability and more performance than your average zero-turn mower.



HYPERDRIVE® HYDRO SYSTEM

Features industrial-grade pumps and motors to handle tough jobs and long days in stride.



104" WIDTH OF CUT

Widest and most productive commercial zero-turn available



80" TRANSPORT WIDTH

Fits most trailers making it easy to transport from job-to-job.

LIFETIME WARRANTY
ON THE FRAME











ENGINE

Manufacturer Vanguard

HP 36HP* - Vanguard BIG BLOCK™

37HP* - Vanguard BIG BLOCK™ EFI

* Per SAE J1995

Displacement 993 cc
Cooling Air cooled

Air Cleaner Heavy duty canister
Engine Warranty 5 year (Vanguard only)

DRIVE SYSTEM

Type Dual hydrostatic
Pumps Danfoss DDC20
Wheel Motors Parker TG0360

Hydraulic Lines Stainless steel Parker seal loc technology

Reservoir Capacity 3 gallons

Speed Up to 11 mph

Parking Brakes Patented automatic

DECKS

Cutting Width Rear discharge: 104"

Cutting Heights 1"- 5.5"

Deck Lift Hydraulic powered

Depth 5.5" Blades 5

Blade Length 1 - 23.86" x 2.50" x .20" CW 1 - 23.86" x 2.50" x .20" CCW

1 - 20.50" x 2.50" x .20" CCW 2 - 20.50" x 2.50" x .20" CW

Spindles Ductile cast iron with steel shafts and

sealed ball bearings

Deck Belts 1 per deck

Drive Electric PTO clutch

Construction 11 ga. welded steel

Spindle Mounts Reinforced 7 ga. doubler

Impact/Trim Areas 1.5" x .375" steel bar protector

CONSTRUCTION

Frame 1.5" x 3.0" x .188" steel

Front Caster Wheels Mounted tapered greasable bearings

Front Caster Forks Fabricated 1/2" steel

GENERAL

Seat Grammer suspension seat, isolator platform

Fuel Capacity 12 gallons
Cup Holder Yes

Front Tire 15 x 6.0 - 6
Drive Tire 26 x 12 - 12

DIMENSIONS

Weight 2500 lbs
Height w/rops up 71.5"
Height w/rops Folded 54"
Length 95.5"

Width 106.1" wings down

80.0" wings up at gauge wheels 72.5" wings up at deck base

Tire Width 60.3"

PRODUCTIVITY'

Acres Per Hour 9.24

OPTIONAL ACCESSORIES

Mulch kit

Steering lever extension kit

Light kit Anti-scalp kit Flasher kit Beacon kit Flex Forks® Hitch kit

SUPER 104 | AT A GLANCE

- Widest and most productive commercial zero-turn available
- Heavy-duty fabricated frame unmatched durability
- Exclusive SmoothTrak™ steering responsive, precise control
- Patented automatic park brake
- Wide area mower with 80" transport width fits most trailers
- Up to 11 mph speed
- 12 gallon fuel capacity
- · Hydraulic powered deck height adjustment
- Grammer suspension seat with isolator platform
- HyperDrive® industrial hydro system mow in tough conditions without losing performance

^{*} Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.