X-ONE®

BUILT FOR ALL DAY, EVERYDAY PERFORMANCE



VERSATILITY AND COMFORT

The X-ONE® is built for the full-time commercial landscaper to provide all day, everyday performance. It offers a choice of carbureted or fuel-injected engines, and a selection of side or rear-discharge decks. And, with an 11.7 gallon gas tank, and speeds of over 10 miles per hour, you can cover a lot of ground in less time. The X-ONE sets the standard for commercial zero-turn value.



INCREDIBLE POWER

Driven by Parker unitized transmissions and choice of engine sizes.



COMMERCIAL FRAME

Full size commercial frame for all day commercial use.



EXTRA HIGH-BACK SEAT

Full mechanical suspension and additional bolstering to reduce pressure on spine and improve lumbar support.



LIFETIME WARRANTY









ENGINE

Manufacturer Kawasaki FX730, FX850

Kohler Command Pro CV742, 824 EFI

HP 54"RD, 60"RD deck: 23.5HP* - FX730

52", 60", 72" deck: 25HP* - CV742 52", 60", 72" deck: 27HP* - FX850 52", 60", 72" deck: 29HP* - 824 EFI

* Per SAE J1995

Displacement FX730: 726cc FX850: 852cc

Kohler 824: 824cc

Cooling Air cooled

Air Cleaner Heavy duty canister

Engine Warranty 3 year

DRIVE SYSTEM

Type Dual hydrostatic

Transmissions Parker unitized 12cc/rev pump &

15.9ci/rev wheel motors

Hydraulic Cooling Transmission mounted fans

Speed Up to 10.5 mph
Parking Brakes Patented automatic

DECKS

Cutting Width Side discharge: 52", 60", 72"

Rear discharge: 54", 60"

Cutting Heights 1"- 5.5"

Deck Lift Foot operated

Depth 5.5" Blades 3

Blade Length 52" deck: 3 - 17.86" x 2.5" x .20"

54" RD deck: 3 - 18.5" x 2.5" x .20" 60", 60" RD deck: 3 - 20.5" x 2.5" x .20"

72" deck: 3 - 23.86" x 3" x .20"

Spindles Ductile cast iron with steel shafts and

sealed ball bearings

Deck Belts

Drive Electric PTO clutch

Construction 10 ga. Fab. with 7 ga. wrappers Spindle Mounts 52", 60", 72": 10 ga. with 7 ga.

doubler, steel

54" RD, 60" RD: 10 ga. + large 11 ga. doubler,

steel

Impact/Trim Areas 11 ga. formed channel with rolled edge

 * Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

CONSTRUCTION

Frame 1.5" x 3.0" x .188" steel tubing

Front Caster Wheels Mounted with tapered wheel bearings and

debris cap

Front Caster Forks Fabricated 1/2" steel

GENERAL

Seat Extra high-back suspension seat

Fuel Capacity 11.7 gallons

Cup Holder Yes

Front Tire 13 x 6.5 - 6

Drive Tire 52", 54" RD deck: 24 x 9.5 - 12

60", 60" RD, 72" deck: 24 x 12 - 12

DIMENSIONS

Weight 52": 1240 lbs 60": 1245 lbs 60" RD: 1305 lbs

54" RD: 1275 lbs 72": 1320 lbs

Height w/rops up 72.5" Height w/rops Folded 49"

Length 52", 60" deck: 80.2"

54" RD deck, 60" RD deck: 80.2" 72" deck: 84"

Width 52" deck: 54.4"

54" RD deck: 55.72" 60" deck: 62.4" 60" RD deck: 61.72" 72" deck: 75.7"

Tire Width 52", 54" RD deck: 51"

60", 60" RD, 72" deck: 54.5"

PRODUCTIVITY*

Acres Per Hour 52": 5.52 54"RD: 5.73

60": 6.36 60"RD: 6.36

72": 7.64

OPTIONAL ACCESSORIES

Semi pneumatic front tires Steering lever extension kit Deck rear anti-scalp wheels 3-bag grass catcher (12 bushels

3-bag grass catcher (12 bushels) Mesh side bagger (3 bushels)

Mesh side bagger (3 bushels) Metal side bagger (3.5 bushels) FlexForks® Mulch kit Light kit Stripe kit Electric deck lift BacVac bagger

X-ONE | AT A GLANCE

- 52", 60" or 72" commercial-style, side-discharge deck
- 54" or 60" rear-discharge deck
- Heavy-duty fabricated frame unmatched durability
- Exclusive SmoothTrak™ steering responsive, precise control
- · Patented automatic park brake
- · High horsepower and varied engine options
- 13" front and 24" drive tires
- · Top pinning height adjustment
- Molded rubber bumper along engine guard