

2019 PRODUCT CATALOG



BOBCATTURF.COM



# ***FIERCELY INDEPENDENT.***

**I don't need someone pointing out the tough spots for me. I know them like the back of my hand. All I need is equipment that works how, when and where I need it to. Not bells and whistles. Just a rugged, reliable machine backed by a warranty I can depend on. Any mower I buy has got to work on my terms because this is my turf. And there's only one way I work: Fiercely Independent.**

## **BUILT LIKE A TANK. NIMBLE LIKE A CAT.**

Combining heavy-gauge steel with sturdy American craftsmanship means BOB-CAT® mowers can take abuse that would send other machines into early retirement. It's just the only way to build a machine that works as hard as you do. And with dual-tube frame construction on our newest, next-generation machines, there's simply no match for BOB-CAT's durability.

## **CUTS LIKE A STRAIGHT RAZOR**

Make them say "Whoa!" when they look at your handiwork. Our decks feature steel blades that slice—rather than chop—giving you vacuum lift, a cleaner cut and more even clipping dispersal for your trademark finish. You're the boss—and when you've got a BOB-CAT®, it's not your job to worry about the details. When it comes to quality of cut, we've got you covered.





## WORKS FOR YOU

BOB-CAT® machines are built for one reason: to cut grass. Simple controls let you show turf who's boss as soon as that BOB-CAT® is yours. Our new rotating bumper and hitch system\* makes maintenance and service quick and easy, because you don't profit from downtime. And we'll always put our money where our mouth is—as proven by our industry-leading MOW WITH CONFIDENCE™ limited warranties.

\* Swing-away bumper and hitch system only on select models, see product spreads for details.



**FIERCELY INDEPENDENT.**



# VICIOUSLY EFFECTIVE MOWING

## ENGINEERED TO KEEP YOU UNSTOPPABLE

No matter which mower you choose, **BOB-CAT®** cutting systems are engineered to provide unstoppable cutting power. Every detail of our decks is precision-designed to knock grass into next week. Whether it's accelerating airflow through our patented baffle systems, busting up clumps of grass in the cutting chamber or shooting clippings out in an even pattern, **BOB-CAT®** understands what it takes to get a high-quality cut. In fact, our high-vacuum decks eliminate negative-pressure pockets, lifting the grass up for a pristine cut. Available in widths up to 72 inches, these heavy-gauge steel powerhouses work every bit as hard as you do.

### SUPERIOR DISCHARGE WITH DURADECK™

The DuraDeck™: Tough enough to handle everything commercial jobs dish out:

- Double-Wave™ or patent pending **Air-Gap** bolt-on baffles to increase airflow throughout the deck (varies by model).
- Even clipping dispersal.
- Adjustable front lip optimizes cutting for varying conditions and grass types.
- Limited lifetime deck, deck cradle and engine deck warranty.

### RUGGED DURABILITY WITH TUFDECK™ PRO AND TUFDECK™

The TufDeck™ Pro and TufDeck™: Tough and reliable for a perfectly manicured finish—every time:

- Cast-aluminum spindles for reliability.
- Constructed with heavy-gauge, fabricated steel.
- Improved vacuum lift.
- Easily replaceable, bolt-on front baffles.
- Adjustable front lip optimizes cutting for varying conditions and grass types.

## OPTIMUM MOWING WITH BULLNOSE AIRFX™ CUTTING SYSTEMS

The AirFX™: A full-scale system designed to keep you a cut above the rest:

- Deeper profile for improved vacuum lift.
- Newly engineered, bolt-on, replaceable, patent pending **Air-Gap** baffles for more efficient airflow and enhanced serviceability.
- Bullnose design that stands the grass up before it reaches the mower blades.
- Cast-iron spindles for increased durability.
- Even clipping dispersal.
- Improved deck cleanliness.
- Limited lifetime deck, deck cradle and engine deck warranty.
- Adjustable front lip optimizes cutting for varying conditions and grass types.





Deep deck design with patent pending Air-Gap baffles increases airflow, delivers a pristine cut, and provides a cleaner deck at the end of the day.



Clean Finish—Powerful airflow aggressively shoots clippings out the extra-large discharge chute.

See the AirFX™ deck in action at [bobcatturf.com/decks](http://bobcatturf.com/decks)



**FIERCELY INDEPENDENT.**



# Predator-Pro™ 7000

## REASONS TO OWN:

### HIGH-PERFORMANCE ENGINE

Kawasaki® FX1000V engine designed to provide major, commercial-grade strength.

### ROTATING BUMPER & HITCH

Access to internal components with the rotating bumper & hitch.

### DUAL FUEL TANKS

Armed with new, 15-gallon capacity, dual fuel tanks.

### COMMERCIAL-GRADE TRANSMISSIONS

Rugged Hydro-Gear® transmission options include Pumps with Wheel Motors or 2-speed ZT-5400 Hydrostatic Transaxles with a transport speed up to 19 MPH.

### DUAL-TUBED FRAME

Larger, robust, ultra-stable, dual-tubed frame for increased durability for traversing even the toughest of turfs.

### BULLNOSE AIRFX™ DECK

61-inch or 72-inch bullnose AirFX™ deck with Air-Gap baffles offers efficient airflow and superior vacuum lift; rugged, cast-iron spindles with double-row bearings assure reliable performance. (See page 4.)

### OPTIMUM USER EXPERIENCE

Comfort, power and performance all within your reach from the center of the deluxe suspension seat, almond-shaped handles and smooth responsive controls.

## WHAT YOU REALLY GET:

All the pro-grade power you can handle and more, to get more jobs done—and done right.

Fast access to get in there, get out and on to the next job.

All the juice you need for hours and hours of unstoppable mowing power.

Getting you from point A to point B faster than ever for more cash in your pocket—plain and simple.

A machine meant to withstand a beating that would send others back to the shop.

Makes grass stand at attention before steel blades cut it down to size.

The kind of ride someone in your position deserves.

Backed by our industry-leading 6-year / 2,750 hour  
MOW WITH CONFIDENCE™ limited warranty.

# THE BEST IN THE BUSINESS







Deck Hand-Lift Assist

Swing-Out  
Bumper

**FIERCELY INDEPENDENT.**



# ProCat™ 6000MX

## & ProCat™ 6000

### REASONS TO OWN:

#### POWERFUL ENGINE PERFORMANCE

Kawasaki® FX series engine options, including FX850V\*, assure peak performance.

#### COMMERCIAL-GRADE TRANSMISSIONS

Hydro-Gear® ZT-4400™ Transaxles or Hydro-Gear® Pumps with Wheel Motors feature ground speeds up to 12 MPH.

#### ROTATING BUMPER & HITCH

Access to internal components with the rotating bumper & hitch.\*

#### BULLNOSE AIRFX™ DECK

Deep-profile, 52- or 61-inch, bullnose AirFX™ deck equipped with rugged, cast-iron spindles with double-row bearings and patent pending Air-Gap baffles. (See page 4.)

#### DUAL-TUBED FRAME

Larger, robust, ultra-stable, dual-tubed frame for increased durability.

#### OPTIMUM USER EXPERIENCE

Comfort, power and performance all within your reach from the center of the deluxe suspension seat, almond-shaped handles and smooth responsive controls.

### WHAT YOU REALLY GET:

The power you need to get the job done, day after day.

A chance to step up your game every time you step on the gas.

A mower so easy to maintain, your kid could do it.

A kicked-up quality of cut, lifting grass so steel blades can cut it down clean as a straight razor.

Virtually indestructible support to mow through the toughest turf with no problem.

Controls and comfort—because you're the only one calling the shots around here.

**Backed by our industry-leading 6-year / 2,750 hour  
MOW WITH CONFIDENCE™ limited warranty.**

\* Available only on the ProCat™ 6000MX.

The MX difference: more horsepower, rotating bumper, 6-spoke wheels, rear hitch.

# BECAUSE YOU'RE IN THIS TO MAKE MONEY





ProCat™ 6000

Deck Hand-Lift Assist



***FIERCELY INDEPENDENT.***



# ProCat™ 5000

## REASONS TO OWN:

### A CHOICE OF ENGINES

Select from proven Briggs & Stratton® Vanguard® or Kawasaki® FX series commercial engines.

### COMMERCIAL-GRADE TRANSMISSION

Equipped with the high-caliber Hydro-Gear® ZT-3400® Hydrostatic Transaxles, featuring ground speeds up to 10 MPH.

### OPTIMUM USER EXPERIENCE

Comfort, power and performance all within your reach from the center of the deluxe suspension seat, almond-shaped handles and smooth responsive controls.

### DUAL FUEL TANKS

Armed with 11-gallon capacity, dual fuel tanks.

### BULLNOSE AIRFX™ DECK

48-, 52-, and 61-inch, bullnose AirFX™ deck equipped with rugged, cast-iron spindles with double-row bearings and patent pending Air-Gap baffles.

## WHAT YOU REALLY GET:

Giving you the power you need to get the job done hour after hour, day after day.

Operations as smooth as the lawn you leave behind.

Built to keep you in charge—and charging forward.

All the juice you need for hours and hours of unstoppable mowing power.

A mower that makes grass stand up and take it when you cut it down to size.

**Backed by our industry-leading 6-year / 2,000 hour  
MOW WITH CONFIDENCE™ limited warranty.**

# BETTER GUTS, MORE GLORY





Deck Hand-Lift Assist

MOW WITH  
**6** YEAR LIMITED  
WARRANTY  
CONFIDENCE

***FIERCELY INDEPENDENT.***



# QuickCat™ 4000

## REASONS TO OWN:

### POWERFUL ENGINE PERFORMANCE

Fully loaded with a powerful Kawasaki® FX series engine.

### TOOL-FREE CONTROLS

Smooth, dampened controls with tool-free, adjustable tracking.

### SERVICEABILITY

Access to internal components with our tethered, removable operator pad.

### DURADECK™ CUTTING SYSTEM

Ruggedly equipped with our heavy-duty 36-, 48-, 52- and 61-inch DuraDeck™ with patent pending Air-Gap baffles featuring cast-iron spindles on the 48-, 52- and 61-inch decks.

### VIBRATION-DAMPENED PLATFORM

Radial-bearing suspension (no mechanical springs) reduces bouncing for a smooth, comfortable ride.

### UNMATCHED STABILITY

Optimal operator-station design and in-frame fuel tank for excellent “center of mass” stability; flip-up operator platform allows walking when necessary.

### DUAL-SPEED CONTROL

Optimized control for you and your crew with 2-speed control—“cut” and “transport.” Also, with adjustable tool-less speed reference bar to set ideal maximum speed for operators.

## WHAT YOU REALLY GET:

The performance you need to power through the workday—because downtime isn't an option.

Your turf. Your terms. You are in control—now more than ever before!

Built like you'd build them with industry-leading serviceability, so you don't have to tinker around and can stay focused when mowing is job one.

One of our most reliable decks to let you tackle even the toughest, tallest turf with ease.

All-day operator comfort.

Stand-on stability and agility on uneven ground and for traversing hills and slopes with ease.

The right speeds for what you need—up to 8 MPH cutting; up to 10.5 MPH transport.

Backed by our industry-leading 6-year / 2,000 hour  
**MOW WITH CONFIDENCE™** limited warranty.

Deck Hand-Lift Assist

# STAND UP TO DOWNTIME







Speed Reference Bar

Flip-Up Operator Platform

MOW WITH  
**6** YEAR LIMITED  
WARRANTY  
CONFIDENCE

**FIERCELY INDEPENDENT.**



# FastCat™ Pro SE

## REASONS TO OWN:

### POWERFUL ENGINE PERFORMANCE

Powered by the precision-designed Kawasaki® FX series engine.

### COMMERCIAL-GRADE TRANSMISSION

Superior transmission capabilities with the durable Hydro-Gear® ZT-3100® Hydrostatic Transaxles, featuring ground speeds up to 8 MPH.

### DURADECK™ CUTTING SYSTEM

Down, dirty and reliable, the 36- and 42-inch DuraDeck™ Cutting System features vacuum lift.

### DUAL FUEL TANKS

Roto-molded, impact-resistant, duel fuel tanks with 9.5-gallon fuel capacity.

### EVC SUSPENSION SEAT

High-back, EVC, spring-dampened suspension seat.

## WHAT YOU REALLY GET:

A level of power that stands up to even the most demanding jobs.

Smooth and steady operation even at your fastest speeds.

A deck that's every bit as bound and determined as you are when it comes to delivering a cut like they've never seen before.

Beat your personal best when it comes to getting work done without taking time to refuel.

The perfect balance of comfort and control to keep you more productive—and profitable.

**Backed by our industry-leading 6-year / 2,000 hour  
MOW WITH CONFIDENCE™ limited warranty.**



# FURIOUS AND FULLY LOADED





MOW WITH  
**6** YEAR LIMITED  
WARRANTY  
CONFIDENCE™

**FIERCELY INDEPENDENT.**



# XRZ™ Pro RS

## REASONS TO OWN:

### POWERFUL ENGINE PERFORMANCE

Fully equipped with a powerful Kawasaki® FX series engine.

### COMMERCIAL-GRADE TRANSMISSION

Superior transmission capabilities with the durable Hydro-Gear® ZT-3400® Hydrostatic Transaxles.

### 10 MPH

Productive ground speeds up to 10 MPH with 23-inch Zero-T drive tires.

### DUAL FUEL TANKS

Rugged, roto-molded, dual fuel tanks with 9.5-gallon capacity.

### PRO-GRADE CUTTING SYSTEM

48-, 52- or 61-inch TufDeck™ Pro Cutting System with professional-grade, 6-bolt, cast-aluminum spindle assemblies.

### OPTIMUM USER EXPERIENCE

Ergonomically engineered performance controls and high-back, full-mechanical suspension seat.

## WHAT YOU REALLY GET:

Inexhaustible power—because there's no rest for the fiercely independent.

Maximum output torque and smooth operation.

A fast track to the best-cut lawn on the block.

Forget wasting time with fueling—this fuel capacity has you covered.

Show the pros how it's done by making your own mark.

A chance to sit back, enjoy the ride and get the job done right.

**Backed by our industry-leading 6-year / 1,200 hour  
MOW WITH CONFIDENCE™ limited warranty.**

# OWN YOUR TURF, ON YOUR TERMS





MOW WITH  
**6** YEAR LIMITED  
WARRANTY  
CONFIDENCE

**FIERCELY INDEPENDENT.**



# XRZ™ Pro

## & XRZ™

### REASONS TO OWN:

#### PROFESSIONAL ENGINE PERFORMANCE

Kawasaki® FX (XRZ™ Pro) and FR (XRZ™) series engines for reliable performance.

#### COMMERCIAL-GRADE TRANSMISSION

Hydro-Gear® ZT-3400® (XRZ™ Pro) or Hydro-Gear® ZT-3100® (XRZ™) Hydrostatic Transaxles deliver ground speeds up to 8 MPH.

#### LARGE FUEL TANK CAPACITY

Rugged, roto-molded, impact-resistant fuel tank with 6-gallon capacity.

#### TOUGH MOWER DECKS

48-, 52- or 61-inch TufDeck™ Pro (XRZ™ Pro) or TufDeck™ (XRZ™) Cutting System with professional-grade, cast-aluminum spindle assemblies.

#### SOLID, TUBULAR FRAME

Lightweight, yet ruggedly constructed, 1.5- x 2.5-inch steel-tube frame.

#### OPTIMUM USER EXPERIENCE

Ergonomically engineered performance controls and high-back, spring suspension seats.

### WHAT YOU REALLY GET:

Reliable, smooth-running, professional-grade engine performance.

Smooth operation and maneuverability to tackle turf faster.

No shortage of fuel to stop you from filling up your schedule.

Exactly what you need when it's time to cut grass down to size.

Unstoppable durability and no frame flexing—no matter what you're up against.

All-day comfort paired with effortless control.

Backed by our industry-leading 6-year / 1,000 hour (XRZ™ Pro) or 600 hour (XRZ™) MOW WITH CONFIDENCE™ limited warranty.

# LET THE JONESES KEEP UP WITH YOU





**XRZ™ Pro**



MOW WITH  
**6** YEAR LIMITED  
WARRANTY  
CONFIDENCE

***FIERCELY INDEPENDENT.***



# CRZ™

## REASONS TO OWN:

### POWERFUL ENGINE PERFORMANCE

Commercial-grade performance with the powerful Kawasaki® FR series engine.

### COMMERCIAL-GRADE TRANSMISSION

Hydro-Gear® ZT-2800® Hydrostatic Transaxles for heavy-duty output torque with productive ground speeds up to 7 MPH.

### HIGH-BACK SEAT

Adjustable, high-back seat with spring-dampened suspension and armrests.

### FUEL TANK

Rugged, roto-molded, impact-resistant fuel tank with 6-gallon capacity.

### SOLID, TUBULAR FRAME

Lightweight, yet ruggedly constructed, 1.5- x 2.5-inch steel-tube frame.

### COMMERCIAL-INSPIRED CUTTING

42-, 48-, 52- and 61-inch TufDeck™ Cutting System with durable, cast-aluminum spindle assemblies.

## WHAT YOU REALLY GET:

More power every time you fire up the mower—job after job.

Smooth and simple operation to temper your tough mower.

Comfort just as good as your lounge so you can sit back, enjoy the ride and get the job done right.

Hours of juice behind you—because you don't rest 'til it's all done right.

Relentless performance on uneven terrain—without any frame flexing.

A mower built to handle everything your lawn dishes out.

**Backed by our industry-leading 5-year / 500 hour  
MOW WITH CONFIDENCE™ limited warranty.**

# MOW LIKE A PRO







***FIERCELY INDEPENDENT.***



# Walk-Behinds

## Commercial 21-Inch Walk-Behind

### REASONS TO OWN:

#### POWERFUL ENGINE PERFORMANCE

Major strength with the all-purpose, compact and lightweight Kawasaki® FJ180V engine.

#### 3-SPEED TRANSMISSION

Productive, 3-speed, rear-wheel drive transmission with 9-inch, cast-aluminum wheels with sealed bearings.

#### CAST-ALUMINUM DECK

Equipped with a rear-discharge, cast-aluminum deck for superior vacuum performance. Edge guard and mulch plug standard.

### WHAT YOU REALLY GET:

The torque you need to take out more jobs—every day.

Models available in zone and blade brake clutch (BBC) start options.

A deck that lasts longer, cuts stronger and resists rust—even after decades of taking on tough turf.

**Backed by our 1-year mower / 3-year engine limited warranty.**

## Hydro-Drive Walk-Behind

### REASONS TO OWN:

#### COMFORT CONTROLS

Available with patented Z-Control™ or SoftGrip™ comfort controls with on-the-go tracking.

#### 6 MPH

Productive ground speeds up to 6 MPH with 16-inch Zero-T drive tires.

#### DURADECK™ CUTTING SYSTEM

Equipped with our heavy-duty DuraDeck™ Cutting System.

### WHAT YOU REALLY GET:

Effortless, zero-turn maneuverability within your reach.

Time to walk the walk with speeds that give you only one choice, to get more jobs done and done faster.

Handle anything Mother Nature throws your way—and so can your machine.

**Backed by our industry-leading 3-year / 2,500 hour  
MOW WITH CONFIDENCE™ limited warranty.**



Commercial  
21-Inch Walk-Behind

# FINISH THE JOB RIGHT



## Gear-Drive Walk-Behind

### REASONS TO OWN:

#### COMFORT CONTROLS

Comfortable handling with intuitive SoftGrip™ controls.

#### 5.1 MPH

Productive ground speeds up to 5.1 MPH with 13-inch Zero-T drive tires.

#### DURADECK™ CUTTING SYSTEM

Equipped with our heavy-duty 32-, 36- or 48-inch DuraDeck™ Cutting System.

### WHAT YOU REALLY GET:

Finally, the level of comfort you deserve in a walk-behind.

You set a new pace for workdays. Let the rest try to keep up with you.

The only clean cut you've ever cared about.

Backed by our industry-leading 3-year / 2,500 hour  
**MOW WITH CONFIDENCE™** limited warranty.



Gear-Drive  
Walk-Behind

Hydro-Drive  
Walk-Behind

**FIERCELY INDEPENDENT.**



# LEAVE NO TRACE

## IT'S A DIRTY JOB, BUT SOMEONE'S GOTTA DO IT.

Going in there and getting your hands dirty is part of the job, but our BOSS-Vac™ Collection Systems make cleanup effortless and efficient, so you can move on to the next lawn leaving nothing but the best cut ever seen. Designed especially for Predator-Pro™ 7000 and ProCat™ series mowers, these debris collectors let any pro leave a striking finish.





BOB-CAT® Parts & Accessories							
	Predator-Pro™ 7000	ProCat™ 6000MX, 6000, 5000	QuickCat™ 4000	FastCat™ Pro SE	XRZ™ Pro RS, XRZ™ Pro, XRZ™	CRZ™	Walk-Behinds
Mulching Baffle Kit: Eliminator Blades	61"	✓	✓	36", 52", 61"	✓	48", 52", 61"	✓
Mulching Baffle Kit: Medium Lift Blades				42"		42"	
Eco Plate	✓	✓	✓	✓	✓	✓	✓
Grass Catcher: Poly-Dump, 3.75 or 5.0 bushel	61"	✓	✓	✓	✓	✓	✓
Grass Catcher: Metal, Jumbo, Easy-Dump, 4.3 cu ft							✓
Weight Kit							36", 48", 52"
Hydro Cold-Start Kit			36", 48", 52"				✓
BOSS-Vac™ Pro 12-bushel Collection System	✓	6000 and 6000MX					
BOSS-Vac™ 8-bushel Collection System	61"	✓					
ZT Hitch Kit		5000 and 6000		✓	✓		
No-Flat Caster Wheel Options		✓	✓	✓	✓	✓	
61-inch Wide Track Kit: Widens Track on Unit	✓	✓					
Magnetic Light Kit, 12V	✓	✓	✓	✓	✓	✓	
Striping Kit	61", 72"	48", 52", 61"					
Light Kit, Footplate		✓					
Operator-Controlled Discharge Chute (OCDC)	✓	✓	✓				

MY MOWER DESERVES  
THE BEST

***FIERCELY INDEPENDENT.***



## Predator-Pro™ 7000

MODEL NUMBER	9997002	9997003	9997001	9997004
ENGINE				
Model	Kaw FX1000V	Kaw FX1000V	Kaw FX1000V	Kaw FX1000V
Displacement (cc)	999	999	999	999
Fuel Capacity (gal)	15	15	15	15
Air Filter	Canister Air Filter			
ELECTRICAL				
Charging System (amp)	15	15	15	15
Clutch (ft lb)	250	250	250	250
DECK				
Mower Deck	AirFX™ Cutting System			
Leading Edge	Adjustable, Front Lip Standard			
Width (in)	61	72	61	72
Adjustable Anti-Scalp Rollers	6	7	6	7
Cutting Height (in)	1–5.5	1–5.5	1–5.5	1–5.5
Blade Tip Speed	18500 fpm @ 3550 Engine rpm	18152 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm	18152 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer			
FRAME				
Front & Rear	Welded, 0.25-inch, 7-gauge Steel; 1.5- x 2.5-inch Steel Tubing			
Machine Length (in)	87	87	87	87
Machine Weight—Wet (lb)	1618	1659	1500	1541
TRANSMISSION				
Type	HG Pumps with HG Wheel Motors		HG ZT-5400 2-Speed Hydrostatic Transaxles	
Pump Displacement (cc)	16	16	16	16
Oil Capacity (qt)	9	9	5.9 each	5.9 each
Forward Speed (mph)	0–15	0–15	0–19*	0–19*
Reverse Speed (mph)	0–5	0–5	0–7.5**	0–7.5**
WHEELS				
Drive Wheel Size	26 x 12.0–12, 6-Spoke	26 x 12.0–12, 6-Spoke	26 x 12.0–12, 6-Spoke	26 x 12.0–12, 6-Spoke
Front Caster Wheel Size	15 x 6.5–6, No-Flat	15 x 6.5–6, No-Flat	15 x 6.5–6, No-Flat	15 x 6.5–6, No-Flat
Caster Arm Attachment	Bolt-On	Bolt-On	Bolt-On	Bolt-On
SEAT				
Description	Extra-High Back, Full-Mechanical Suspension Seat			
Fore-Aft Adjustment	Seat Slide Lever			
WARRANTY				
6-year / 2,750 hour MOW WITH CONFIDENCE™ limited warranty				

\* 0–13 mph cutting; 13–19 mph transport

\*\* 0–5 mph cutting; 5–7.5 mph transport



ProCat™ 6000MX		
MODEL NUMBER	9996005	9996006
ENGINE		
Model	Kaw FX850V	Kaw FX850V
Displacement (cc)	852	852
Fuel Capacity (gal)	15	15
Air Filter	Canister Air Filter	
ELECTRICAL		
Charging System (amp)	15	15
Clutch (ft lb)	225	225
DECK		
Mower Deck	AirFX™ Cutting System	
Leading Edge	Adjustable, Front Lip Standard	
Width (in)	61	61
Adjustable Anti-Scalp Rollers	6	6
Cutting Height (in)	1–5.5	1–5.5
Blade Tip Speed	18500 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer	
FRAME		
Front & Rear	Welded, 0.25-inch, 7-gauge Steel; 1.5- x 2.5-inch Steel Tubing	
Machine Length (in)	83	83
Machine Weight—Wet (lb)	1464	1517
TRANSMISSION		
Type	HG ZT-4400 Hydrostatic Transaxles	HG Pumps with HG Wheel Motors
Pump Displacement (cc)	12	12
Oil Capacity (qt)	4.5 each	9
Forward Speed (mph)	0–12	0–11
Reverse Speed (mph)	0–4	0–4
WHEELS		
Drive Wheel Size	24 x 12.0–12, 6-Spoke	24 x 12.0–12, 6-Spoke
Front Caster Wheel Size	13 x 6.5–6	13 x 6.5–6
Caster Arm Attachment	Bolt-On	Bolt-On
SEAT		
Description	High-Back, Full-Mechanical Suspension Seat	
Fore-Aft Adjustment	Seat Slide Lever	
WARRANTY	6-year / 2,750 hour MOW WITH CONFIDENCE™ limited warranty	



## ProCat™ 6000

MODEL NUMBER	9996001	9996003	9996002	9996004
ENGINE				
Model	Kaw FX730V	Kaw FX730V	Kaw FX801V	Kaw FX801V
Displacement (cc)	726	726	852	852
Fuel Capacity (gal)	15	15	15	15
Air Filter	Canister Air Filter			
ELECTRICAL				
Charging System (amp)	15	15	15	15
Clutch (ft lb)	225	225	225	225
DECK				
Mower Deck	AirFX™ Cutting System			
Leading Edge	Adjustable, Front Lip Standard			
Width (in)	52	52	61	61
Adjustable Anti-Scalp Rollers	6	6	6	6
Cutting Height (in)	1–5.5	1–5.5	1–5.5	1–5.5
Blade Tip Speed	18586 fpm @ 3550 Engine rpm	18586 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer			
FRAME				
Front & Rear	Welded, 0.25-inch, 7-gauge Steel; 1.5- x 2.5-inch Steel Tubing			
Machine Length (in)	83	83	83	83
Machine Weight—Wet (lb)	1427	1371	1477	1421
TRANSMISSION				
Type	HG Pumps with HG Wheel Motors	HG ZT-4400 Hydrostatic Transaxles	HG Pumps with HG Wheel Motors	HG ZT-4400 Hydrostatic Transaxles
Pump Displacement (cc)	12	12	12	12
Oil Capacity (qt)	9	4.5 each	9	4.5 each
Forward Speed (mph)	0–11	0–12	0–11	0–12
Reverse Speed (mph)	0–4	0–4	0–4	0–4
WHEELS				
Drive Wheel Size	24 x 10.5–12	24 x 10.5–12	24 x 10.5–12	24 x 10.5–12
Front Caster Wheel Size	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6
Caster Arm Attachment	Bolt-On	Bolt-On	Bolt-On	Bolt-On
SEAT				
Description	High-Back, Full-Mechanical Suspension Seat			
Fore-Aft Adjustment	Seat Slide Lever			
WARRANTY				
6-year / 2,750 hour MOW WITH CONFIDENCE™ limited warranty				



ProCat™ 5000					
MODEL NUMBER	9995010	9995011	9995012	9995008	9995009
ENGINE					
Model	B&S Vanguard 24hp	B&S Vanguard 24hp	B&S Vanguard 26hp	Kaw FX730V	Kaw FX801V
Displacement (cc)	724	810	810	726	852
Fuel Capacity (gal)	11	11	11	11	11
Air Filter	Canister Air Filter				
ELECTRICAL					
Charging System (amp)	15	15	15	15	15
Clutch (ft lb)	200	200	200	200	200
DECK					
Mower Deck	AirFX™ Cutting System				
Leading Edge	Adjustable, Front Lip Standard				
Width (in)	48	52	61	52	61
Adjustable Anti-Scalp Rollers	6	6	6	6	6
Cutting Height (in)	1–5.5	1–5.5	1–5.5	1–5.5	1–5.5
Blade Tip Speed	17800 fpm @ 3550 Engine rpm	18586 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm	18586 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer				
FRAME					
Front & Rear	Welded, 0.25-inch, 7-gauge Steel; 1.5- x 2.5-inch Steel Tubing				
Machine Length (in)	83	83	83	83	83
Machine Weight—Wet (lb)	1253	1267	1318	1267	1318
TRANSMISSION					
Type	HG ZT-3400 Hydrostatic Transaxles				
Pump Displacement (cc)	12	12	12	12	12
Oil Capacity (qt)	2.5	2.5	2.5	2.5	2.5
Forward Speed (mph)	0–10	0–10	0–10	0–10	0–10
Reverse Speed (mph)	0–4	0–4	0–4	0–4	0–4
WHEELS					
Drive Wheel Size	24 x 8.5–12	24 x 10.5–12	24 x 10.5–12	24 x 10.5–12	24 x 10.5–12
Front Caster Wheel Size	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6
Caster Arm Attachment	Bolt-On	Bolt-On	Bolt-On	Bolt-On	Bolt-On
SEAT					
Description	High-Back, Full-Mechanical Suspension Seat				
Fore-Aft Adjustment	Seat Slide Lever				
WARRANTY		6-year / 2,000 hour MOW WITH CONFIDENCE™ limited warranty			



## QuickCat™ 4000

MODEL NUMBER	912360	912480	912520	912610
ENGINE				
Model	Kaw FX600V	Kaw FX651V	Kaw FX691V	Kaw FX730V
Displacement (cc)	603	726	726	726
Fuel Capacity (gal)	5.1	6.5	6.5	6.5
Air Filter	Dual Element			
ELECTRICAL				
Charging System (amp)	15	15	15	15
Clutch (ft lb)	125	200	200	200
DECK				
Mower Deck	DuraDeck™ Cutting System			
Leading Edge	Adjustable, Front Lip Standard			
Width (in)	36	48	52	61
Adjustable Anti-Scalp Rollers	3	4	4	7
Cutting Height (in)	1.5–4.5	1.5–4.5	1.5–4.5	1.5–4.5
Blade Tip Speed	17600 fpm @ 3550 Engine rpm	17800 fpm @ 3550 Engine rpm	18586 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer			
FRAME				
Front & Rear	Welded, 7-gauge Steel; 1.5- x 2.5-inch Steel Tubing			
Machine Length (in)	64	64	64	68
Machine Weight—Wet (lb)	800	961	991	1028
TRANSMISSION				
Type	HG ZT-3100 Hydrostatic Transaxles		HG ZT-3400 Hydrostatic Transaxles	
Pump Displacement (cc)	10	12	12	12
Oil Capacity (qt)	4	4	4	4
Forward Speed (mph)	0–9	0–10.5	0–10.5	0–10.5
Reverse Speed (mph)	0–3.5	0–3.5	0–3.5	0–3.5
WHEELS				
Drive Wheel Size	20 x 8.0–10	23 x 8.5–12	23 x 10.5–12	23 x 10.5–12
Front Caster Wheel Size	11 x 4.0–5	13 x 5.0–6	13 x 5.0–6	13 x 5.0–6
Caster Arm Attachment	Bolt-On	Bolt-On	Bolt-On	Bolt-On
OPERATOR PLATFORM				
Adjustment	Flip Up and Latch			
Rider Pad	Tethered, Removable for Service			
Vibration Isolation	Dampened			
WARRANTY	6-year / 2,000 hour MOW WITH CONFIDENCE™ limited warranty			



FastCat™ Pro SE		
MODEL NUMBER	942297	942302
ENGINE		
Model	Kaw FX541V	Kaw FX600V
Displacement (cc)	603	603
Fuel Capacity (gal)	9.5	9.5
Air Filter	Canister Air Filer	
ELECTRICAL		
Charging System (amp)	15	15
Clutch (ft lb)	125	125
DECK		
Mower Deck	DuraDeck™ Cutting System	
Leading Edge	Adjustable, 2 Positions	
Width (in)	36	42
Adjustable Anti-Scalp Rollers	0	2
Cutting Height (in)	1.5–4.875	1.5–4.875
Blade Tip Speed	18142 fpm @ 3550 Engine rpm	18809 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer	
FRAME		
Front & Rear	Welded, 7-gauge Steel; 1.5- x 2.5-inch Steel Tubing	
Machine Length (in)	79	79
Machine Weight—Wet (lb)	705	744
TRANSMISSION		
Type	HG ZT-3100 Hydrostatic Transaxles	
Pump Displacement (cc)	10	10
Oil Capacity (qt)	4	4
Forward Speed (mph)	0–8	0–8
Reverse Speed (mph)	0–3.5	0–3.5
WHEELS		
Drive Wheel Size	20 x 6.5–10	20 x 8.0–10
Front Caster Wheel Size	11 x 4.0–5	11 x 4.0–5
Caster Arm Attachment	Bolt-On	Bolt-On
SEAT		
Description	High-Back, EVC Spring-Dampened Suspension Seat	
Fore-Aft Adjustment	Seat Slide Lever	
WARRANTY	6-year / 2,000 hour MOW WITH CONFIDENCE™ limited warranty	



XRZ™ Pro RS				XRZ™ Pro		
Model Number	942630	942631	942632	942620	942621	942622
ENGINE						
Model	Kaw FX651V	Kaw FX691V	Kaw FX730V	Kaw FX651V	Kaw FX691V	Kaw FX730V
Displacement (cc)	726	726	726	726	726	726
Fuel Capacity (gal)	9.5	9.5	9.5	6	6	6
Air Filter	Dual-Stage Canister			Dual Element		
ELECTRICAL						
Charging System (amp)	15	15	15	15	15	15
Clutch (ft lb)	125	125	125	125	125	125
DECK						
Mower Deck	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts					
Leading Edge	Adjustable, Front Lip Standard					
Width (in)	48	52	61	48	52	61
Adjustable Anti-Scalp Rollers	3	3	7	3	3	7
Cutting Height (in)	1.5–4.875	1.5–4.875	1.5–4.875	1.5–4.875	1.5–4.875	1.5–4.875
Blade Tip Speed	17365 fpm @ 3550 Engine rpm	18142 fpm @ 3550 Engine rpm	18809 fpm @ 3550 Engine rpm	17365 fpm @ 3550 Engine rpm	18142 fpm @ 3550 Engine rpm	18809 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer					
FRAME						
Front & Rear	Welded, 7-gauge Steel; 1.5- x 2.5-inch Steel Tubing					
Machine Length (in)	76	76	79	76	76	79
Machine Weight—Wet (lb)	773	789	832	758	774	817
TRANSMISSION						
Type	HG ZT-3400 Hydrostatic Transaxles					
Pump Displacement (cc)	12	12	12	12	12	12
Oil Capacity (qt)	4	4	4	4	4	4
Forward Speed (mph)	0–10	0–10	0–10	0–8	0–8	0–8
Reverse Speed (mph)	0–3.5	0–3.5	0–3.5	0–3.5	0–3.5	0–3.5
WHEELS						
Drive Wheel Size	23 x 10.5–12	23 x 10.5–12	23 x 10.5–12	22 x 11.0–10	22 x 11.0–10	22 x 11.0–10
Front Caster Wheel Size	13 x 6.5–6	13 x 6.5–6	13 x 6.5–6	13 x 5.0–6	13 x 5.0–6	13 x 5.0–6
Caster Arm Attachment	Welded to Frame	Welded to Frame	Welded to Frame	Welded to Frame	Welded to Frame	Welded to Frame
SEAT						
Description	High-Back, Full-Mechanical Suspension Seat			High-Back, Spring Suspension Seat		
Fore-Aft Adjustment	Seat Slide Lever					
WARRANTY						
6-year / 1,200 hour MOW WITH CONFIDENCE™ limited warranty				6-year / 1,000 hour MOW WITH CONFIDENCE™ limited warranty		



XRZ™				CRZ™			
MODEL NUMBER	942610	942611	942612	942607	942604	902605	902606
ENGINE							
Model	Kaw FR651V	Kaw FR691V	Kaw FR730V	Kaw FR651V	Kaw FR651V	Kaw FR651V	Kaw FR691V
Displacement (cc)	726	726	726	726	726	726	726
Fuel Capacity (gal)	6	6	6	6	6	6	6
Air Filter	Dual Element						
ELECTRICAL							
Charging System (amp)	15	15	15	15	15	15	15
Clutch (ft lb)	125	125	125	105	105	105	125
DECK							
Mower Deck	TufDeck™ 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts						
Leading Edge	Adjustable, 2 Positions						
Width (in)	48	52	61	42	48	52	61
Adjustable Anti-Scalp Rollers	3	3	7	2	3	3	7
Cutting Height (in)	1.5–4.875	1.5–4.875	1.5–4.875	1.5–4.875	1.5–4.875	1.5–4.875	1.5–4.875
Blade Tip Speed	17365 fpm @ 3550 Engine rpm	18142 fpm @ 3550 Engine rpm	18809 fpm @ 3550 Engine rpm	18809 fpm @ 3550 Engine rpm	17365 fpm @ 3550 Engine rpm	18142 fpm @ 3550 Engine rpm	18809 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer						
FRAME							
Front & Rear	Welded, 7-gauge Steel; 1.5- x 2.5-inch Steel Tubing						
Machine Length (in)	76	76	79	76	76	76	79
Machine Weight—Wet (lb)	736	752	795	684	736	752	795
TRANSMISSION							
Type	HG ZT-3100 Hydrostatic Transaxles			HG ZT-2800 Hydrostatic Transaxles			
Pump Displacement (cc)	10	10	10	10	10	10	10
Oil Capacity (qt)	4	4	4	4	4	4	4
Forward Speed (mph)	0–8	0–8	0–8	0–7	0–7	0–7	0–7
Reverse Speed (mph)	0–3.5	0–3.5	0–3.5	0–3	0–3	0–3	0–3
WHEELS							
Drive Wheel Size	22 x 11.0–10	22 x 11.0–10	22 x 11.0–10	20 x 8.0–10	20 x 10.0–10	20 x 10.0–10	20 x 12.0–10
Front Caster Wheel Size	13 x 5.0–6	13 x 5.0–6	13 x 5.0–6	13 x 5.0–5	13 x 5.0–5	13 x 5.0–5	13 x 5.0–5
Caster Arm Attachment	Welded to Frame	Welded to Frame	Welded to Frame	Welded to Frame	Welded to Frame	Welded to Frame	Welded to Frame
SEAT							
Description	High-Back, Spring Suspension Seat						
Fore-Aft Adjustment	Seat Slide Lever						
WARRANTY							
6-year / 600 hour MOW WITH CONFIDENCE™ limited warranty				5-year / 500 hour MOW WITH CONFIDENCE™ limited warranty			



Commercial 21-Inch Walk-Behind		
MODEL NUMBER	922106	922107
ENGINE		
Model	Kaw FJ180V	Kaw FJ180V
Engine Shaft	25mm Crankshaft—Zone Start	7/8 in Crankshaft—BBC
Fuel Capacity (gal)	0.48	0.48
DECK		
Mower Deck	Cast-Aluminum, High-Vacuum, Rear-Discharge, Steel Edge Guards	
Width (in)	21	21
Cutting Height (in)	1–4	1–4
Discharge Chute	Rear-Discharge, Mulch Plug Standard	
Bag	Easy-Lift, Nylon-Mesh, Dust Liner, 2.5 bu (3.1 cu ft) Capacity	
FRAME		
Machine Weight—Wet (lb)	125	130
TRANSMISSION		
1st Gear Wheel Drive (mph)	2.4	2.4
2nd Gear Wheel Drive (mph)	3.3	3.3
3rd Gear Wheel Drive (mph)	4.1	4.1
WHEELS		
Drive Wheel Size	9 x 2.25	9 x 2.25
OPERATOR ZONE		
Handle	1 in Diameter, 1-piece Steel	
Height Adjustment	3 Positions	
WARRANTY		
	1-year mower / 3-year engine limited warranty	

Gear-Drive Walk-Behind			
MODEL NUMBER	932007	933007	934007
ENGINE			
Model	Kaw FS481V	Kaw FS481V	Kaw FS481V
Displacement (cc)	603	603	603
Lubrication	Full-Pressure—Spin-On Oil Filter		
Fuel Capacity (gal)	5	5	5
Air Filter	Dual Element		
ELECTRICAL			
Charging System (amp)	15	15	15
Clutch (ft lb)	125	125	125
DECK			
Mower Deck	DuraDeck™ Cutting System		
Leading Edge	Fabricated, 7-gauge Deck Top Plus 7-gauge Reinforcements and Skirts		
Width (in)	32	36	48
Cutting Height (in)	1.5–4.5	1.5–4.5	1.5–4.5
Blade Tip Speed	17886 fpm @ 3600 Engine rpm	18784 fpm @ 3600 Engine rpm	17886 fpm @ 3600 Engine rpm
Spindle Type	Maintenance-Free with 1-inch Shaft		
Spindle Bearing	Double-Sealed, Precision-Ground Ball Bearings		
Discharge Chute	Flexible Molded Polymer		
FRAME			
Machine Length (in)	78	78	78
Machine Weight—Wet (lb)	400	428	476
TRANSMISSION			
Type	Pearless 5-Speed with Rev Assist		
Forward Speed (mph)	0–5.1	0–5.1	0–5.1
WHEELS			
Drive Wheel Size	13 x 5.0–6, 4-ply	13 x 5.0–6, 4-ply	13 x 5.0–6, 4-ply
Front Caster Wheel Size	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat
WARRANTY			
3-year / 2,500 hour MOW WITH CONFIDENCE™ limited warranty			



## Hydro-Drive Walk-Behind

ELECTRIC START				Z-CONTROL		
MODEL NUMBER	933305	934306	935308	934307	934331	934332
ENGINE						
Model	Kaw FS481V	Kaw FS541V	Kaw FS600V	Kaw FS541V	Kaw FS541V	Kaw FS541V
Lubrication	Full-Pressure—Spin-On Oil Filter					
Displacement (cc)	603	603	603	603	603	603
Fuel Capacity (gal)	5	5	5	5	5	5
Air Filter	Dual Element					
ELECTRICAL						
Charging System (amp)	15	15	15	15	15	15
Clutch (ft lb)	125	125	125	125	125	125
DECK						
Mower Deck	DuraDeck™ Cutting System					
Leading Edge	Fabricated, 7-gauge Deck Top Plus 7-gauge Reinforcements and Skirts					
Width (in)	36	48	52	48	36	48
Cutting Height (in)	1.38–4.63	1.38–4.63	1.38–4.63	1.38–4.63	1.38–4.63	1.38–4.63
Blade Tip Speed	16964 fpm @ 3600 Engine rpm	15315 fpm @ 3600 Engine rpm	16964 fpm @ 3600 Engine rpm	15315 fpm @ 3600 Engine rpm	16964 fpm @ 3600 Engine rpm	15315 fpm @ 3600 Engine rpm
Spindle Type	Maintenance-Free with 1-inch Shaft					
Spindle Bearing	Double-Sealed, Precision-Ground Ball Bearings					
Discharge Chute	Flexible Molded Polymer					
FRAME						
Machine Length (in)	78	78	78	78	78	78
Machine Weight—Wet (lb)	528	582	593	582	488	528
TRANSMISSION						
Type	HG Variable-Displacement Pumps					
Forward Speed (mph)	0–6	0–6	0–6	0–6	0–6	0–6
WHEELS						
Drive Wheel Size	16 x 7.5–8, 4-ply	16 x 7.5–8, 4-ply	16 x 7.5–8, 4-ply	16 x 7.5–8, 4-ply	16 x 7.5–8, 4-ply	16 x 7.5–8, 4-ply
Front Caster Wheel Size	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat	9 x 3.5–4, No-Flat
WARRANTY						
3-year / 2,500 hour MOW WITH CONFIDENCE™ limited warranty						





### THE FREEDOM TO DO IT YOUR WAY

Like you, we don't worry about what others are doing or saying. We don't concern ourselves with popular notions of what a mower *is* or *was*. We only care about what it *can* be—precisely the same way you think about your business, your home, your life. That's why you choose BOB-CAT®. And that's why we work harder each day to meet your approval.

Your local dealer is

One BOB-CAT Lane | P.O. Box 0469  
Johnson Creek, WI 53038-0469  
1.866.469.1242 | [bobcatturf.com](http://bobcatturf.com)



©2019 Schiller Grounds Care, Inc. All rights reserved.  
P/N 900001A 12/2018